

OPTIMIZATION OF VERTICAL HANDOVER DECISION BASED STRATEGIES IN WIRELESS OVERLAY NETWORKS

Thesis Submitted For the Award of the Degree of

DOCTOR OF PHILOSOPHY

in

Electronics and Communication Engineering

By

Keshav Jha

Registration Number:11617079

Supervised By

Dr. Akhil Gupta(20239)

Electronics and Electrical Engineering (Associate Professor)

Lovely Professional University



**LOVELY PROFESSIONAL UNIVERSITY
PUNJAB
2022**

DECLARATION

I, hereby declared that the presented work in the thesis entitled “Optimization of Vertical Handover Decision based strategies in wireless overlay Networks “ in fulfilment of degree of **Doctor of Philosophy (Ph.D.)** is outcome of research work carried out by me under the supervision Dr. Akhil Gupta working as Associate Professor in the _School of Electrical and Electronics Engineering of Lovely Professional University, Punjab, India. In keeping with general practice of reporting scientific observations, due acknowledgements have been made whenever work described here has been based on findings of other investigator. This work has not been submitted in part or full to any other University or Institute for the award of any degree.



(Signature of Scholar)

Name of the scholar: KeshavJha

Registration No.: 11617079

Department/school:SEEE

Lovely Professional University,

Punjab, India



(Signature of the Ph.D. Supervisor)

CERTIFICATE

This is to certify that the work reported in the Ph.D. thesis entitled “Optimization of Vertical Handover Decision based strategies in wireless overlay Networks” submitted in fulfillment of the requirement for the reward of degree of **Doctor of Philosophy (Ph.D.)** in the School of Electrical and Electronics Engineering is a research work carried out by _KeshavJha_, (Registration No.) 11617079, is bonafide record of his original work carried out under my supervision and that no part of thesis has been submitted for any other degree, diploma or equivalent course.



Dr. AKHIL GUPTA

Assistant Professor

School of Electronics and Electrical Engineering

Faculty of Technology and Sciences

University,

Phagwara, Kapurthala-182320 (Punjab)

ABSTRACT

During the most recent couple of many years, remote advancements have encountered a change in perspective by moving towards the mix and coordination of various radio access innovations to shape the Heterogeneous Wireless Network (HWN). The motivation behind coordinating the autonomous organizations is to receive the expected rewards of heterogeneity regarding consistent availability with high information rate, asset use and better Quality of Service (QoS). Because of the assorted attributes of heterogeneous organizations like data transmission, cost, inactivity and the inclusion territory, a few difficulties must be tended to regarding QoS, versatility the executives and client inclinations. In any case, a heterogeneous remote climate is fundamental to fulfill the unique requests of versatile clients.

In this unique situation, there is a requirement for an effective Vertical Handover Decision (VHD) component to change starting with one organization then onto the next organization to give portable clients bound together and ceaseless administrations, including consistent network and universal assistance access. The VHD includes the mix of handover inception and Network Selection measure. The organization choice interaction is a focal segment for making VHD for a portable client in heterogeneous climate. The organization determination choice is a difficult errand, since it includes the quantity of static and dynamic boundaries as choice measurements and it deals with an intricate issue while forming the effect of these measurements on the QoS, client inclinations and portability qualities.

This investigation presents the plan of a client driven versatility based assistance situated organization choice methodology to offer omnipresent remote access in heterogeneous climate. This exploration work proposes an organization determination procedure dependent on half breed utilization of Cuckoo Search calculation and Genetic Algorithm to offer great types of assistance with least expense to the portable client in a multi innovation, multi interface and multi client climate. Utility worth decides the capacity of the organization to fulfill the QoS prerequisites of utilization.

At the point when the Mobile Terminal (MT) moves with high speed, it is important to discover how long the MT stays in the objective organization. Versatile limit is likewise determined with change in the MT speed to lessen the quantity of handovers. On the off chance that the assessed time is not exactly the versatile home time edge,

handoff to such an organization isn't gainful, as it requires more number of handoff to finish the continuous help. The proposed plot is executed for a client moving with a steady speed. The strategies utilized in the writing depend on the customary methodologies between the section and leave points of MT at the limit of the organization. This strategy for assessment will expand the likelihood of handovers, handover disappointments and pointless handovers.

In any case, the proposed arrangement gives a most extreme effectiveness in any event, when the MT is inside the organization particularly in the covering of organizations. Through Hybrid model of cuckoo and hereditary methodologies it is demonstrated that the proposed versatile limit conspire beats against steady edge plot by diminishing the likelihood of handovers, handover disappointments and superfluous handovers by 25%, 16% and 8% separately for the speed of 40 m/s. Subsequently, consistent edge esteem can't be utilized as a choice measurement to perform handover for high speed clients. The proposed versatile edge conspire keeps the likelihood of handovers, handover disappointments and pointless handovers inside as far as possible.

The proposed network determination procedure is joined in IEEE 802.21 norm, which has indicated Media Independent Handover Function (MIHF) as a bound together interface between connect layer and upper layers to empower the handover interaction free of innovations in incorporated organizations. MIH structure empowers the handover cycle by giving ideal data about the connection quality and organization setting data to the handover module. In the proposed work, MIH structure is stretched out by coordinating its administrations with proposed multiplicative utility capacity and RRT assessment based organization choice plan to get Enhanced MIH (EMIH) system. EMIH based organization determination fuses versatility, administration and client setting to improve the effectiveness of MIH based organization choice procedure. The proposed EMIH based organization determination plot lessens the superfluous handovers and administration interruption time by setting off the handover interaction precisely utilizing both connection layer and application layer data. Matlab reenactment is directed to confirm the presentation of the proposed approach regarding improving the normal throughput by 26%, diminishing the bundle misfortune rate by 36% and lessening the handover delay by 85% contrasted with the current methodologies in the organization choice component, for example, MIH with network choice plans or just setting mindful organization determination plot.

ACKNOWLEDGEMENT

High achievement always takes place in the framework of high expectation. The expectation was there and I begin with determined resolve and put in sustained hardwork. It has been rightly said that every successful individual knows that his or her achievement depends on a community of persons working together but the satisfaction that accompanies the successful completion of any task would be incomplete without the mention of the people who made it possible.


This is to acknowledge with gratitude the guidance and ameliorating suggestion from my supervisor, Dr. Akhil Gupta for his support and motivation throughout the thesis work.

I am grateful to the members of School of Research Degree Programme (RDP) for being in my entire research progress review panel, providing useful suggestions during the period. I am indeed thankful to all anonymous reviewers of my research papers submitted to various International Journal and International conferences, due to which I was indeed able to improve upon the work containing herein.

I am indebted to Honorable Chancellor, Worthy Pro-Chancellor, the Vice Chancellor, and the successive Deans, LPU, for facilitating the administrative issues involved and encouraging me throughout.

I express my heartfelt gratefulness to Head of School, of the School of Electronics and Electrical Engineering, and the staff of Electronics and Electrical Engineering School for their cooperation and support. I am indeed thankful to my colleagues in Department.

Last but not the least, I am thankful to my parents, wife and my children's for their blessing and supported me throughout the long process. I could not have been able to finish it without the full and unconditional support I received.



KESHAV JHA

CONTENTS

	Page No.
Declaration	
Certificate	
Abstract	
Acknowledgement	
Contents	
Abbreviations	
List of Tables	
List of Figures	
1. Introduction	1-31
1.1 Specialized background	1-7
1.1.1 Advancements in wireless communication	1-5
1.1.2 Heterogenous wireless networks	5-7
1.2 Sorts of Handoff	7-13
1.2.1 Vertical Handoff	9-10
1.2.2 Vertical Handoff Operation	10-11
1.2.3 Vertical Handoff criteria and metrics	12-13
1.3 Vertical Handoff decision	13-16
1.4 Motivation and Significance of research	16-20
1.5 Research contributions	20-21
1.6 Research Challenges	21-26
1.7 Research Gap	26-27
1.8 Execution requirements of Vertical Handoff Decision Algorithms	27-29
1.9 Objectives of Research work	29-30
1.10 Proposal Organization	30-31
1.11 Outline	31-31
1.12 Summary	31-31
2. Literature Survey	32-71
2.1 Introduction	32-57
2.2 Organisation Selection Algorithms	57-70
2.2.1 Utility based network selection	58-60

2.2.2 Portability based network selection	60-63
2.2.3 MIH based Network selection	63- 65
2.2.4 Fuzzy Logic and MADM based Network selection	65-70
2.3 Examination issues for proposed solutions	70-71
2.4 Outline	71-71
2.5 Summary	71-71
3. Portability based network selection	72-82
3.1 Overview	72-73
3.2 Role of utility hypothesis in network choice	73-74
3.3 Portability based scenario	74-76
3.4 Overview of Handoff Algorithms	76-82
3.4.1 RSS based algorithms	77-80
3.4.2 Limitations of RSS based algorithms	81-82
3.5 Summary	82-82
4. Cuckoo Search and Genetic Algorithm	83-94
4.1 Introduction	83-84
4.2 Cuckoo search method	84-88
4.2.1 Cuckoo Search	85-85
4.2.2 Levy flights	85-85
4.2.3 Cuckoo search algorithm	86-88
4.3 The Genetic algorithm Scheme	88-94
4.4 Summary	94-94
5. Design of Vertical handoff using hybridization of Cuckoo search and Genetic Algorithm	95-112
5.1 Overview	95-96
5.2 Approach	96-97
5.3 Flowchart of proposed model	96-99
5.4 Proposed Hybrid algorithm	99-101
5.5 Reenactment results	101-112
5.5.1 Reenactment model	101-106
5.5.2 Realization and representation of objectives	106-112
5.6 Summary	112-112

6. Conclusion and Future work	113-117
6.1 Overview	113-113
6.2 Examination contributions	113-115
6.3 Extension to future work	115-117
6.4 Summary	113-113
Rundown of Publications	118-118
Bibliography	119-138

ABBREVIATIONS

ABC	Always Best Connected
AHP	Analytic Hierarchy Process
ARTT	Adaptive Residence Time Threshold
AN	Access Networks
ANS	Automatic Network Selection
CDF	Cumulative Distribution Function
CAM	Context Aware Module
CS	Carrier Sense
CN	Correspondent Node
CR	Consistency Ratio
EMIH	Enhanced MIH
FLC	Fuzzy Logic Controllers
FAHP	Fuzzy Analytic Hierarchy Process
FIS	Fuzzy Inference System
GRA	Grey Relational Analysis
GPRS	General Packet Radio Service
GSM	Global System for Mobile Communication
HNE	Handover Necessity Estimation
HWN	Heterogeneous Wireless Networks
HDM	Handover Decision Module
IP	Internet Protocol
LGD	Link Going Down
LTE	Long Term Evolution
MT	Mobile Terminal

MS	Mobile Station
MADM	Multi Attribute Decision Making
MIH	Media Independent Handover
MIHF	Media Independent Handover Function
MEW	Multiplicative Exponent Weighting
MIES	Media Independent Event Services
MIIS	Media Independent Information Services
MICS	Media Independent Command Services
NGWNs	Next Generation Wireless Networks
NRT	Non- Real Time
NIST	National Institute of Standards and Technology
ND	Network Discovery
NEF	Network Evaluation Factor
PCA	Principal Component Analysis
PRMC	Prioritized Rating for Multiple Criteria
PDF	Probability Distribution Function
PDA	Personal Digital Assistants
QoS	Quality of Service
QoE	Quality of Experience
RS	Router Solicitation
RAT	Radio Access Technologies
RSS	Received Signal Strength
RT	Real Time
RA	Router Advertisement
SAP	Service Access Points
SAW	Simple Additive Weighting

TOPSIS	Technique for Order Preference by Similarity to Ideal Solution
UMTS	Universal Mobile Telecommunications System
VHO V	Vertical Handover
VHD	Vertical Handover Decision
WP	Weighted Product
WiMAX	Worldwide Interoperability for Microwave Access
WLAN	Wireless Local Area Network

LIST OF TABLES

Table No.	Title	Page No.
2.1	An outline of RSS based calculations	33
2.2	A rundown of transmission capacity based calculations	35
2.3	A synopsis of cost work based VHD calculations	37
2.4	A rundown of blend calculations	39
2.5	A relative rundown of the four gatherings.	40
2.6	Outline of existing vertical handover choice procedures	55
4.1	local and global random walk parameters	87
5.1	Simulation parameters	102
5.2	Various boundaries for current PoA	103
5.3	Parametre esteems when MS moves from current PoA	103
5.4	Network parameter values	104
5.5	Comparison of the handoff decision methods	111

LIST OF FIGURES

Figure No.	Caption	Page No.
1.1	Advancements in wireless communication	2
1.2	Handover Process	3
1.3	Heterogeneous wireless environment	5
1.4	Handoff classification tree	7
1.5	Measurements utilized in Vertical Handoff choices	12
1.6	Handover Scenario	14
1.7	Vertical handover decision process	14
1.8	Execution measurements for vertical handover choice	16
2.1	Portability and handoff based techniques	61
5.1	Flowchart of the proposed model	98
5.2	Flowchart of the proposed model	99
5.3	System Model	102
5.4	Comparison of Delay	106
5.5	Comparison of Number of Handoffs	107
5.6	Comparison of throughput	109
5.7	Comparison of handoff failure probability	107

CHAPTER1

INTRODUCTION

1.1 Specialized Background

This part specifies the specialized foundation ideas in heterogeneous systems administration expected to comprehend the motivation behind the investigation of the organization choice methodologies in the vertical handover dynamic cycle. With propels in remote correspondence innovations shaping a group of consistent heterogeneous remote climates, cell phones like PDAs, Personal Digital Assistants (PDAs), tablets and other incorporated portable terminals work with clients to be in every case very much associated anyplace and whenever.

1.1. 1Advancements of Wireless Communication

During the most recent couple of many years, there have been critical improvements in remote organization innovation. As we can see from Figure 1.1, the current patterns and requests in the space of remote innovation are to give and present continuous interactive media applications over heterogeneous remote organizations with ensured Quality of Service (QoS). The client's interest to access such applications and administrations anyplace and whenever is continuously on the ascent. The improvement of new mechanical frameworks, like the Fourth Generation (4G) remote frameworks and their reconciliation, offers these rich types of assistance and applications at high information move rates and offer worldwide meandering and consistent portability through a different scope of heterogeneous remote organizations.

Versatile Stations (MS) in an average 4G organization will be furnished with various interfaces and will have the necessary insight to settle on improved choices to have the option to associate with an assortment of Access Networks (AN) to give rich media administrations. These entrance networks comprise various sorts of cell organizations like Code Division Multiple Access (CDMA), Global System for Mobile Communication (GSM), High-Speed Downlink/Uplink parcel Access (HSDPA/HSUPA), General Packet Radio Services (GPRS), Bluetooth-based Personal Area Network (PAN), IEEE 802.11 Wireless Local Area Network (WLAN), IEEE 802.16 Worldwide interworldwide for Microwave Access (WiMAX), Vehicular Ad-

hoc Network (VANET), and satellite organizations. These remote organizations regularly have covering inclusion in similar help zones and can offer inventive administrations dependent on client requests. A definitive objective of such a climate is to give basic, continuous administrations to an ideal assistant at whenever, autonomous of gadgets, areas, and accessible organizations while additionally keeping up palatable client experience in a practical way.




Fig 1.1 Advancements in wireless communication

The remote advances in a heterogeneous remote organization are typically unique concerning one another from an innovative perspective. The majority of them ordinarily vary as far as their offered data transmissions, working frequencies and expenses, inclusion territories, and latencies. At present there is no single remote innovation that professes to offer savvy types of assistance, which offer high data transmissions and low latencies to all versatile clients in a huge inclusion region. This is the place where the requirement for efficient vertical handoffs (VHOs) between heterogeneous remote advances gets significant. The term 'handoff' or 'handover' alludes to the way toward moving a versatile station starting with one base station or channel and then onto the next. One model is a consistent exchange of a progressing

voice or video discussion from one channel served by a central organization to another.

And more specifically, the hand of correspondence is a way to change the channel, which includes repetition, rate of information, adjustment conspiracies, diffusion codes, or a combination of those related to the current union when the correspondence meeting is taking place. The hand of the cycle can be thought of as two important stages: the hand of initiation and the hand of execution. In the main stage, the mobile station is selected concerning the new base station (BS) or root (AP) option to be moved. During the implementation phase, new radio connections between BS, AP, and MS are configured and assets are specified. The exact outlines of how to hand off the board are given and illustrated in Fig. 1.2.




Fig 1.2 Handover Process

In the course of the most recent decade, the Internet has developed altogether and gone through unprecedented advancement. The presentation of an assortment of new organizational advances and the critical enhancement of conventions and end gadgets have introduced issues and challenges that have not been experienced previously. The answer for one of these problems, versatility for continuous traffic in heterogeneous conditions, can be obtained by utilizing the conceivable outcomes made by conventional IP availability while consenting with application prerequisites. IP the way things are is the ideal decision for "sticking" together heterogeneous remote conditions and thus giving a non-exclusive between working platform. This thesis presents the exploration behind a dream for proficient heterogeneous Internet availability for cell phones and organizations; zeroing in on vertical handovers.

The significant commitment is to give a genuine experience of the proposed arrangements through their viable acknowledgment on a proving ground comprising various remote mediums and associated networks. These arrangements plan to give progressed plans and mechanisms for working between different conventions helped by higher layers, too as enhancements to applications at the sender and receiver. Inter-working plans and instruments represent a test to the current conventions such as the meeting commencement convention (SIP) and versatile IP (MIP) because commonly these protocols are intended to perform assignments in an exceptionally productive way and free of each other. The level of working between conventions is arranged into two categories: free coupling and tight coupling. These coupling strategies are designed and tried through working among MIP and SIP to manage terminal versatility in both arranged and spontaneous handover situations.

The testing uncovers shortcomings in the loose coupling approach, while tight coupling brings about a tradeoff between performance and program intricacy. The tight coupling method is likewise utilized to design, execute and test a handover procedure for another kind of portability called meeting versatility. This procedure tends to three essential difficulties presented by this type of portability in particular: terminal revelation, flagging, and versatility support. Today, vertical handover conventions and instruments are not broadly sent on the Internet despite the accessibility of a wide scope of arrangements. One of the primary reasons for this is

the different ideas of portability systems and conventions carried out in end devices. This variety joined with the absence of bound together between working mechanisms, often makes an inadmissible degree of contradiction among terminals and thus hinders far and wide organization.

1.1.2 Heterogeneous Wireless Networks

The heterogeneity of the remote organizations includes the coordination of assorted Radio Access Technologies (RAT) like Long Term Evolution (LTE), Universal Mobile Telecommunications System (UMTS), General Packet Radio Service (GPRS), Global System for Mobile Communication (GSM), Worldwide Interoperability for Microwave Access (Imax) and Wireless Local Area Network (WLAN) while taking out the requirement for the sending of new advancements as demonstrated in figure 1.3. Figure 1.3 portrays a model situation [1] in which fixed and versatile organizations union, access innovation assembly, application combination, multi-standard gadget union, and so forth, exist together to frame a heterogeneous remote climate. These organizations were initially planned as an independent innovation for explicit help prerequisites and vary for the most part for their upheld advancements, conventions, network structures, and flagging interaction. The reason for incorporating the free organizations is to receive the likely rewards of heterogeneity as far as a consistent network with a high information rate, minimal expense, and improved Quality of Service (Qos).




Fig 1.3 Heterogeneous wireless environment [1]

To undertake the huge improvement of intelligent sight and sound administrations and ever-developing requests of portable clients, remote organizations have been advanced from 1G to 5G. 3G organizations, for example, UMTS are founded on the wide territory network plan. They are not adequate to fulfill the needs of future administrations like sight and sound, remote coordinating, full motion video, and so forth, likewise, single Radio Access Technologies (RAT) can't uphold all kinds of administrations with wide inclusion, high data transfer capacity, and minimal expense. The principal deterrent for the activity of 3G [2] is the improvement of bringing together innovation to join every one of the frequencies in an assembly stage to remove the advantages of different organizations. Consequently, there is a requirement for innovation to improve the presentation of 3G organizations and a requirement for the interworking system to coordinate various advances to give worldwide wandering arrangements proficiently.

To tackle these issues and to offer administrations with ensured Qos, high information rate, minimal expense, and wide inclusion, the current remote organizations are moving towards an all Internet Protocol (IP) based idea in which all information and flagging traffic will be directed through IP on the network layer. Dissimilar to 1G, 2G, and 3G, 4G just as future 5G remote organizations have been focused to give an all-IP based Heterogeneous Wireless Networks (HWN). Hence, the Next Generation Wireless Networks (NGWN) grants clients to get to interactive media applications in every case best-associated mode [3] over an IP spine.

IEEE 802.21 standard [4, 5] has portrayed Media Independent Handover Function (MIHF) as a brought-together interface between the interface layer and upper layers to help consistent availability in multi-interface MT. It works with the handover between IEEE 802 (WLAN, IMAX) and non-IEEE 802 (UMTS/LTE) advancements to offer continuous types of assistance to portable clients across heterogeneous organizations. MIHF comprises three useful administrations like Media Independent Event Services, Media Independent Information Services, and Media Independent Command Services to gather the data from both MT and the organization and to create the conceivable handover setting off occasions. In the proposed work, the MIH structure is reached out by incorporating its administrations with client, administration, and portability setting to give an improved degree of Qos by lessening handover latencies and bundle misfortune rate.

The heterogeneous remote climate is portrayed by its dynamic nature, vulnerability, and ambiguous and uncertain boundaries. Because of this ambiguity, the precise estimation of organization boundaries, for example, information rate, administration cost, network idleness, speed of portable, battery level, and impedance proportion in a remote climate is a difficult errand. As the outcome, it is fundamental to adjust the fluffy rationale control to deal with loose data, which utilizes human knowledge and methods of thinking to offer the best reasonable organization to versatile clients. The fluffy rationale-based Vertical Handover Decision (VHD) calculation [6,7] permits sharp tuning of the uncertain organization boundaries to offer a reasonable tradeoff among different attributes of heterogeneous remote climates.

1. 2Sorts of Handoff

Handoffs can be arranged as depicted beneath:




Fig. 1.4: Handoff classification tree

Level and vertical handoff: Depending on the progress of the participating organization, the handoff can be given evenly or vertically. Also known as traditional handoff, sum, or intra-framework handoff, MS equivalent access occurs when switching between different BS and APs of a network. For example, this usually happens when the client is moving between two geographically adjacent cells of a third-age (3G) cell organization. Again, the vertical handoff or framework handoff consists of two specific organization interfaces representing different remote access companies or innovations, for example, BS in IEEE 802.16 and AP in IEEE 802.11.

Figure 1.4 describes the different types of handoffs available based on different network conditions.

By and large, there are two kinds of vertical handoff: vertical and descending. A vertical handoff is a handoff to a remote underlay with bigger cell size and lower bandwidth. A descending vertical handoff is a handoff to a remote overlay with smaller cell size and bigger data transmission. Along these lines, a cell phone playing out a vertical handoff separates from an organization giving more modest inclusion territory and higher access speed (for instance, WLAN) to another one giving more extensive inclusion however lower access speed (for instance, WWAN), while a cell phone playing out a descending vertical handoff detaches from an organization giving more extensive inclusion region and lower access speed to another one giving restricted inclusion yet higher access speed.

Hard and soft handoff: This type of handoff is based on the number of Bs as well as the MS and AP. Hard handoffs, also known as 'Break before Make', include every BS or AP. MS must serve its affiliation with an existing access network before interfacing with others. Additionally, MS can provide an interface to more than one access network during the hands-off cycle, in a sensitive hand-off also referred to as "Make before Break".

Portable Controlled, Mobile-Assisted, and Network-Controlled Handoff: As the name suggests, these types of handoff order elements are based on MS or Access organization, based on handoff options. The Portable Assisted Handoff is a crossbreed of the versatile controlled and enterprise-controlled Handoff, where it settles on hands-off options in partnership with the MS Entry Organization.

A consistent handoff implies that the progress to the new organization point of connection is transparent to the client (that is, there is no recognizable assistance corruption). It is a handoff that is both quick (low handoff dormancy) and smooth (insignificant bundle misfortune).

In a latent handoff, the client of an MT has no power over the handoff cycle. Passive handoff is the most widely recognized in 2G and 3G remote organizations.

In a proactive handoff, the client is permitted to choose when to handoff. The handoff decision can be founded on inclinations indicated by the client. This kind of handoff is expected to include unmistakably in 4G remote organizations.

1.2. 1Vertical Handoff

Remote organizations, applications, and gadgets have been going through amazing advancement in the course of the most recent decade. On account of the intricacy of the remote climate, no single innovation can be proficient to give portable clients a high information rate and great Quality of Service (QoS) overall circumstances. Without a doubt to satisfy the expanding need of versatile clients, cutting-edge remote frameworks are depending on helpful heterogeneous remote advancements permitting the clients to be associated whenever and anyplace. Heterogeneous remote organizations may consolidate diverse radio access advances including GSM, GPRS, HSPA, UMTS, WiMAX, and even LTE which is turning into the new 4G norm for remote correspondence.

The primary guarantee of the interworking of these heterogeneous networks is to give superior exhibitions by accomplishing a high information rate and supporting video communication, web-based and multicasting with high QoS support and consistent handover. Versatility choices depend on vertical handover choice standards and calculations expecting to guarantee computerized, speedy, and right choices for network choice. Versatility protocols tackle tending to and directing systems including the help of multihoming permitting clients to be all the while associated with different remote organizations.

In a heterogeneous climate, clients will want to pick a blend of several networks to get specific help and save their meetings under different mobile conditions. This part presents the design, practical elements, and protocols that this examination depends on. This design gives portability support over heterogeneous networks. Versatility alludes to the capacity of keeping up with meeting-based services (like ongoing administrations) when managing area change (terminal mobility), job change (individual portability), and changes in gadgets being used (service mobility). The arrangement depends on upgrading a typical IP center organization with mobility

systems just as adding the same help in both the versatile and correspondent has dwelled in outer organizations. IP is utilized as the ideal decision for 'sticking' the different heterogeneous conditions and subsequently giving the nonexclusive interworking platform. The engineering goals are best depicted as far as some of the key moving issues to which they offer arrangements.

Give consistent terminal and meeting versatility across heterogeneous organizations. The recognition and setup of new organization associations are straightforward to the users is the choice of the best organization in the range. Consistent versatility implies making the progress between various kinds of organization straightforward to the application with almost no information misfortune. The client can move between various organizations with the solitary noticeable change being the restrictions of the particular organization interfaces. For instance, the WLAN network upholds high data transfer capacity sound and video while higher rover laid organizations, for example, GPRS may just help the inferior quality sound.

If the client was part of a full sound and video meeting, moving to a higher overlay organization will result in minimizing the sound transfer and ending the video meeting. Achieving seamless vertical handovers includes extra motioning in the structure of configuration and handover messages. It likewise requires communication and coordination between different portability conventions in both the organizations and end gadgets. Backing for dynamic variation of substance, tuning the substance explicitly for the device, the client, and the qualities of the organization association, often considerably diminishing inactivity and parcel misfortune.

1.2. 2Vertical Handoff Operation

Customer flat hand research includes hand-based options based on a manual evaluation of the estimated RSS in MS to assist in the "best connected in every respect" interchange. These traditional handoffs are discontinued when the RSS value of the serving BS falls within a predetermined margin. Again, in a different remote environment, MS can move between different ANs with different utility and features (data transfer capacity, idleness, power consumption, cost, etc.) that cannot be directly analyzed.

Subsequently, in the case of vertical handoff, RSS is not sufficient to settle on productive and effective handoff options; Measurements of other infrastructure, including cost, network load and performance, accessibility, security, and customer orientation should also be considered. Again, the inclusion of multiple dimensions expands the complexity of the vertical handoff options and tests the overall interaction. There are also three stages in the above handoff. The vertical handoff is performed in the following manner:

Observing the current serving organization – getting opportune data and regular refreshes on the situation with the current serving access network together to minimize administration interruption and enhance the nature of administration.

Organization Discovery: A MS with numerous dynamic interfaces can find several wireless organizations dependent on communicated administration commercials from these wireless networks. Notwithstanding, keeping every one of these interfaces dynamic all the time can altogether affect the battery force of the MS.

Handoff Triggering and Decision: This is the stage of choosing when to perform the handoff "when". At this stage, the intended remote access network is selected depending on the different models as described earlier.

Handoff Execution: This is the last period of the upward handoff measurement, where the actual movement of the current meeting takes place. This requires an existing network to transfer instructions and other logical data identified with MS to the newly selected AN as soon as possible.

So upward Handover framework needs to deal with the accompanying:

- Maintaining a network for clients in a hurry.
- Choosing among various access network types dependent on network characteristics, services offered, needs, and client inclinations.
- Preserving key client-driven capacities across limits among networks, devices, and administrations.
- Configurable, power-productive multimode cell phones that can accommodate new remote access advances in an assortment of recurrence groups.
- Dynamic utilization of authorized and unlicensed range.

We accept and trust that the proposed working of portability systems, application upgrades, and most the practical realization of these arrangements, will speed up the far and wide improvement of vertical handovers and make them a necessary piece of the Internet framework of things to come.

1.2. 3Vertical Handoff Criteria and Metrics.

- **Gotten Signal Quality:** This rule is used in straight, straight, and generally flat and vertical handoffs. This organization scale is easy to measure and it is directly related to the course of the application. Similarly, regressions are inversely related to the distance between MS and AP and can lead to excessive and unnecessary handoff.
- **Accessible Bandwidth:** Measured in bits/sec (bps), accessible transmission capacity issued to determine traffic-stacking states of AN, and is a good measure of accessible correspondence assets at the BS.




Fig1.5 :Measurements utilized in Vertical Handoff choices.

- **Organization Connection Duration:** It is a measure of the time that MS connects to a specific AN. This period depends on the position and speed of the MS, which affects its RSS. Due to the different inclusion areas in different remote organizations, the evaluation of this criterion is important to identify

two factors: 1) setting the necessary conditions for timely handoff to have good kvass while minimizing network waste resources and 2) reducing the amount of unnecessary handoff. For example, IEEE 802.11 wastes quick hand-off of network assets from WLAN to 3G cellular networks. On the other hand, postponing the handoff between these companies can lead to handoff disappointments and incoming call drops. Insights, for example, the season of full-time and attending to bring someone else into the company can also be considered a hand-off model.

- **Financial Cost:** Different administrators may work heterogeneous wireless networks and may have fluctuating expenses related to them. The network with the smallest expense ought to be a favored objective of handoff.
- **Handover Delay:** For an MS, handoff inertness is characterized as the elapsed time between the last bundle got from the old AN and the appearance of the first parcel utilizing the new AN after an effective handoff. This metric varies impressively between different heterogeneous remote advancements.
- **Security:** Certain applications necessitate that the privacy, as well as the integrity of the moved information, be protected. This measurement can be utilized to hand off to an organization that offers higher security when contrasted with other available organizations.
- **Force Consumption:** Handoff measure requests a considerable lot of force utilization. On the off chance that an MS was coming up short on battery power, it would be preferable to hand off to an objective a would help broaden the MS's battery life.
- **Speed:** Speed is a significant choice factor as it identifies with the network-association length metric and area of the MS. A MS going extremely fast may bring about inordinate handoffs between remote organizations.

1.3 Vertical Handover Decision

Figure 1.6 outlines the ideas of level and vertical handover measures for the reconciliation of remote organizations. The Vertical Handover (VHO) is the way toward changing starting with one organization and then onto the next organization to meet the necessities of client and administration. A productive versatility of the executives [8] is needed to change the mark of connection without intruding on the assistance. It involves three stages in particular organization disclosure, handover

choice, and handover execution as demonstrated in figure 1.7. Organization revelation measures intermittently screen the organization conditions just as organizations accessible in a given inclusion region. It is additionally liable for gathering the data identified with the organization conditions, client inclinations, and continuous applications on the MT and their Qos prerequisites to cater for insightful determination of the best objective organization [9].




Fig 1.6 Handover Scenario




Fig 1.7 Vertical handover decision process

VHD making is the way toward assessing the applicant organizations to turn out the best reasonable organization for the MT to execute the handover interaction [10, 11]. The VHD cycle chooses when and to which network the handover should be acted in a heterogeneous climate when the client is progressing. The handover choice stage includes the blend of handover inception and organization determination measures

[12]. In HWN, handover is started either consequently or by a solicitation for another association made on the MT.

The handover interaction is set off under the accompanying conditions:

- Whenever Qos offered by the serving network dip under a specific limit level.
- Whenever the distinguished organization offers top caliber and savvy administrations than the serving organization.

The organization determination measure is a focal segment for making VHD for a portable client in a heterogeneous climate. The presentation of the strategies and systems utilized for the organization's determination to perform VHD could be assessed utilizing the measurements, for example, handover rate, the likelihood of pointless handovers, the likelihood of handover disappointments, handover inactivity, throughput and parcel misfortune rate as demonstrated in the figure. 1.8. The organization's choice relies predominantly upon the choice rules since they decide the client fulfillment level to the chosen target network as for Qos and client inclination. The accompanying measurements are summoned to give a total answer for the consistent network in HWN.

- Network-related measurements: Technology type, information rate, inertness, connect quality, Coverage, cost, network burden, and force utilization .
- Terminal-related measurements: Interfaces upheld, speed, battery power.
- Service-related measurements: Qos level – delay, parcel misfortune rate, throughput.
- User-related measurements: client inclinations, which remember the inclination for the expense of administration, Qos, energy utilization, and so on.

The intricacy of dynamic interaction relies upon the kind of choice measurements (static, dynamic) and several measurements considered for the assessment of applicant organizations. Since numerous other options (UMTS, GPRS, GSM, WiMAX, and WLAN) and different traits (information rate, postponement, cost, and force utilization) are considered to improve the precision level of determination choice, choosing an interface gets perplexing in heterogeneous remote climate.




Fig 1.8 Execution measurements for vertical handover choice

When the objective organization is chosen, the handover execution measure is set off. Assuming the chosen network is inaccessible at the hour of handover, the following organization in the rundown is liked as the objective organization. The association arrangement is handled by a portability-the-board convention, for example, MIPv6 at whatever point MT gets across the mix of various RATs. The primary test in the VHD measure is to guarantee that continuous assistance isn't upset during the handover cycle. The focal point of this work is on network checking and network choice interaction, being essential for the handover choice stage.

1.4 Motivation and Significance of the Research

Up until this point, huge exploration has been done to accomplish consistent versatility while an MS gets across various heterogeneous remote organizations. In any case, this examination centers mostly on a significant part of consistent portability: Vertical handoff inceptions and choices. Level handoff choices between homogeneous remote organizations are made essentially based on the Received Signal Strength. Choices for vertical handoffs are normally performed, in light of more than one organization's boundaries, like RSS, MS-Velocity, Security, Cost, and QoS

boundaries. These choices frequently fuse network administrators' approaches and end-client inclinations also. Robotizing these handoff choices in a heterogeneous climate is an unpredictable assignment, contrasted with homogeneous remote organizations, because of a few reasons including differing network attributes, ecological conditions, and versatility designs.

The handoff can be separated into handoff inception, target network choice, and handoff signal preparation. Handoff inception chooses when a handoff ought to be started. The objective of handoff commencement is exactness in planning, to make the handoff. Both early handoff and late handoff are unwanted because an early handoff would prompt a bogus handoff and a late handoff would prompt a handoff disappointment. A bogus handoff would make the second piece of the handoff cycle, target network choice, less productive, and a handoff disappointment would add a colossal burden to the third piece of the handoff interaction, handoff signal handling. To accomplish exactness in the handoff choice, numerous handoff calculations are proposed in writing.

Be that as it may, these calculations overlook network choice, in light of the static boundaries of the organization. Something else, the vast majority of the examination works manage the objective organization choice, disregarding the handoff inception and need assessment that is of equivalent significance. Both ought to be joined to boost the end client's fulfillment. Concerning ongoing interactive media applications, handoffs are a significant obstacle in the way toward consistent portability. One approach to handle this issue is to figure out the versatile station's next passageway, to take proactive measures. The issue of determining a portable station's next passage is known as portability expectation. By applying the forecast technique, the accessible assets in base stations are resolved ahead of time, and afterward, a handoff is made, if essential.

In this manner, the quantity of handoffs is diminished. A significant number of the current handoff calculations don't misuse the advantages of multi-rules and the intrinsic information about the sensitivities of these handoff boundaries in a heterogeneous remote climate. Moreover, while performing vertical handoffs, these calculations don't consider the Qos of a continuous meeting to amplify the end-clients fulfillment dependent on their inclinations, area, and additionally application settings.

Components, similar to the accessible organization transmission capacity, idleness, security, utilization cost, power utilization, battery status of MS, and client inclinations ought to be altogether thought of while playing out these handoff choices. In essentially all the current multi-measures handoff plans, doling out various loads assists with focusing on the organization's boundaries.

More often than not, the task of these loads is done physically without thinking about the amount of weight required for a specific organization boundary. This could prompt a debased handoff execution on the off chance that one boundary is given higher weight esteem when contrasted with another, particularly during a continuous client meeting, like a Voice over Internet Protocol (VoIP) discussion, where accomplishing the base degree of nature of administration is fundamental. In this way, the computation of the right loads for network boundaries is a significant assignment, while working in a heterogeneous remote climate. Besides, practically all handoff plans use fresh qualities for these loads, disregarding the way that the run-of-the-mill upsides of boundaries in a remote organization are not exact, and are portrayed by characteristic vulnerability. Subsequently, to ensure the nature of the presently used help, legitimate weight task, particularly for Qos-related boundaries, is of most extreme significance and ought to be done cautiously. What's more, the fluffy idea of these qualities ought to be remembered, while allotting these loads.

With an excess of administrations, gadgets, and advances, the organization administrators' center is furnishing assorted scope of appealing administrations with required Qos for minimal prices by consolidating the upsides of different organizations. With the expansion of intelligent sight and sound administrations, clients' interest in consistent availability on their MT is likewise expanding to get to administrations with severe Qos necessities like video on-request or high goal TV and to finish each day exercises like work, diversion, and long-range interpersonal communication. In this manner, clients hope to be associated anyplace, whenever to give a worldwide wandering where they will profit by an ideal help conveyance by choosing the best reasonable organization that fulfills their necessities. In this specific circumstance, the primary test for the organization administrator is to offer omnipresent remote access at a better caliber with the least expense for the portable client in a multi-innovation, multi-interface, and multi-client climate [13].

The client portability, heterogeneity of uses (voice, real-time, and information administrations) just as the heterogeneity of cell phones (diverse working frameworks, capacities, battery support, and so on) dispatches the interest for network determination arrangements in HWNs to choose the best appropriate objective organization dependent on the fundamental organization conditions and gadget qualities. In a heterogeneous climate, the dynamic interaction of handover might be incorporated or decentralized (i.e., the handover choice might be made at the organization or MT). In customary organization-driven methodology executed in 3G organizations, for example, UMTS, and Mobile WiMAX 1.0 (IEEE 802.16e), administrators hold firm power over clients to accomplish beneficial asset usage. In any case, NGWNs require client driven methodology in which the clients will approach the accessible assets as indicated by the application Qos, client inclination, and portability attributes [14].

In client-driven methodology, the MT will make the last determination among the combination of various RATs for a given traffic. From this point of view, the client-driven portability based-administration situated organization choice technique is engaged as an examination work in this proposition to track down the best reasonable organization to perform VHD in a heterogeneous climate to appreciate consistent availability and worldwide help access. The powerful requests of portable clients have expanded radically because of client portability, headways of advances, and the selection of new multi-interface gadgets [15]. Accordingly, the clients will expect better-mixed media administrations on their gadgets. In HWN, a client needs to cross the number of accessible organizations to acquire universal assistance access as far as administration congruity and administration quality. Consequently, the client is frequently occupied with a handover activity to hold the continuous associations continuous. The handover is performed not exclusively to keep up help coherence of portable clients yet additionally improving the administration nature of media administrations like voice, video, and E-mail administrations being carried on the IP all the while. Accordingly, it is important to give answers for the difficulties behind the coordination of Qos and versatility attributes for high-speed clients in heterogeneous climates.

From the examination endeavored, when the serving network can't meet the incredible Qos necessities, too as another open association can offer better assistance, the multi-

interface MT will change its relationship among heterogeneous associations. Thusly, how to survey the elective associations and select the ideal one for the MT is central and stays a troublesome issue. It can similarly be seen that a wide extent of factors may impact the overall value of the customer concerning the picked target network: network manager, decision estimations, device characteristics, application (video call, scrutinizing, online shopping, web-based, etc), network ascribes (incorporation region, network conditions) and customer convenience. Thusly, an appropriate interworking plan is relied upon to perform network divulgence and assurance in the coverage area of different RATs to assist predictable accessibility without any obstructions to the convenient customers.

1.5 Research Contributions

In this work, endeavors are made to advance another calculation, which is computationally basic yet unbending, for a proficient vertical handoff choice. We have advanced three calculations. The first is a position-based vertical handoff calculation which is known as Cuckoo Search Algorithm. The second one is likewise a position-based calculation and is known as Genetic Algorithm. The third one is a consolidated calculation of Cuckoo Search and Genetic Algorithm that joins the static boundaries of the organization, for example, cost, accessible data transfer capacity and force utilization, and dynamic boundaries like RSS, speed, and position of the portable station.

Portability expectation assumes a significant part in the productive activity of remote organizations. The unexpected effects of handoffs can be decreased, by knowing ahead of time where the portable station is going. It permits the framework to take proactive measures. Earlier data about the portable station's next objective is helpful in a handoff choice. A strategy for portability expectation, i.e., anticipating the versatile station's next area dependent on Hybrid Model is proposed. Half and half Model indicators can precisely appraise the following area visited by the portable station, given the current and authentic development data. There is a clever and productive plan, which is utilized to play out an effective handoff need assessment and target network choice.

The proposed plot is separated into two sections: In the initial segment, a plan of RSS expectation is proposed, to anticipate whether the portable station draws nearer or away from the current place of connection, and to appraise the need for a handoff. In the subsequent part, various boundaries of all accessible competitor networks are used to decide another mark of connection or an entrance organization, which satisfies the end client's necessities. The organization determination calculation positions the accessible organizations dependent on different rules. The proposed plot is utilized to expand the end client's fulfillment, considering the nature of the help that the end client encounters at the portable station. Coming up next are the principle commitments of this exploration work.

An exhaustive overview of vertical handoff choice calculations in heterogeneous remote organizations is given. A position-based vertical handoff calculation that consolidates the static boundaries of the organization, for example, cost, accessible transfer speed, and force utilization, and dynamic boundaries like RSS, speed, and position of the versatile station, is created. A technique for versatility expectation, i.e., anticipating the portable stations' next area dependent on Hybrid Model, is proposed. A plan dependent on polynomial relapse is intended to anticipate the future upsides of the deliberate RSS, to limit the call-dropping likelihood of the portable station, because of an unexpected drop of the RSS. This plan is additionally used to gauge the need for a handoff.

The Hybrid model calculation is used to exhibit the choice of the best objective organization among other accessible competitor organizations, in light of the deliberate upsides of various boundaries from each organization. Reproduction is done for assessing the presentation of the proposed plans.

1. 6Research Challenges

In the accompanying segment, the upward handover challenges are distinguished and depicted in more itemized. An upward handover is characterized as a handover between heterogeneous types of organizations, for example, networks that utilize various innovations (like WLAN, GPRS, DVB, and UMTS) under various regulatory spaces, empowering the client to use a few of these organizations in equal. This kind of handover is more muddled than a flat one (for example between similar access organizations) and requires cautious thought and comprehension to make the progress straight to the client. From a general viewpoint, the handover ought to give the accompanying.

Firstly, it should uphold ideal setting off and network access determination. Finding the correct chance to play out a handover is a central question.

Just through brief responses can handover be started and performed proficiently. A handover can be set off by the network (for example load adjusting situation) or it could likewise be client started (for example user requesting a handover to a particular organization).

Secondly, both genuine and non-constant applications ought to be upheld. Applications have diverse execution requirements and should be taken care of distinctively during handovers.

Constant applications are sensitive to postpone and bundle misfortune requiring quick and dependable handovers, while TCP-based applications should keep up their end-focuses meeting by giving continuous connection support during handovers. To help vertical handovers, there is a need to trade data through flagging. This flagging may represent a significant overhead as far as transfer speed and preparing necessities, affecting the exhibition of handovers.

Accordingly, a key necessity is to limit the flagging overhead however much as could be expected to improve and streamline the handover performance. Another significant part of vertical handovers is the need to give dependable and transparent handovers. As clients move between network limits, the handover mechanism should empower progress that is straightforward to the application layer with the just apparent change to the client being because of the impediments of the new network interface. Besides, vertical handovers ought to give a shielded instrument for failed handoffs or detachments. Clients may encounter times of separation that can either be short or long enough to cause extreme issues at higher layers. This is also the situation when a handover methodology is started yet neglects to finish. Handover fallback mechanisms ought to be available to help in such situations.

- **Finally, interoperation is an unequally significant test. Vertical handover instruments regularly make the presumption that a few parts of the organizations can be modified (e.g., broadening the taste intermediary worker programming).**

Be that as it may, this may not be true for all organizations. Consequently, this is a significant thought that ought to be taken into account when planning answers for

help vertical handovers, that is to keep interoperation with accessible administrations and advancements we can't adjust. These difficulties emerge principally due to the various qualities of the network technologies. This work centers around a portion of these issues exhaustively and addresses them by utilizing a mix of conventions between working procedures just as charms to applications and conventions dependent on the accompanying design.

Up until now, a critical examination has been done to accomplish consistent portability while an MS gets across various heterogeneous remote organizations. Be that as it may, this examination for the most part centers on a significant part of consistent versatility: vertical handoff inceptions and choices. Flat handoff choices between homogenous remote organizations are made mostly based on Received Signal Strength (RSS), though choices for vertical handoffs are ordinarily performed dependent on more than one organization's parameters. These choices frequently join network-administrators strategies and end-administrators arrangements and end-clients inclinations too.

Robotizing these handoff choices in a heterogeneous climate is a perplexing assignment contrasted with homogenous remote organizations because of different organizational reasons including shifting organization attributes, natural conditions, and portability designs. Large numbers of the current handoff calculations, which depend on single measurements like RSS, don't misuse the advantages of multi-models and the innate information about the sensitivities of these handoff parameters in a heterogeneous remote climate. Furthermore, while performing vertical handoffs, these calculations don't consider the Qos of a progressing meeting to augment the end-clients fulfillment dependent on their inclinations, area, and additionally application settings. Components like accessible organization data transmission, idleness, security, use cost, power utilization, battery status of MS, and client inclinations ought to be thoroughly thought of while playing out these handoff choices. In practically all the current multi-measures handoff plans, relegating various loads focuses on network parameters...

More often than not, the task of these loads is done physically without thinking about the amount of weight required for a specific organization parameter. This could prompt a debased handoff execution if one parameter is given higher weight esteem when contrasted with another, particularly during a continuous client meeting, like

voice-over IP (VoIP) discussions, where accomplishing a base degree of nature of service is fundamental. Subsequently, the estimation of the right loads for network parameters is a significant errand while working in a heterogeneous remote environment. Furthermore, practically all handoff plans use fresh qualities for these loads, overlooking the way that commonplace upsides of parameters in a remote organization are not exact and are portrayed by innate uncertainty. Accordingly, to guarantee the nature of the as-of-now used assistance, an appropriate weight task, particularly for Qos-related parameters, is of the most extreme significance and ought to be done cautiously. Moreover, the fluffy idea of these qualities ought to be remembered while relegating these loads.

The handoff can be isolated into handoff inception and target network determination. A large portion of the exploration work manages the objective organization determination, disregarding the handoff commencement and need assessment that is of equivalent significance, as handoff inception and its need assessment that is of equivalent significance, as handoff commencement and its need assessment assume a basic part in amplifying end-clients fulfillment. Actually like the upsides of loads related to network parameters, the computations to perform handoff need assessment and target network determination are normally done utilizing crude or fresh upsides of parameters given by various organizations, without giving a lot of consideration to the unclarity and fluffiness contained in this data.

Both original portable (simple) and second-era versatile (advanced) systems were planned essentially to offer solitary help, i.e., discourse. They additionally have a limited capability to bring to the table low information rates over voice channels utilizing ordinary modems. Notwithstanding, third-era portable frameworks are required to offer top-notch multimedia (multi-rate administrations) to focalized organizations of the fixed, cell, and satellite components. 4G isn't market or innovation-driven, it is client driven and will have user-controlled administrations. That implies that clients are in charge of their collaborations. As George H. Heilmeier once said, "I think the reality is to bring data age capabilities to everybody, capacities that empower individuals and their machines to access information anyplace, whenever, in any medium or mix of media cost-effectively and securely." To accomplish this vision the accompanying difficulties must be met between the working of fixed and adaptable associations.

- Mobility among heterogeneous access organizations.
- Mobile clients and organization specialists.
- Reconfigurable terminals and organizations.

The initial two difficulties can be acknowledged by IP innovation, the third one by specialist innovation, and the fourth one by utilizing middleware innovation. The main test is that of portability among existing and arising heterogeneous access organizations, both public and private. The advancement of remote and fixed organization access innovation is extending and a few new options will be offered in the following not many years from those giving broadband remote areas of interest (e.g., HIPERLAN 2) to those giving worldwide inclusion (e.g., UMTS, DVB) just as fixed admittance such as DSL. Thus, client interest in persistent availability is expanding regardless of the sort of interface or organization they are utilizing. Giving nonstop availability to aloof kinds of organizations with fixed and remote sections is itself a difficult errand. We accept that there are two central difficulties identified with portability that hamper the acknowledgment of this vision.

The difficulties given by NGWN unmistakably feature the deficiency of customary remote correspondence networks in making availability universal and unavoidable [16]. Giving ideal compromise between boundaries, for example, administration progression, portability of the executives, framework intricacy, and Qos issues in a heterogeneous organization climate would make a few exploration challenges in a multi-interface MT during network determination measure. They are:

- Due to the diverse characteristics of heterogeneous networks such as bandwidth, latency, cost, and coverage, mobile users face the problem in terms of Qos, mobility management, and user preferences during network selection.
- Providing interdependence between different decision criteria while considering both static and dynamic attributes.

Due to the assorted qualities of heterogeneous organizations like data transmission, dormancy, cost, and inclusion, versatile clients dealing with the issue as far as Qos, portability of the board, and client inclinations during network determination.

- Providing association between various choice measures while thinking about both static and dynamic credits.

- Providing sight and sound administrations with ensured Qos .
- Tradeoff between Qos-cost-energy utilization during network choice cycle .
- Maintaining VHO rate, pointless handovers, and handover disappointments inside as far as possible because of capricious versatility attributes (course and speed) .
- Providing ongoing answers to improve the client level Qos like bundle Misfortune rate, handover dormancy, and normal throughput.
- Uncertainty related to elements of remote climate, client versatility, and elements of organization qualities.
- Optimization among consistency and intricacy.

1. 7Research Gap

Vertical handover components have gone through numerous upgrades and numerous new advances have been presented in the course of the most recent couple of years. There are still a few holes requiring further investigation. This part sums up the holes that need further consideration.

(i) When vertical handover happens, giving the necessary Qos across the diverse remote organizations is a significant issue and undeniable degrees of versatility have further difficulties. To ensure the Qos, VHO strategies should cautiously think about client portability and organization conditions to pick the best applicant to arrange and play out a quick handover.

(ii) Guaranteeing the Qos isn't sufficient to offer the most ideal support to clients Quality of Experience (QoE) is an idea that is acquiring significance. It is identified with clients' fulfillment. Giving great systems administration execution need not generally give absolute satisfaction to the end clients. Consequently, there is a need to contemplate client inclinations and portable hardware also while planning VHO systems and methods.

iii) Security is a significant issue that is frequently ignored in systems administration situations. To improve VHO strategies, there is a requirement for joining powerful security arrangements in heterogeneous organizations that would permit security whenever and anyplace.

(iv) In a heterogeneous climate, access networks should be associated in an ideal way to such an extent that the clients are in every case best associated. Notwithstanding, issues identified with the busy organizing including charging and valuing for the utilization of the organizations, the board of other such issues between administrators should be tended to work with the VHO and to ensure QoE just as Quality of Service (Qos). The between-systems administration of these heterogeneous remote organizations has become a difficult and significant space of examination. Diverse access networks including 3GPP (e.g., EDGE, HSPA, UMTS, LTE) and non-3GPP (e.g., WiMAX, Wi-Fi) guidelines should be entomb associated in an ideal way to give clients a decent Qos.

(v) There is an absence of a homogeneous VHO assessment strategy. Hence, a typical approach is required with the goal that the analysts, designers, and clients effectively can think about and assess the different VHO strategies found in the writing. Henceforth, there is a need to deliver standards or rules on great practices for VHO assessment.

1. 8Execution Dependence Of Vertical Handoff Choice Calculations

From the survey, it is uncovered that there is a requirement for a strategy that can make an examination between the different VHO methods proposed and do the assessment of these strategies. Considering this, we propose a strategy to ascertain the VHO record that would give a sign about the adequacy of vertical handoff of the board interaction. This file can be determined dependent on the accompanying standard got from the writing:

(I) Seamless (S): Handover is considered "consistent" when it can keep up the network of all applications running on the cell phone, giving a persistent start-to-finish information administration inside a similar meeting during the switchover, offering both low inertness and insignificant bundle misfortune.

(ii) Packet misfortune (PL): it is a proportion of measure of parcels dropped during VHO measure. Numerically, it tends to be communicated as,

Bundle Loss for vertical handover = $(1 - \text{no. of parcels got}) / \text{Total no. of bundles sent}$
 Here parcel misfortune is determined for the handover period as it were

iii) Throughput (TH): it alludes to the information rate conveyed to the versatile terminals during handover. It is normally attractive to get higher throughput during handover to a specific organization.

(iv) Handover delay (HD): alludes to the span between the commencement and finishing of the handover cycle. More perplexing is the VHO cycle; more handover postponement would be there. Accordingly, for delay-touchy voice or sight and sound meetings, a decrease in the handover delay is significant. Handover delay is the amount of all individual defers engaged with handover. It would thus be able to be composed as:

$T_{\text{handover}} = TL_2 + T_{\text{sig}} + T_d + T_{IP}$; where TL_2 is the time needed to build up layer 2 networks between the versatile hub and passageway or base station of the new passage. T_{sig} is the time needed for trading control messages, T_d is the single direction delay for the information bundle in the new organization, and T_{IP} is the IP address obtaining delay in the new organization.

(v) Number of handovers (h): number of handovers included ought to be low as continuous handovers would cause wastage of organization assets.

(vi) Handover disappointment likelihood (HF): A handover disappointment happens when the handover is started yet the objective organization doesn't have adequate assets to effectively finish it. It is the number of handoffs all through the length of the call at that point, Handover disappointment likelihood is given as:

$1 - (1 - P_{h,j})^h$ where, $P_{h,j}$ means the likelihood that a handoff endeavor for a call of type j is impeded.

(vii) Handover convention overhead (PO): It addresses the amount of overhead made by convention for handover flagging and the overhead of the extra bytes sent with every information parcel.

Along these lines, $PO = \text{Overhead HO} + \text{Overhead AD}$

viii) Vertical handover measure assessment list would give the sign about the propriety and adequacy of the handover interaction. This list can be determined as:

$VHOI = w_s N (S_j) + w_{PL} N (1/PL_j) + w_{TH} N (TH_j) + w_{HD} N (1/HD_j) + w_{HF} N (1/HF_j) + w_{PO} N (1/PO_i)$.

Where, w_s , w_{PL} , w_{TH} , w_{HD} , w_{HF} , and w_{PO} address loads allotted to the previously mentioned rule as per their significance. While $N(I)$ is the standardization capacity of its criterion. Since each organization boundary has an alternate unit, so standardization measure is required.

With this technique, it is feasible to make a quantitative evaluation of the different VHO calculations in writing. The higher the worth of the VHO list got for a specific VHO calculation, the more productive the handover choice cycle. This will be very useful to scientists in choosing whether a given VHO calculation is appropriate for a specific handover climate. Further, VHOI's satisfactory qualities may shift for various classes of traffic types. Concerning occurrence, non-ongoing traffic (for example text information move, email, and so on,) can endure huge postponements, so the high worth of handover delay is average, which suggests low scores for VHOI for such traffic types are satisfactory. While ongoing traffic (for example video and voice) is exceptionally deferred and delicate, so high scores for handover delay are unsatisfactory.

1.9 Objective of the Research Work

To adapt to the blast of broadband information administrations and the staggering development of web clients, an efficient interworking component is proposed to foster an IP-center heterogeneous climate with an intermingling of organizations, administrations, and gadgets. Accordingly, the test for the versatile client is to choose the best reasonable organization to fulfill the consistently developing requests in the heterogeneous climate.

The goal of the proposal is to give answers for the multi-interface MT to identify, select and connect consequently to the objective organization thinking about the heterogeneity of the applications and their necessities, distinctive client inclinations, various gadget qualities, and heterogeneity of various RAT and their attributes. The principle point of convergence of this proposition is giving answers for the difficulties behind the joining of organization determination and portability support. They are:

- **To decrease the postponement during vertical handover**

In a heterogeneous climate, there are likely various up-and-comer networks when the handover choice happens. Subsequently, it is alluring to devise calculations that select the most proficient organization among all competitors as the handover target so the clients can profit by the entrance in an "in every case best associated" mode. So we

utilize a handover target determination technique depending on an expense work which comprises parameters including transfer speed, battery force, and delay. The network with the base expense is chosen as the handover target. This strategy expands the level of client-fulfilled demands and diminished the call-obstructing likelihood.

- **To decrease the quantity of handover**

We utilize the calculation to assess the handover need into a WLAN cell. This technique depends on two sections: voyaging time assessment and time edge estimation. The voyaging time assessment depends on RSS estimations and the speed of the portable terminal. The time limits are determined dependent on different organization parameters, for example, pointless handover probability. This strategy can diminish superfluous handovers by up to 70%.

- **To cut off the handover disappointment likelihood**

In this method, we utilize the calculation for time limit calculation. This calculation contains two sections that plan to limit handover failures. The reason for this time edge computation is to keep the number of handover disappointments under an attractive edge. That is, for instance, if the framework creator has a prerequisite of restricting the likelihood of handover disappointments under 1%, at that point the time edge is acclimated to make the proportion of the quantity of bombed handovers to the all-out number of handovers underneath 1%. The time edge is determined utilizing numerical displaying and likelihood computation which diminishes the number of handover disappointments by up to 80%.

- **To increment the throughput of the organization**

It is critical to limit association breakdowns as handovers happen between these access networks so meeting progression is kept up without recognizable interruptions. Thus the handover setting off condition assessment strategy is acquainted which endeavors to gauge the ideal handover setting off the moment that an MT needs to start a handover back from a WLAN to a cell network. HVHD is conceived to keep the association breakdown likelihood underneath client customizable cutoff points under various MT speeds, just as to furnish the client with authority over the tradeoff between association breakdown likelihood and WLAN utilization.

1.10 Proposal Organization

The excess piece of the proposal is coordinated into six sections as follows:

- **Chapter 2** offers a far-reaching writing audit of related works in the field of organization determination techniques on the accompanying Categories: i) Utility-based ii) Mobility based iii) MIH based iv) Fuzzy and MADM-based calculations and guidelines that help the organization choice cycle.
- **Chapter 3** portrays the different calculations and the restrictions of RSS-based calculations and what is the need for a mixture model of Cuckoo Search and Genetic Algorithm.
- **Chapter 4** portrays the Cuckoo Search Algorithm and Genetic Algorithm. A logical arrangement is dependent on client portability and multi-rules advancement for network choice is proposed.
- **Chapter 5** clarifies the condensation of vertical handoff utilizing hybridization of cuckoo search and Genetic calculation structure in which client, organization, and administration sets are coordinated with MIHF to work with consistent availability with ensured Quality of Service (QoS) and insignificant handover inactivity.
- **Chapter 6** finishes up the postulation with a rundown of exploration commitments with conceivable future work.

1.11 Outline

This part has given a prologue to the upward handoff choice in heterogeneous remote organizations. The principle issues in the plan and execution of a handoff choice are talked about further, featuring the roads wherein this investigation can be made viable. At that point, the part progressed with the commitments of this proposition. Further, it depicted the association of the various sections in this postulation, and lastly, closes with a synopsis of the issues talked about.

1.12 Summary

Wireless communication has evolved over the years and rapid advancements have been done to satisfy the user's requirements owing to environmental fluctuations and traffic scenarios. In this thesis we have talked about how easily we can improve the dynamically changing network technologies and how much work has been done over the years and what are the limitations to these works. That limitations are removed and new methods are evolved that adaptively adjust to user requirements.

CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

Vertical Handover Decision (VHD) calculations are fundamental segments of engineering in the impending NGWNs. These calculations should have been intended to give the necessary Qos to a wide scope of uses while permitting consistent association among more than entrance remote organization advancements. In this section, a thorough study of the VHD calculations intended to fulfill these necessities is introduced. To offer an orderly correlation, the calculations are sorted into four gatherings dependent on the primary handover choice rule utilized. In the NGWN, versatile clients can move between heterogeneous organizations, utilizing MTs with various access interfaces and non-constant or ongoing administrations. The main issue in such a climate is the ABC idea of permitting the best network to applications anyplace whenever. To answer ABC's necessity, different VHD approaches have been proposed in the writing utilizing progressed devices and demonstrated ideas. An survey of the most fascinating and late methodologies is examined in this section.

Zahran et al. [17] introduced in their paper the presentation of vertical handoff utilizing the coordination of 3G cells and remote neighborhoods for instance. Specifically, he examined the impact of an application-put together sign strength limit concerning a versatile favored organization lifetime-based handoff procedure, as far as the flagging burden, accessible transmission capacity, and parcel delay for a between network meandering portable. In this paper an insightful structure to assess the combined framework execution, which is approved by PC reenactment. It has been shown the proposed logical model can be utilized to give plan rules for the advancement of vertical handoff in the cutting edge incorporated remote organizations.

Mohanty et al. [18] discussed the various kinds of handoff in the cutting-edge remote frameworks and the new trend of connecting layer-helped handoff the board convention design. Then, in this paper, he examined the presentation of handoff management protocols that utilize a fixed worth of RSS limit (Sth) to initiate the

handoff cycle. Through his examination, he observed that, when a fixed worth of Sth is utilized, handoff failure likelihood speeds up or handoff signaling defer increments. Utilizing the experiences from examination, he fostered a cross-layer handoff management protocol called CHMP, which gauges the portable's speed and predicts the handoff flagging deferral of conceivable handoffs. CHMP utilizes this data to compute a unique worth of RSS limit (Sath) for handoff commencement.

Yan et al. [19] Vertical handover choice (VHD) calculations are fundamental parts of the architecture of the approaching Fourth Generation (4G) heterogeneous remote organizations. These algorithms need to be intended to give the necessary Quality of Service (Qos) to a wide range of applications while permitting consistent wandering among a large number of access network technologies. In this paper, the creators present an extensive review of the VHD algorithms designed to fulfill these prerequisites. To offer an efficient correlation, creators categorize the calculations into four gatherings dependent on the fundamental handover choice rule utilized. Also, to assess tradeoffs between their intricacy of execution and proficiency, creators discuss three delegate VHD calculations in each gathering.

Table2.1 :An outline of RSS-based calculations

Heuristic	Year	Material Area	Highlight	Benefits	Hindrances
Zahran et al.'s heuristic [17]	2006	Among 3G and WLANs	The RSS is joined with an expected lifetime or the accessible data transfer capacity to choose the handover time	Variation to application necessities and client versatility • Improvement in the accessible data transfer capacity	Long parcel delay • Extra query table
Mohanty and Akyildiz's heuristic [18]	2006	Among 3G and WLANs	A unique RSS limit is determined and looked at with the current RSS to decide the handover time	• Decrease the bogus handover commencement and • handover disappointment probabilities	• Expanded handover disappointment • Wastage of network assets
Yan et al.'s heuristic [19]	2010	Among cellular Networks and WLANs	A powerful time limit is determined and thought about with the anticipated voyaging time inside the WLAN to assist with handover choices	Minimization of the handover disappointment, superfluous handover also, association breakdown probabilities	• Extra handover delay

Lee et al [20] proposed a paper in which the speed versatile handoff calculation is recommended, and the assurance strategy for staggered edge estimates for calculation as per the portable speed is proposed. To dissect VAH calculation in levy qualities, focused on handoff channel task strategy is received. Additionally, the impact of staggered edge quantize is broken down, and the recreation for VAH calculation as far as the traffic execution is acted in the microcell administration region which consists of the rectangular cell. According to the outcomes, Multi-level edge handoff calculation dependent on portable speed address great execution. As the quantity of limit level is expanded, the exhibition of the framework is improved. Additionally, the task of handoff limit level as MAX quantizes addresses preferred execution over that of uniform quantizes.

Yang et al. [21] With the thought of client and framework settings, the proposed vertical delicate handoff calculation (CAVSH) can improve the general heterogeneous remote organizations' performance contrary to the standard flat delicate handoff in WCDMA systems. The consolidated impacts brought by parting the user traffic among multi associations from various access networks prompt below cost to the client traffic as well as permits the framework to help more client traffic even while some BSs and APs are clogged. The proposed CAVSH algorithm likewise gives the framework lower dropping likelihood as well as higher throughput, contrasting, and the vertical hard handoff calculation (CSVH).

Chen et al. [22] proposed in his paper, and contemplated configuration issues and proposed relating answers for offering support nimbleness for versatile hosts in different vertical handoff situations. Utilizing TCP and TFRC as examples, we proposed Implicit Handoff Notification (IHN), a calculation to identify the events of vertical handoffs by inactively observing and assessing the connection limit with installed start to finish assessment apparatuses (for example TCP Probe and TFRC Probe). Start to finish conventions, for example, TCP Probe or TFRC Probe is recommended to recognize the idea of the handoff occasion gauge the measure of progress in interface limit. For versatile frameworks outfitted with a savvy handoff administrator, we purposed the Explicit Handoff Notification (EHN) plot. The handoff chief consequently screens the actual connection characteristics, and triggers handoff

occasions when fitting. EHN expressly notices the continuous applications when/what handoff occasion is going to be produced by the supervisor, empowering the upper layer application to adjust its sending rates likewise.

Table2.2 : A rundown of transmission capacity based calculations

Heuristic	Year	Material Area	Highlights	Benefits	Hindrances
Lee et al.'s heuristic [20]	2007	Among WWANs and WLANs	The data transmission is consolidated with the RSS, framework status also, application type to make handover choices	High framework throughput • Low handover dormancy for continuous transmission	Difficulty in procuring accessible data transfer capacity data • Increased new application obstructing rate
Yang et al.'s heuristic [21]	2008	Among WCDMA and WLANs	The SINR esteems are contrasted with decide the handover choice	High by and large throughput • Balance of the organization load between WLANs what's more, WCDMA	Exorbitant handovers • Ping-pong impact
Chi et al.'s heuristic [22]	2005	Among any two wireless networks	Accessible transmission capacity, network traffic and superfluous handover likelihood are considered in the handover choice measures	Decreased pointless handover likelihood • Balance of the traffic load	Expanded association breakdown likelihood without considering the RSS

Zhu et al.[23] Expanding administrations through the utilization and coordination of assorted organizations makes the test of fostering a more mind boggling, versatile, and astute vertical handoff convention. In this paper, MUSE-VDA has been created to augment the benefit of the handoff for both the client and the organization. The advancements join an organization disposal highlight to diminish the deferral and preparing needed in the assessment of the expense work, and a multi network enhancement is acquainted with improve APUSR for versatile terminals with numerous dynamic meetings. A presentation investigation showed significant gains in

the capacity to fulfill client's solicitations for various concurrent administrations and a more efficient utilization of assets from the proposed improvements. In this treatment, a "proof-of-idea" has been given dependent on the capacity of a client or organization to pick among various organization types, in light of various assistance prerequisites. Future work is continuous to take a gander at a more unpredictable treatment, including the investigation of ideal and sensible weight determination, Qos factor normalizations, and strategy choice point design executions.

Hassawaet.al [24] The coordination of a large number of remote organizations is relied upon to prompt the development of the fourth era (4G) of remote technologies. Under the inspiration of expanding the degrees of client fulfillment while keeping up consistent availability and a palatable degree of Qos, we plan a novel cross-layer engineering that gives setting mindfulness, savvy handoff and portability control in heterogeneous remote IP organizations. The creator has fostered a Transport and Application Layer Architecture for vertical Mobility with Context mindfulness (Tramcar). Cable car presents another way to deal with vertical handoff choices, which isn't only founded on network attributes yet in addition on more significant level boundaries which fall in the application and transport layers. Cable car is custom-made for a wide range of organization advancements with various qualities and has the capacity of adjusting to changing climate conditions and flighty foundation traffic. Besides, Tramcar permits clients to distinguish and focus on their inclinations. Cable car is a brilliant and reasonable framework, which is more equipped for managing 4G difficulties. Reproduction results show that Tramcar builds client fulfillment levels and organization throughput under harsh organization conditions and diminishes in general handoff latencies.

Tawilet.al [25] presented a compelling and novel Distributed Vertical Handoff Decision (DVHD) plot. DVHD distributes the estimation of the organization quality among target VNs instead of the portable terminal and thinks about the transfer speed, the dropping likelihood and the expense boundaries as measurements of the NSF.

Table2.3 : A synopsis of cost work based VHD calculations

Heuristic	Year	Material Area	Highlights	Benefits	Hindrances
Zhu and McNair's heuristic[23]	2004	Among any two heterogeneous wireless networks	An expense work is presented what's more, clients' dynamic applications are separately given over to target networks with the minimum costs	Expanded client fulfillment •Low impeding likelihood	•Missing definite data, for example, standardization technique furthermore, loads task to make the calculation reasonable
Hasswaet al.'s heuristic[24]	2007	Among any two heterogeneous remote networks	Standardization and loads conveyance strategies are given • A handover need assessor is proposed	High throughput • High clients' fulfillment	Trouble in assessing boundaries, for example, security and impedance level
Tawil et al.'s heuristic [25]	2008	Among any two heterogeneous wireless networks	A weighted capacity is presented • The handover computation is assigned to the meeting network rather than the MT	Short hand over delay •Low handover impeding rate •High throughput	Prerequisite of participation between the MT and the PoA of the visiting organization

Nasser et al.[26] The joining of heterogeneous remote organizations is quite possibly the most expected highlights of fourth-age frameworks. This is relied upon to be a colossal advance toward widespread consistent access and inescapable registering. One of the primary difficulties for consistent versatility is the accessibility of dependable level (intersystem) and vertical (intersystem) handoff plans. Level and vertical handoffs are necessary parts of future fourth-age correspondences. This article presents an instructional exercise on the various parts of handoffs, and examines handoff plan and execution related issues. Probably the best highlights of handoff plans are examined . Handoff choices, radio connection transfer, and channel task are depicted as phases of the total handoff measure. Handoffs are likewise delegated either deliberate or required ,and handoff situations of the two classes are

introduced. At last, we propose an upward handoff choice capacity that gives handover choices while wandering across heterogeneous remote organizations. By reproduction, we have demonstrated the practicality and carry out capacity of VHDF. **Pahalvan et al. [27]** introduced an outline of the issues identified with handoff with specific accentuation on mixture versatile information organizations. Handoff issues can be grouped into two autonomous parts: structural issues and IIO choice time calculations. The previous are open and normalized, yet the last are generally exclusive. Handoff structures in versatile information organizations and rapid WLANs have a few similitudes. Customary HO calculations have terrible showing and are being supplanted by arising progressed HO algorithms. A model neural organization calculation decreases the quantity of superfluous handoffs as well as limits the HO delay in a microcellular scenario. No one innovation or administration can give universal inclusion, and it will be essential for a versatile terminal to utilize different marks of attachment to keep up availability to the organization consistently, bringing about the requirement for HO in a mixture organization of portable information and WLAN. The HO design issues identified with crossover networks are examined through an illustration of a mixture network that utilizes GPRS and IEEE 802.11. Portable IP is the most reasonable design for HO in a mixture network. Again neural organization based calculations perform better compared to conventional calculations for handoff time in half and half organizations.

Xia et al. [28] Introduced in their paper, A Deep Vertical Hand of Calculation in Heterogeneous Distant Organizations. Our proposed vertical handoff calculations take into account specific network parameters, including current RSS, predictive RSS, and available data transfer capability coordination of up-and-coming companies. The Forward Differential Expectation calculation is used to obtain predictive RSS, which triggers a premature handoff. Additionally, pre-choice technology is implemented before the handoff decision module, which can transmit unwanted information and provide accurate handoff triggering. The SOP Logic standard-based evaluation and selection calculation is applied to the overlap organization of FNQD UMTS and WLAN. The final customized handoff option is based on PEV. FNQD calculations can save MH memory for storing rule bases, save the opportunity to expand within standard bases, and isolate the best ones across different up-and-comer networks.

Reproduction results suggest that the proposed vertical hand-off scheme could better manage the ping-pong effect in a different organization.

Table2.4 : A rundown of blend calculations

Heuristic	Year	Material Area	Highlights	Benefits	Hindrances
Nasser etal.'sheuristic[26]	2006	Among any two heterogeneous wireless networks	An expense work is embraced also, the framework is prepared prior to being utilized in the handover choice	High achievement rate in finding the best organization up-and-comer	Preparing delay • Increased framework intricacy
Pahlavanetal.'sheuristic[27]	2000	From WLANs to GPRS	The RSS tests are gathered as the contributions of the neural organization and the framework is prepared previously being utilized in the handover choice	Diminished number of handovers • Elimination of the ping-pong impact	Absence of detail on preparing cycle and boundaries choice • Training delay • Increased framewor k intricacy
Xia et al.'s heuristic [28]	2007	Among WLANs and cellular networks	Current RSS, anticipated RSS and transmission capacity are fuzzificated and standardized to be utilized as the handover	Decreased number of handovers • Elimination of the ping-pong impact	Fixed loads which neglect to address the issue of constantly evolving remote climate

So far twelve VHD calculations have been examined and arranged into four gatherings dependent on the measures they use for settling on handover choice. To give a general examination of the four gatherings, their highlights are summed up on five perspectives: organizing innovations that they can be relevant, input parametres,

handover target determination criteria, complexity and unwavering quality as demonstrated in the table beneath.

Table 2.5: A relative rundown of the four gatherings.

Gathering	Appropriate systems administration advancements	Info boundaries	Handover target choice rules	Intricacy	Unwavering quality
RSS based VHD calculations	Normally between large scale cell what's more, microcellular networks	RSS as the primary information	The organization competitor with the most steady RSS	Basic	Diminished dependability in light of the vacillation of RSS
Bandwidth based VHD calculations	Between any two heterogeneous networks	Data transfer capacity consolidated with different boundaries like RSS	The organization applicant with the most elevated data transmission	Basic	Diminished dependability due to the changing accessible transfer speed
Cost function based VHD calculations	Between any two heterogeneous networks	Different boundaries like expense, transmission capacity and security	The organization applicant with the most noteworthy generally speaking execution	Complex	Decreased dependability in view of the trouble in estimating a few boundaries
Combination based VHD calculations	Among any two heterogeneous networks	Diverse information boundaries contingent upon various strategies	The organization up-and-comer with the most elevated generally execution	Very complex	High dependability due to the preparation of the framework

Bhute et al. [29] presented in his paper, an outline of vertical handoff system giving a point by point portrayal and order of different diverse existing vertical handover choice procedures. To meet the necessities of the heterogeneous remote access organization, setting mindful vertical handoff system can assume a fundamental part in the exploration of handoff the executives which thus deals with versatility the board of heterogeneous remote networks. In this paper it has been recommended that enhancements in the presentation of the handoff can be accomplished when various rules are utilized for handover decisions. With the increment in intricacy of the assessment work for handoff choices, it expands the defers significantly. So from reasonable mark of view, this application may not be fitting or feasible. Thus, three is a requirement for the present continuous work to foster half breed strategies which can improve the outcomes without being perplexing as versatile or canny conduct which can deal with uncertainty and address the unique idea of portable conditions.

Hua et al. [30] presented and concentrated in his paper the exhibition of V-MFVHO, and furthermore contemplated that speed assessing the speed assessing the speed of versatile units assumes a fundamental part and is critical in the investigation of progressive cell frameworks. Creator additionally expressed that network suppliers and administrators need to ceaselessly screen and increment the limit of their framework networks to help more number of clients and furthermore to upgrade the limit per client. Creators called attention to that to support this, a progressive multi recurrence cell framework will turn into something typical in future. Authors have utilized a situating component like fingerprinting and counterfeit neural organization to distinguish and gauge the specific precise speed of the MS and by utilizing this innovation he could set the speed as a handover initiator in overlaid multi-recurrence system. In this paper the reenactment results shows us that situating instrument fingerprinting and back-spread neural organization can assess the most exact speed of the MS and with the assistance of this innovation above we could set the speed as a handoff initiator in the overlaid multi-recurrence framework.

Yan et al. [31] studied and proposed a handover choice strategy dependent on the expectation of voyaging distance inside an IEEE 802.11 remote neighborhood (WLAN) cell. Creators expressed that the above strategy utilizes two limits which are determined by the portable terminal (MT) as it enters a WLAN cell. The anticipated voyaging distance is contrasted against these edges with settle on a handover choice to limit the likelihood of handover disappointments or pointless handovers from a cell organization to a WLAN. The outcome investigation shows that proposed technique work effectively keeps the quantity of fizzled or pointless handovers low.

Mcnaair et al.[32] inspected and proposed in his paper an educational exercise work on the arrangement and execution openings for achieving a flexible vertical handoff in a multinetwork 4G environment. Possible plan fragments were depicted past 3G, and the further advances and improvement of Mobile IP were envisioned as a basic development toward a 4G structure subject to all-IP putting together advancement. Standard customary protons are not satisfactory enough to deal with the goal of steady immovability and setting careful organizations. However, there are constant tries are being gained for the ground by the IETF and among experts to make canny vertical handoff shows to furnish and execute really confusing handoff decision estimations and handoff procedures, and setting careful handoff interface moves.

Austin et al. [33] In this paper creators have proposed and described a fast speed versatile handoff calculations for microcellular frameworks equipped for giving predictable and close to ideal execution. Creators have introduced first rules for the improvement of the measure of spatial averaging needed for neighborhood mean assessment in microcellular frameworks. After this, three distinctive speed assessors are introduced constantly and they are additionally contrasted with deference with their affectability to r-9 9 ice factors, non-isotropic dissipating, added substance Gaussian clamor, and execution in a versatile handoff calculation.

Austin et al. [34] In this paper creators have proposed a novel class of bearing based handover calculations is proposed for improving the handoff execution in metropolitan microcells. Multi-cell metropolitan microcell handoff properties are determined for a phone format with base stations at each other intersection. The course one-sided handoff calculations are appeared to improve cell enrollment properties and handoff execution by lessening the mean number of handoffs while at the same time decreasing the handoff delay. A bearing assessment procedure which depends on the sign strength history is portrayed to give improved handoff execution, particularly for view handoffs.

Zheng et al. [35] In this paper creators have talked about and assessed two kinds of handoff algorithms. The calculation exhibitions have been assessed and analyzed dependent on the normal number of handoffs and least got signal strength. It is gotten and reasoned that calculation B with better execution is appropriate for DWCS with fixed planning Scathe proposed calculation B for a position area and heading helped and it can give more precise handoffs and less incessant handoff times without debasing sign quality. So it is settled that position area and bearing helped Algorithm B ought to be received in DWCS.

Tripathi et al. [36] In this paper the creators have talked about another fluffy rationale based calculation that uses a brought together handoff applicant determination basis and versatile heading biasing. The brought together preselection rule permits extra levels of opportunity in getting wanted tradeoff among the framework qualities. This standard additionally all the while considers a few handoff rules so all that accessible competitor can be chosen under indicated constraints. It is additionally presumed that versatile course biasing lessens both the quantity of

handoffs and the handoff delay. Reproduction results show that the examined proposed calculation expands the presentation of the fundamental fluffy rationale and course one-sided calculations.

Yates et al. [37] It has been appeared in the past work that that a handoff calculation dependent on SIR alone precludes handoffs close to ostensible cell limits, causing cell hauling and superfluously high transmitter powers. In this paper , creators have proposed and examined about the Minimum Power Handoff (MPH) calculation in which mobiles continually look for a mix of base and channel task that limits the uplink sent power. The calculation introduced in this paper has been shown that it can lessen the normal force level by 4dB when contrasted with SIR based Handoff. Simulation results show that utilizing got power as a handoff basis diminishes call dropping yet builds the quantity of superfluous handoffs significantly. To keep away from a "ping pong" impact, a clock is acquainted with delay the intercool handoff.

Modica et al. [38]To give and carry out consistent portability inside a heterogeneous framework (for example integrated, multiple GPRS/WiFi access framework), an upward handoff strategy needs to planned and formulated. This is concocted typically at the portable terminal ,allowing it to be modified from an end-client point of view with the goal that it can fulfill singular necessities and preferences. In this paper, Authors have proposed another methodology in executing vertical handover choices, which isn't any longer only dependent on the information on the accessible access networks qualities yet additionally on more significant level parameters which fall in the vehicle and application layers. Soto address the above difficulties, in this paper creators have proposed and understood a model and reenactments have been rushed to talk about and assess the effect of the upward handoff and its scope of frequencies on particular set of regular client's organization applications and services. Authors have likewise dealt with the client preferences consisting of cost and nature of service. In expansion to this ,creators accept that this technique takes care of optimal settings from the end client's place of view with respect to his running administrations and applications. Author's center is to devise a system or characterize a metric which can give answer for match the general expense of vertical handoffs with good advantages to genuine client's organizing needs. In this way portable hub client can accomplish and apply self-governing the handoff choice arrangement which is more productive to his particular necessities.

Hasswa et al. [39] In this paper, creators have proposed a model vertical handover choice capacity, VHDF which produces handoff choices while getting across various heterogeneous remote organizations. This model licenses clients to deliberately focus on the organization setup and attributes and give loads to various organization parameters, for example, monitory cost, service quality, power necessities, and so forth This model VHDF is exceptionally basic and can be handily applied to any upward handover measure. It is profoundly huge and prompts progression in the framework adaptability and extensibility and gives more precise handoff choices at some random time.

Dugong et al. [40]In this paper, creators has researched holes influencing handoff the executives of portable hubs (terminals) in heterogeneous remote environments. The versatile hubs are associated with numerous remote radio interfaces and have an extremely restricted lifetime battery. Seamless portability and force usage effectiveness become two significant elements of the handover management. Authors have presented in this paper the client driven organization choice, power-saving interface the board and versatile handover commencement answers for give consistent terminal started and terminal-controlled vertical handover. The proposed model of access network choice is circumstance mindful to suit distinctive correspondence contexts. It makes the terminals to choose the most reasonable access network as indicated by different access network attributes. Numerous remote interfaces of a terminal gadget are dealt with in both inactive and dynamic correspondence modes to streamline the force consumption. Authors have additionally proposed a versatile handover inception plan to define and investigate the assistance continuity. Authors have likewise directed recreations and examinations of the proposed answers for show their reasonableness and their productivity.

Farkas et al. [41] This paper details an engineering that targets streamlining portable organization administrations dependent on setting information. This intends to assemble data from various organization components and to utilize this data in MNs for neighborhood setting mindful and better decisions. The design proposed by the creators in this paper licenses for an adaptable utilization of various conventions to trade various sorts of setting information. In expansion to this it also allows for an adaptable utilization of various setting mindful choice calculations in MNs.The

proposed arrangement takes care that the right setting data is accessible at the perfect spot at the perfect time, and handles diverse, dynamic and circulated setting data.

Ahmed et al. [42] The creators have proposed a setting mindful choice calculation dependent on the AHP method. The calculation considers setting data from both the terminal and organization side and it is reasonable for vertical HO dynamic cycle in heterogeneous networks climate. The proposed calculation is completely adaptable and subject to the quantity of picked destinations that will decide the element of the pair wise examination grid for goals just as the quantity of pair wise correlation lattices for networks as far as every unbiased. The choice calculation depends on the essential numerical computations that could be especially appropriate for installed equipment in a cell phone. It is a help type based calculation which implies that the entire cycle is executed once for each sort of running application, not for each running application. Subsequently, even in the most pessimistic scenario the all out number of execution of the entire cycle is confined to just multiple times while utilizations of every one of the three sorts are running. This is ordinarily valuable in limiting handling time, handover postponement, and CPU and memory use.

Leung et al. [43] In this paper, authors have proposed a calculation for a setting mindful organization determination that depends on a changed WPM for access network selection. The creators have utilized a weight dissemination strategy which depends on affectability examination of WPM for the most compelling measures dependent on the condition of client at a given time. Creators' assessment technique depends on contrasting WPM and TOPSIS that is effectively utilized in numerous dynamic issues.

Zekri et al. [44] Permitting consistent administrations while wandering through heterogeneous remote Networks is a primary worry in the cutting edge 4G remote organizations. So to conquer this test, in this paper, authors have planned an effective vertical handover dynamic calculation that considers administrations' necessities, considers clients' inclinations and insurances consistent handoff over heterogeneous innovations. This methodology depends on cutting edge choice innovations like fluffy rationale and insightful chain of importance processes (AHP).

Ludwig et al. [45] The creators have introduced the choice model in this paper and it considers setting data from both the terminal and organization side, should be

reasonable for vertical HO dynamic cycle in heterogeneous networks environment. The model clarified in this paper is completely adaptable and is reliant upon the quantity of picked goals that will decide (i) dimension of the pair wise correlation framework for targets and (ii) number of pair wise examination lattices for networks as far as each objective. The choice calculation depends on numerical estimations that are normally appropriate for implanted equipment in a cell phone. It is a help type based model in which the entire interaction is executed once for each sort of running application. This application is used in limiting handling time, HO deferral, and CPU and memory utilization.

Stevens et al. [46] In this paper, creators have introduced a choice calculation for the upward handoff choice stage in heterogeneous remote organizations. The calculation depends on the MDP plan with the goal of expanding the normal complete award of a connection. A interface reward work has been utilized to display the Qos of the versatile connection. A flagging expense work has been utilized to show the exchanging and rerouting tasks when an upward handoff happens. In this paper, the work is pointed toward clarifying the tradeoff between these two significant angles in the upward handoff decision. A fixed deterministic approach is gotten when the association end time is mathematically distributed. The model expansions and the execution rules have been depicted, which are viable with the IEEE 802.21 norm.

Lee et al. [47] When cell associations are needed to relocate between heterogeneous networks for a superior exhibition and high-accessibility reasons, at that point consistent vertical handover is a first fundamental step. Besides, new measurements for vertical handoff keep on arising in this world. in this paper, creators have attempted to feature the measurements most appropriate to vertical handover choices. Creators have additionally proposed a summed up vertical handoff choice calculation that streamline a joined expense work including battery lifetime of MNs and burden adjusting over APs/Bss. Simulation results show that the proposed calculations perform far superior to the customary advancement dependent on the SSF technique, which depends on RSS alone. The proposed strategy gives the organization administrator the influence to effectively fluctuate the accentuation from amplifying the general framework battery lifetime for MNs to looking for decency of burden appropriation over APs and BSs, with weighted mixes in the middle.

Wang et al. [48] In this paper, the creators have introduced the outcomes for the four distinctive vertical handoff choice calculations specifically: MEW (Multiplicative Exponent Weighting), SAW (Simple Additive Weighting), TOPSIS (Technique for request inclination by likeness to ideal arrangement), and GRA (Gray Relational Analysis). The parameters and traits considered in the reenactment model included transmission capacity, deferral, jitter and BER. In this paper, the reproduction results show that MEW, SAW, and TOPSIS gave comparative execution to each of the four traffic classes. GRA gave a marginally higher transfer speed and lower delay for intuitive and foundation traffic classes. The recreation results additionally showed that every one of the four calculations rely upon the exhibition loads appointed to the parameters.

Sgora et al. [49] Ubiquitous administration conveyance requires the choice of the optimal access network in a heterogeneous wireless environment. The MADM strategies give a successful structure to positioning the competitor networks in a heterogeneous remote climate through their appraisals regarding numerous attributes. In this paper, the creators have proposed an access network choice calculation that consolidates with the AHP technique to decide the significance of the organization parameters and the TOPSIS strategy to rank the up-and-comer networks. The mathematical outcomes acquired by the client showed that the blend of these two techniques can be powerful for the determination of the ideal access network as indicated by necessities of the application that the client wishes to start.

Tran et al. [50] In this paper creators has introduced an exhibition correlation between the procedures like SAW, WP and TOPSIS techniques. In this paper the creators have contemplated, featured and distinguished the limits of each MADM calculation affecting the dynamic for interface selection. Presently creators are fostering another choice calculation which dissimilar to TOPSIS isn't dependent upon the irregularity issue and gives more exactness than SAW and WP in position ID. This work is a piece of a general system that creators create to execute a versatile terminal ready to use simultaneously various interfaces to exploit of fault-resistance/repetition, load sharing, and interface selection limits gave by the multi-homing idea.

Das et al. [51] In this paper, the creators have talked about how the IEEE 802.21 standard structure and administrations are tending to the difficulties of consistent versatility for multi-interface gadgets. Notwithstanding this, authors have depicted and talked about plan contemplations for a proof-of-idea IEEE 802.21 execution and shared functional bits of knowledge into how this standard can upgrade handoff execution.

Bari et al. [52] In this paper, the creators have talked about and applied TOPSIS, a MADM algorithm, to the issue of organization determination and broke down the reasons for the positioning irregularities issue for TOPSIS as applied to the issue of organization selection. In this paper, creators have proposed an iterative methodology for use of TOPSIS, which can improve the outcomes for network choice by contrasting just the more probable competitors all the while. Reproduction results have been presented to show that the top competitor network determinedly TOPSIS can change when an applicant at the lower part of the ranking is taken out from the examination, and the iterative approach gives a more predictable and exact eventual outcome.

Farooq et al. [53] The paper has featured the significant issue of organization choice that exists today while conveying administrations on a heterogeneous blend of remote access advances. It has described transformation of ELECTRE, a MADM calculation, for ranking network options during the organization selection process. The utilization of a specific MADM calculation for specific issue depends on an appraisal about the fittingness of the calculation for application to the issue space. The paper has recommended utilization of changed calculation that gives a total positioning of elective organizations. The alterations additionally permit use of ELECTRE with attributes exhibiting a non-monotonic utility. These alterations make the calculation more capable to application in network selections it grows its pertinence to more extensive scope of advancement targets.

Mohamed et al. [54] proposed a cross breed strategy dependent on multi quality dynamic strategies AHP and TOPSIS to choose the best other option . This work improves the issue of the positioning irregularity of TOPSIS and DIA. The viability of crossover technique is endorsed by simulation. We reason that the positioning oddity

because of the utilization of MAD methods is being diminished when the heterogeneity of the criteria are mulled over for the organization determination.

Kosmidiset.al [55] In this paper, creators center on the Network Selection issue to allot terminals to most appropriate RATs by mutually analyzing the two clients and providers' inclinations. Creators present a utility-based optimization function and plan the terminal task issue as an optimization issue which is perceived as NP-hard. Creators propose a Greedy heuristic which abuses a metric that measures the utility acquired versus the limit asset spent for each allocation and affirm its unrivaled presentation against three Bin-Packing heuristics.

Song et al. [56] present a novel organization choice plan for the joining of UMTS and WLAN to consistently ensure the best Qos through choosing the most appropriate network while forestalling incessant handoffs. Creators improved the use by utilizing a blend of AHP and GRA to assess client inclinations and administration classes quantitatively and positioned the organization options productively. AHP exploits progression and pair wise comparison, and GRA centers around discovering the distinction between the relative and ideal options. Unlike different plans, creators considered as numerous Qos-central consideration, and weighted them dependent on their significance to Qos. This guarantees that clients can appreciate the best available eservice without pointless handoff.

Hsu et al. [57] In this paper, creators propose a versatile organization choice (ANSWER)scheme, which can settle on the better choice about when to turn and choice on which access organization. That is, creators need to give the consistently best connected service however much as could reasonably be expected for the clients. In particular, to accomplish the above objectives, the accessible data transfer capacities of every conceivable organization, the area of user's gadget and its moving bearing are adopted into thought in the ANSWER strategy. Creators assess the presentation of the ANSWER scheme through broad reenactments and the outcomes concur with our objectives.

Opricovic et al. [58] In VIKOR linear normalization and in TOPSIS vector standardization is utilized to dispense with the units of rule capacities. The VIKOR method of give and take positioning decides a trade off arrangement, giving a greatest "bunch utility" for the 'majority' and at least an individual lament for the "rival". The

TOPSIS strategy decides an answer with his most brief distance to the ideal arrangement and the best separation from the negative-ideal arrangement, however it does not consider the overall significance of these distances. A near examination of these two techniques is represented withal mathematical model, showing their similitude and a few contrasts.

Wang et al. [59] In request to intervene the contentions and inconsistencies in the reconciliatory interaction and act in light of the absence of adaptability while receiving conventional multi-measures technique to tackle fluffy issues, the investigation plans to utilize Fuzzy VIKOR strategies to solve fuzzy multi-models dynamic issues. Fluffy VIKOR expects to discover the chief's ideal trade off that suits human target cognizance. In this paper, we use case examination to figure out the methodical arrangement measure, and at last think of a best arrangement and bargain arrangement that can be a significant reference of dynamic. At last, our decision and idea for cutting edge works are likewise advertised.

Medina et al. [60] In this paper, creators propose the utilization of Multiple Attribute Decision Making (MADM) strategy: VIKOR for vertical handoff decision. The possibility of VIKOR for dynamic depends on an aggregating capacity addressing closeness to the ideal arrangement. Creators execute recreation tests to look at the performance of VIKOR for vertical handoff choice in B3G networks with other MADM plans like SAW and TOPSIS.

Ethics et al. [61] In this paper, creators gives a reenactment investigation of a few vertical handoff choice calculations, with the point of comprehend its performance for various client applications. Creators think about two different applications: voice and information associations. Strategies as SAW, VIKOR and TOPSIS are reasonable for voice connections, these calculations give a trade off to accomplish the lower values of jitter and postpone parcel accessible in a 4G wireless network. In an information association case, GRA and MEW algorithms provide the arrangement with most noteworthy accessible bandwidth necessary for this application.

Mohmed et al. [62] this paper proposes a new approach for network determination choice dependent on Saaty's Fuzzy Analytical Hierarchy Process (FAHP) and the Technique for Order Preference by Similarity to an Ideal Solution (TOPSIS). The FAHP technique is utilized to decide a load for every model, and the TOPSIS strategy

is applied to rank the other options. Recreation results are introduced to show the viability of our new methodology for network choice.

Lahbey et al. [63] This paper proposes a novel technique dependent on mahalanobis distance which mulls over the connection with various standards and furthermore plans to pick the ideal organization while guaranteeing no positioning abdominal muscle ordinariness and lessening the quantity of handoffs. Reproduction results are introduced to show the viability of our novel technique dependent on mahalanobis distance.

Leghris et al. [64] In this work, we have proposed another upgraded network choice calculation which permits to choose the most fitting standards which ought to be utilized for vertical handover choice. The reproduction results show that, our technique dependent on Algorithm 1 can lessen the handover measurements for all traffic classes specifically: foundation conversational, intuitive and streaming.

Attioui et al. [65] In this work, we have proposed another methodology dependent on various insightful organization measure (M-ANP) strategy and TOPSIS technique. The M-ANP strategy, permits to relegate an appropriate loads of various models better compared to ANP technique.

Sunisa et al. [66] This paper has proposed a prescient RSS and fluffy rationale based organization choice for vertical handoff in heterogeneous remote organizations. The RSS anticipated by back proliferation neural organization is helpful to try not to drop calls on the off chance that it predicts a versatile is moving away from the checked remote organization. In extra to the RSS metric, the home time in the objective organization is anticipated which is considered for handoff trigger. The expectation period compares to the versatile abide time. Legitimacy work assessing network conditions and client inclination is utilized as the handoff measures to decide up-and-comer organizations. Fluffy rationale utilizing quantitative choice calculation settles on an official choice to choose the objective organization with the biggest QDV. Subsequently, the proposed approach outflanks different methodologies.

Chen et al. [67] another engineering fit for supporting ABC administration is proposed in this investigation. There are three sections to the proposed design. Initial, a novel access revelation instrument that incorporates SLP and LCS administration is introduced. Second, another customized network determination conspire is proposed.

Clients can choose their customized best organization by changing weight elements and imperatives in a solitary target advancement issue. Third, a consistent handover system dependent on Mobile IPv6 is proposed in this investigation. The component upholds start to finish Qos. Through investigation, this design shows that it offers benefits not just for network operators, but likewise for clients.

Taaghola et al. [68] In this article we address the coordination of mobile WiMAX with developed 3GPP organizations as a average and financially convincing illustration of conveying heterogeneous cutting edge versatile organizations. We examine the design and key systems that empower WiMAX/3GPP combination, and present a novel handover mechanism that empowers consistent portability between versatile access advancements with single radio portable terminals. We presume that solitary radio handover (i.e., with terminals that don't have to at the same time send on both access types) can alleviate the RF concurrence gives that exist with double radio handover instruments at an expense of more insight in the organization and terminal.

Lampropoulos et al. [69] In this article, the point of convergence is the fulfillment of administration prerequisites during versatility and all the more explicitly, how the arising IEEE802.21 standard empowers consistent, between innovation handover. In light of earlier work and a notable illustration of consistent versatility, the primary consistent portability standards are recognized and utilized as the reason for additional assessing the capability of the IEEE 802.21 norm to meet the prerequisites of utilizations for least interruption during a between innovation handover.

N. Golmie et al. [70] While numerous arrangements have been grown so far toward supporting consistent versatility, it is obvious from the difficulties staying to be tended to that we have not arrived at our objective yet. Another significant obstruction is by all accounts the market acknowledgment and business case for conveying and supporting such utilization situations. A portion of the innovation accessible today might be adult enough for arrangement, however administrators and specialist co-ops stay hesitant to accept it. Taking everything into account, the street ahead may in any case be long and troublesome, yet the future actually favors consistent portability.

Falowo et al. [71] Next age multimode terminals have the capacity to at the same time support at least two distinct classes of brings in HWNs. The issue of RAT choice for different brings in HWNs has been conceptualized. The Fussy TOPSIS collective

choice making procedure has been applied to tackle the issue of RAT determination for various brings in HWNs. Mathematical reproductions have been led to show the exhibition of the proposed RAT-choice calculation, utilizing a three-RAT HWN, and thinking about various call needs. Reenactment results show the call needs fundamentally influence RAT choice for each gathering of brings in HWNs.

Spirits et al. [72] In this paper, we give a recreation investigation of a few vertical handoff choice calculations, with the point of comprehend its exhibition for various client applications. We think about two distinct applications: voice and information associations. Techniques as SAW, VIKOR and TOPSIS are appropriate for voice associations, these calculations give a trade off to accomplish the lower upsides of jitter and postpone parcel accessible in a 4G remote organization. In an information association case, GRA and MEW calculations furnish the arrangement with most elevated accessible data transfer capacity important for this application.

Zhu et al. [73] In this paper, new improvements for vertical handoff choice calculations have been created to augment the advantage of the handoff for both the client and the organization. The enhancements fuse an organization end highlight, to diminish the postponement and handling needed in the assessment of the expense work, and a multi-network streamlining is acquainted with improve throughput for portable terminals with various dynamic meetings. An exhibition examination showed critical additions in nature of administration and a more productive utilization of assets from the proposed enhancements.

Kassar et al. [74] In this paper, creators give an outline of the upward handover decision measure with a characterization of the different existing vertical handover choice techniques. It has shown that progressed assessment works and advanced architectures are expected to perform better handover choice making for client fulfillment just as for the productive use of network assets.

Akyildiz et al.[75] This paper portrays current and proposed conventions for mobility management for public land versatile organization (PLMN)- based networks, versatile Internet convention (IP), remote asynchronous transfer mode (ATM), and satellite organizations. The coordination of these organizations will be talked about with regards to the following evolutionary step of remote correspondence organizations.

Ian et al.[76] In this article we give a far reaching overview of versatility the executive's methods in NG all-IP based remote frameworks. Since worldwide wandering in heterogeneous remote conditions will turn into a fundamental pattern sooner rather than later, we center on portability the board methods in heterogeneous remote organizations. We depict current proposed conventions for portability the board in NG all-IP-based remote frameworks. These conventions attempt to give versatility the executives from various layers. We think about the current arrangements and point out the inspirations for the plan of a more proficient versatility the board design. We additionally fostered a conversation for open exploration issues in this field.

Sun et al.[77] This paper talks about the versatility the board plans for the cutting edge portable organizations. A worldwide hierarchical framework model for the versatility the executives of remote organizations are introduced, in which the portability the board is divided into two correlative assignments: full scale versatility and miniature versatility. As the full scale versatility arrangement, basic principle of Mobile IP is presented, along with ideal plans and the advances in IPv6. The hindrances of the Mobile IP on taking care of the miniature portability issue are investigated, in light of which three fundamental recommendations are examined as the miniature versatility arrangements, including HMIP, Cellular IP, and HAWAII. A bound together model is additionally portrayed in which the distinctive miniature portability arrangements can coincide at the same time in versatile organizations. The introduced structure and content examined in the paper can fill in as a viable manual for the general arrangement and precise examination on the problem of portability the executives for the cutting edge remote correspondences. Further exploration themes focus mainly on the assessment of the recommendations in a tested with genuine traffic load and a cautious thought of safety.

Swami et al.[78] An intensive investigation of existing VHD calculation utilizing fluffy rationale idea delights that, utilization of fluffy rationale ideas to plan a multicriteria vertical handoff choice calculation is both savvy and exceptionally helpful. For the handoffs started by portable hubs, fuzzy logic based vertical handoff choice calculation (VHDA) is utilized to choose the most fitting organization for the versatile hubs. Still currently proposed VHD Algorithms either need a comprehensive thought of different organization Parameters or need enough details for execution.

Investigation into vertical handover choice calculations in heterogeneous organizations is as yet a difficult region. The main trouble is to plan a calculation which is really valuable in wide going conditions and use all the helpful organization boundaries.

Table 2:6.Outline of existing vertical handover choice procedures

Heuristic	Year	Info boundaries	Highlights	Benefits	Hindrances
<i>Capacity based</i> Organization based admittance determination in composite radio climate [79]	2007	RSS, mentioned administration, bit rate and defer resilience, accessible transmission capacity, delay at the line, cost, trust, similarity, capacity	A goal work (OF) is characterized through boundaries assembled by the two clients furthermore, networks, MNs are associated with the network that expands OF	Least corruptions in high burden and blockage circumstances	Tedious if administrations and additionally accessible passages increment
Client driven Organization determination choice in remote heterogeneous networks [80]	2005	Terminal ability, information move prerequisites, clients spending plan, adaptability to postpone	A client utility or advantage work is characterized to address the client's inclination rating of wanted organization measurements or ability to pay	Maximizes clients' utility	Non ongoing help, basic rate forecast technique
<i>MADM</i> An organization determination component for next age organizations [81]	2005	Availability, delay, jitter, reaction time, BER, burst blunder, bundle misfortune proportion, RSS, security, cost, unwavering quality, normal number of retransmission	_ AHP is utilized to characterize the heaviness of each choice boundary then GRA is utilized to rank the accessible organizations	_ Multi rules thought	Medium execution intricacy
<i>Markov based</i> A VHO choice calculation for heterogeneous remote networks [82]	2007	Network ID, transfer speed, delay, application Qos necessities, preparing load, flagging overhead	(1) A connection reward work is characterized based on the Qos necessities, (2) A flagging expense work related with the handling load also, flagging overhead is characterized) expand the normal complete limited reward	Versatile and pertinent to a wide scope of conditions, improvement over SAW and GRA	Execution intricacy
VHO choice in an improved media autonomous handover structure [83]	2008	Complete transmission capacity, permitted transmission capacity, cost per byte, load, delay,jitter, parcel misfortune	Meaning of weighted Markov Chain and determination of the most loved organization that Amplifies the SD vector	Better deferral execution than TOPSIS	Execution intricacy
<i>Fuzzy logic based</i>	2007	RSS, CPICH	A FLC based	Settles on	Intricacy

Neural organizations for versatile vertical handover choice [84]		Ec/N0, velocity, load	calculation is proposed and upgraded by a multi-facet perception NN that learns the connection transport between the FLC boundaries and adjust them	choices in an autonomic manner, considers multi-measures	increments if extra info boundaries are thought of
<i>Game theory based</i> A helpful game for transmission capacity allotment in 4G remote organizations [85]	2006	Data transfer capacity, cost	N-individual helpful game, networks participate to give new and VHO associations with the necessary transmission capacity and amplify their income	Effective asset the executives	Extra choice boundaries are needed practically speaking to guarantee better nature of administration
A nashstackelberg fuzzy q-learning decision approach in heterogeneous cognitive networks [86]	2010	Load information, throughput, acceptance ratio, file transfer time, average file download time	Decision based on Aggregated load information, interaction and convergence are modeled using a Nash-Stackelbek fuzzy Qlearning framework, MTs aim to maximize their Qos and Networks aim to maximize their profit	Improves the individual efficiency of mobile users	
<i>Reputation based</i> On the utilization of Network Qos notoriety for VHO dynamic [87]	2010	Network reputation, RSS, load	Organization notoriety is determined through a standing framework and used to settle on VHO choice	– Faster VHO decision	Notoriety maintainability should be tended to in more profundity
A client driven examinations of vertical handovers [88]	2004	Client inclinations as far as Qos also, cost	Two VHO choice strategies: (1) fulfill client's necessary Qos (2) fulfill client's ability to pay) an expense work is characterized to track down the ideal VHO choice strategy	High client thought and low execution intricacy	No ongoing help

In the research work proposed in [89] **2007**, it talks of lesser delay, lesser additional handover and better throughput but it doesn't give any information about handover failure probability.

In the published work in [90] 2005 doesn't give any information about delay, number of handovers and handover failure probability but gives significant improvement in throughput.

Research work [91] 2005 also doesn't give any information about delay, handovers and handover failure probability but talks about throughput.

Research work [92] 2007 discusses about handovers but doesn't give any information about other parameters.

Proposed work [93] 2008 also discusses the same thing as discussed in previous one.

Research work [94] 2007 also discusses the same thing as previous one.

Research work published in [95] 2006 talks about handover failure probability but doesn't give any information about other parameters.

Published work [96] 2010 also discusses the same thing as previous one.

Published research work [97] 2010 gives information about delay but doesn't give any information about other parameters.

During the most recent couple of many years, continuous advancements in the field of remote innovations have been coupled to bring to the table improved organization network for supporting rapid sight and sound administrations. With the flare-up of all IP-based organizations, administration administrators offer various administrations to fulfill the client's requirements with a superior Quality of Experience (QoE). An enormous work has been completed in the field of organization choice instruments for causing VHD to satisfy client requests for better Qos and QoE. This section diagrams the current guidelines, designs, versatility models and techniques utilized in the organization determination methodologies. It additionally presents an outline of the dynamic exploration drives in the space of versatility the executives and access choice calculations in HWN.

2.2 Organization Selection Algorithms

The impact of the evolution of the heterogeneous wireless environment on the network selection problem has been deliberated in the previous chapter. This chapter delineates the scope of each category on the network selection process and the proposed work of thesis in this background while highlighting the significance of each technique with their advantages and disadvantages. The existing network selection algorithms are classified based on the type of decision metric and techniques used for the evaluation of available networks. The second section of chapter outlines the research issues for the user-centric network selection to perform VHD in heterogeneous wireless environment determination issue has been thought in the past

part. This section portrays the extent of every classification on the organization determination measure and the proposed work of theory in this foundation while featuring the meaning of every method with their benefits and impediments. The current organization choice calculations are ordered dependent on the sort of choice measurement and procedures utilized for the assessment of accessible organizations. The second segment of part traces the exploration issues for the client driven organization choice to perform VHD in heterogeneous remote climate.

A clever MT should be given numerous radio interfaces to get to various RATs. Since the terminal-controlled versatility depends essentially on the terminal as opposed to the organization, the terminal ought to be sufficiently shrewd to choose the most reasonable access network as far as client fulfillment and improved Qos. Different organization choice procedures have been introduced in the examination writing to comprehend the specialized foundations of organization determination arrangement. The current multi-rules network choice calculations are essentially characterized into four classes. i) Utility based ii) Mobility based iii) MIH based iv) fluffy rationale and MADM based calculations v) game hypothesis based procedures.

2.2.1 Utility Based Network Selection

Hesham El-Sayed et. al, [98] introduced an outline of Qos models dependent on deterministic and probabilistic methodologies, which can be utilized for expanding asset usage and limiting expense of administration for versatile clients across heterogeneous organizations. It additionally summed up a portion of the specialized issues in giving start to finish Qos to an assortment of administrations in an incorporated cell/WLAN organizations.

In [99], network determination calculation dependent on Simple Additive Weighting (SAW) technique is introduced in which the weighted standardized upsides of the multitude of boundaries are basically added to deliver the worldwide utility of specific organization. The organization with the most elevated score is chosen as the objective organization to offer better Qos and client fulfillment. In SAW, the weighted standardized qualities are added to track down the general utility of the organization. In any case, the quantity of handovers is high contrasted with other MADM techniques. This influences the consistency level of organization determination

despite the fact that there is a critical decrease in the intricacy. In any case, interdependency among the models was not considered in this methodology.

IoannisChamodrakas et. al, [100] proposed energy productive organization determination strategy, which consolidates the utilization of utility capacity to display the flexibility of various applications and appraisals the energy utilization for constant and non-continuous application. This proposition thinks about client inclinations, Qos, network conditions and energy utilization to choose the ideal organization while accomplishing tradeoff among execution and energy utilization. At long last, fluffy Technique for Order Preference by Similarity to an Ideal Solution (TOPSIS) strategy is utilized to figure the general score of the organizations. This strategy isn't reasonable for high speed clients since portability attributes were not thought of.

In [101], single and multi-models based utility hypothesis is introduced to assess the nature of organizations as far as acknowledgment likelihood and application prerequisites. The intricacy of the calculation increments since it considers an excessive number of steepness boundaries to mirror the client affectability.

El HadiCherkaouil et. al, [102] drew nearer multi-standards utility capacity based organization determination strategy that utilizations sigmoid capacity to decide the rudimentary utility of each characteristic. At that point, these rudimentary traits are amassed to track down the worldwide utility of each organization by thinking about the reliance among the models. This strategy needs adjusting the weight esteems as per the application Qos of running assistance and client inclination.

Lashing Wang et. al, [103] gave the different numerical models and speculations like utility hypothesis, MADM, Fuzzy rationale and Game hypothesis to accomplish the throughput streamlining and low intricacy in network choice issues. It gives a wide report on displaying of organization choice cycle with various types of utility structures. The benefits and impediments of numerical hypotheses and the coordination of various innovations were talked about to accomplish balance between intricacy of organization determination and organization execution.

PavlosKosmides et. al, [104] planned the organization determination and the terminal task issue that considers the two clients' and specialist co-op's inclinations to choose the best reasonable RAT for the multi-interface MT with low computational expense. The viability of the utility-based improvement capacities, for example, ideal Branch

and Bound calculation and a Greedy calculation were explored both in disconnected and online conditions as far as client fulfillment degree.

Sun Lei et. al, [105] proposed a versatile organization determination plan to offer expense proficient and client driven organization choice plan to portable clients. The Cobb-Douglas utility capacity is introduced to quantify the client fulfillment to various organizations, which thinks about both client inclination and application level Qos. Subsequently, this technique guarantees the fulfillment level of clients to the chose network concerning client and administration prerequisites.

Ramona Trestian et. al, [106] proposed an energy effective handover arrangement, which incorporates both versatile interactive media conveyance and organization choice to diminish power utilization for battery worked gadgets in a heterogeneous remote organizations. It assumes a significant part when the client's access video content through the concurrence of various radio access advances with the utilization of organization choice cycle. This force the executives conspire additionally offers tradeoff between Qos, cost and energy utilization while moving starting with one RAT then onto the next RAT.

2.2.2 Portability Based Network Selection

Versatility the board is the vital innovation to be examined to help terminal portability, individual portability, administration portability and meeting portability in the concurrence of various RATs to offer omnipresent assistance access at worldwide level [107,108]. The likelihood of handover disappointments and pointless handovers increments as the multi interface MT travels through the combination of various access organizations. Portability based organization determination calculations involve various techniques to plan a handover choice plan to limit the likelihood of handovers. Versatility and handover related issues are summed up in figure.2.1 to recognize the difficulties behind the combination of portability and handover the executives. Picking the most important and appropriate boundaries is as yet an open issue in handover dynamic as it straightforwardly impacts the presentation of handover choice. This segment presents the outline of the versatility related boundaries that empower the incitement of the handover choice method and the difficulties looked during access choice along the direction of MT in various portability situations.

Terminal controlled portability the executives are proposed in [109], which doesn't need any engineering changes in the current organization design. The terminal controlled expense mindful organization determination procedure is offered to the clients to choose the best appropriate organization to amplify their fulfillment. The aftereffect of this methodology demonstrates the effectiveness of force saving interface the board framework as far as least deferral and force utilization.




Figure 2.1 Portability and handoff based techniques

Notwithstanding, area data and MT ability was not considered for the assessment of accessible organizations. **Abdul Hasib et. al, [110]** proposed the asset the board component in the heterogeneous climate utilizing the huge boundaries, for example, i.e., administration type, client versatility, area data, and administration cost. The effectiveness of this plan is logically assessed utilizing probabilistic based methodology. Normal Radio Resource Management (CRRM) plot limits the VHO rate and handoff call impeding likelihood contrasted and the current help based and load-adjusting plans.

In [111], **Lee et al.** fostered a development mindful VHO calculation to perform VHD among WLAN and Mobile WiMAX to offer consistent omnipresent access. This calculation misuses the MT speed and development design for the forecast of stay

time for versatile clients. The MAV handover calculation outflanks the fixed abide clock plot by limiting the ping-pong impacts and pointless handovers. This strategy can't be utilized to assess the excess home time accessible for the MT in the covering locales of organizations.

Yun Meng et. al, [112] proposed a versatile organization determination conspire, which decides the portability edge dependent on portability qualities and appearance rate. The worth of versatility limit is acclimated to adjust with dynamic attributes of heterogeneous organizations to limit the call impeding likelihood.

Tariq Ali et. al, [113] introduced a system to work with the investigation of various practical portability situations with various arbitrary client versatility models to abuse the heterogeneity of the remote climate. This technique gives scientific arrangement dependent on RSS tests to improve the quality and congruity of voice consider when the client is wandering in the incorporation of WLAN and cell organizations. The variety of sign strength with various speeds of MT can't be considered as a dependable factor to guarantee the application level Qos.

Abhinav Kumar et. al, [114] introduced a structure to investigation the elements of organization choice because of lopsidedness attributes of organizations and dynamic conduct of versatile clients.

The general organization choice elements and the exhibition of the organizations are investigated through progress and consistent state probabilities. The organization level Qos is resolved as far as hand off dropping and call-impeding probabilities utilizing state progress model. This probabilistic based methodology can consider the parcel misfortune rate as a choice measurement to improve both client level and organization level Qos.

Dawei Mu et. al, [115] examined the effects of client speed and traffic load on the presentation of portable clients when changing starting with one organization then onto the next network in the heterogeneous remote organizations. The reenactment results reason that the continuous handoff has happened because of high speed of clients, which may debase the client level Qos as far as parcel misfortune rate and handoff idleness.

Hao Wang et. al, [116] introduced an assessment system for network determination measure utilized in 3G-WLAN interworking climate. It gives an insightful answer for

catch the traffic and versatility models of MT in various portability and traffic situations. The impact of versatility model on normal throughput, handover rate, and impeding likelihood are assessed to show the exhibition of the structure.

In [117], a Handover Necessity Estimation (HNE) is presented in which voyaging time expectation and time edge computations are completed to limit handover disappointments and pointless handovers between cell organizations and WLAN. This strategy can appraise just the voyaging time among section and leave focuses on the WLAN cell and don't consider the leftover home time accessible to the client inside the WLAN. Thusly, it might cause superfluous handovers if the excess home time is not exactly the handover delay. This issue is considered in the proposed work to improve the presentation of the organization determination.

Riaz Hussain et. al, [118] proposed stay time forecast model, which gauges the need of VHO to WLAN dependent on point of appearance, which thusly keeps up the likelihood of handover disappointment and likelihood of superfluous handovers inside worthy cutoff points. It can assess the home time between the section and leave point of the MT at the limit of the organization. In any case, this technique can't appraise the home time accessible to the clients along its direction, while the proposed logical methodology gauges the home of portable terminal anytime on the direction inside the organization and performs handover just if the assessed home time is more noteworthy than the limit esteem.

2.2.3 MIH Based Network Selection

Hugo Marques et. al, [119] introduced a short portrayal of NIST add on modules that backings IEEE 802.21 norm and its execution in NS2 alongside the flagging utilized during handover among WiMAX and Wi-Fi organizations. This strategy considers just occasion and order administrations of MIHF and doesn't use the data administrations of MIHF to get the data about the neighbor organizations.

In [120], an ideal successful handover dynamic is proposed to start the VHO cycle in right an ideal opportunity to keep away from ahead of schedule and late handover setting off occasions. It utilizes MIH structure to give ideal data about the connection quality to use the assets of serving network to the extent that this would be possible. The handover costs are assessed as far as handover time required and the help disturbance time to upgrade the handover execution in heterogeneous remote

organizations. Notwithstanding, administration and client setting were not considered to perform VHD to help consistent versatility in different remote organizations.

Omar Khattab et al.[121] introduced an outline of two primary interworking structures, for example, Media Independent Handover IEEE 802.21 and IP Multimedia Subsystem (IMS) upheld by IEEE Group and 3G Partnership Project. What's more, the overview of VHO approaches proposed in the writing and ordered them into four classifications: MIH based class, IMS based classification, MIP under IMS based classification and MIH and IMS mix based class.

Behrouz Shahgholi et al.[122] introduced an inescapable study of IEEE 802.21 norm and design of MIH system. It gives the mechanical advancements behind the utilization of MIH administrations in the versatility the executive's conventions and various kinds of MIH sending situations. It additionally analyzed different handover choice plans abusing MIH with their benefits and hindrances.

In [123], innovation mindful vertical handover calculation is assessed for Constant Bitrate (CBR) traffic dependent on IEEE 802.21 norm. VHO is performed just dependent on the attributes of organizations accessible in the given inclusion territory. Nonetheless, client inclinations and MT portability attributes were not considered for network choice to perform VHD in heterogeneous organizations.

In [124], VHO is performed utilizing IEEE 802.21 empowered Proxy MIPv6 to keep up consistent network with required Qos. This strategy improves the presentation of VHD instrument as far as handover inertness, bundle misfortune, and normal throughput contrasted with PMIPv6 alone components.

In [125], VHO among GSM and UMTS networks is displayed logically. This methodology starts the handover cycle utilizing arrived at the midpoint of sign strength, blackout likelihood and distance. Subsequently, it offers the organization choice with least flagging expense, parcel conveyance cost and overhead. Notwithstanding, application profile and client inclination were not thought to improve the client level Qos.

In [126], IEEE 802.21-based media free handover is proposed to offer continuous types of assistance with least handover inactivity for the reconciliation of Wi-Fi and UMTS organizations. The effect of MT speed and touch rates on the presentation measurements like throughput, parcel misfortune rate and handover dormancy are

broke down. Notwithstanding, it requires further examination in improving the client level Qos when the MT speed increments.

NouriOmheni et. al, [127] proposed a novel design for the choice of the best appropriate access network in heterogeneous remote frameworks. IEEE 802.21 standard is introduced for handover commencement, data assembling and observing of organization assets. This technique is as yet ailing in giving tradeoff among Qos and cost of administration.

In [128], an organization choice system dependent on improved admittance switch revelation is created to perform vertical handover in the incorporation of WiMAX and WLAN organizations. The focused on rating for numerous measures procedure is used in this technique to choose the objective organization for various traffic.

2.2.4 Fuzzy Logic and MADM Based Network Selection

This classification of VHOs and organization determination systems utilize fluffly rationale to give streamlining among precision and intricacy.

A. Singhrova et. al, [129] fostered a Neuro fluffly based vertical handover choice calculation, which thinks about RSS, speed, data transfer capacity, number of clients, battery level and inclusion. Versatile neuro fluffly deduction framework based framework improves the throughput and Qos by decreasing ping-pong impacts contrasted with fluffly method. This calculation expands the computational intricacy with increment of information boundaries despite the fact that it improves the Qos by lessening the quantity of pointless handovers.

Dimitris E. Charilas et. al, [130] introduced a bound together organization determination outline work in which PCA is utilized to eliminate the cooperation between the models and furthermore to acquire the important segments. These segments are utilized in Analytic Hierarchy Process (AHP) to decide the weight upsides of the quality. In any case, application Qos isn't considered during weight estimation and organization determination measure. Hence, administration versatile PCA based organization choice is required.

Faisal Kaleem et al. [131] introduced the execution of fluffly preprocessing module in which the handover need is performed to trigger the handover interaction in legitimate time while accomplishing the end client's fulfillment by giving continuous

Qos to the clients. The quantity of FLCs and the quantity of rules needed to handle the boundaries increments with increment of traits. This requires the advancement among exactness and the computational expense of the calculation.

In [132], Fuzzy Q-learning algorithm is proposed as a load balancing problem in order to minimize call blocking and dropping probability in congested cells. Two different optimization approaches such as Balanced Exploration and Exploitation and Unbalanced Exploration and Exploitation have been investigated to evaluate the performances of the approach. This approach provides load balancing among the networks by adjusting the call-dropping threshold.

In [133], a proactive fluffy guided organization determination calculation is projected to deal with the organization data from the MIHF and to create the handover setting off occasions. In this manner, it can keep away from superfluous handovers and administration interference time in the heterogeneous remote organizations. This strategy doesn't consider the client inclination to choose the objective organization to boost the end client fulfillment

KantubuktaVasu et al.[134] proposed a fluffy standard based assessment utilizing FUZZY-Technique for Order Preference by Similarity to Ideal Solution (FUZZY-TOPSIS) to give Qos-mindful VHD by considering the Qos ascribes like data transmission, start to finish postponement, jitter, and touch blunder rate. A non-birth-passing Markov bind model is utilized to track down the consistent state likelihood of organizations to offer better execution for various traffic classes. Fluffy TOPSIS strategy considers application and force necessities to perform VHD among the reconciliation of UMTS, GPRS and WLAN organizations.

In [135], Qos guaranteed VHD is introduced in which weight esteems are determined utilizing AHP. At that point weighted choice grid is examined utilizing PCA to take out the essential segments that contains limit of unique data. In any case, handover need check must be performed to limit the likelihood of handovers.

FAHP is utilized in [136] to deal with the loose data about the organizations during weight computation though ordinary AHP doesn't manage vulnerability. Hereditary calculation works with pair shrewd correlation grid of various orders to give the positioning of accessible organizations. This calculation improves the consistency level of FAHP in multi models dynamic calculations.

Ding Zhang et. al, [137] proposed an entrance choice calculation dependent on FAHP and entropy hypothesis. They are utilized to perform emotional and target weight computations and Gray Relational Analysis (GRA) is utilized to rank the accessible organizations. This plan decreases the call hindering likelihood while adjusting the organization load proficiently.

In [138], two multi characteristic dynamic strategies, for example, Diff-AHP and the TOPSIS are utilized to choose the best organization as indicated by the Qos necessities. The Diff-AHP strategy is utilized to discover the separate loads of qualities and to discover the score worth of accessible organizations. TOPSIS technique is utilized to rank the organizations dependent on application profile in heterogeneous climate.

Bin Liu et. al, [139] proposed various rules choice strategy in which AHP is utilized to discover the loads of properties and insolvency game is essentially used to evaluate the possibilities of accessible competitor networks by considering the boundaries like transfer speed, jitter, delay, power utilization and touch mistake rate. In this manner, the blend of AHP and game hypothesis evaluates the potential commitment proportion of accessible organizations and the organization with the most noteworthy score is chosen as an objective organization.

Rajiv Verma et. al, [140] introduced a multi-models access network choice calculation dependent on AHP and GRA strategies to offer VHD for the coordination of WiMAX and Wi-Fi organizations. The proposed technique utilizes AHP to decide the general loads of models as per organization's exhibition and GRA to rank the organizations to offer ideal organization determination in heterogeneous climate. Despite the fact that this calculation is basic, the impact of intricacy level in the organization choice interaction was not examined.

In [141], multi rules VHD calculation dependent on fluffy expansion of the TOPSIS is introduced to rank the accessible organizations. This methodology handles the fluffiness and ambiguity of loose boundaries to improve the precision level of organization determination.

Jos'eD. Mart'inez-Morales et. al, [142] introduced the relative investigation of various MADM strategies like SAW, GRA, Multiplicative Exponent Weighting (MEW), VIseKriterijumskaOptimizacija I KompromisnoResenje (VIKOR) and

TOPSIS. From these techniques, SAW, VIKOR and TOPSIS are reasonable to choose the ideal organization for voice application while GRA and MEW for information application.

In [143], two MADM strategies like Analytic Network Process (ANP) and the GRA strategy are utilized to discover the loads of accessible organizations by thinking about every choice measurement, and to rank the accessible organizations individually for network determination as for foundation and streaming applications.

Abolfazl Mehbodniya et al. [144] proposed VHO choice calculation dependent on Fuzzy VIKOR (FVIKOR), which consolidates the utilization of equal Fuzzy rationale regulators with least number of rules to gauge the need of HO and select the objective organization.

Zhang Lina et. al, [145] projected a MADM based organization determination calculation thinking about AHP and synergetic hypothesis to decrease the quantity of vertical handoff in heterogeneous climate. The organization execution is assessed dependent on the worth of cooperative energy degree. The calculation thinks about the coordination of choice measurements as well as Qos necessities into record to guarantee that clients select the ideal organization with upgraded handover execution.

Vinícius de Miranda Rios et. al, [146] proposed the blend of fluffy rationale strategy with two dynamic strategies, AHP and GRA procedures to perform handover choice in heterogeneous remote climate. This strategy improves the consistency level contrasted with just fluffy rationale based methodology. The reenactment results were contrasted and an expense Function based and fluffy rationale based organization determination to show the viability of the methodology.

In [147], a smart organization choice plan is introduced to empower vertical handover for the joining of cell and remote LAN networks to furnish the client with ensured Qos whenever. AHP is utilized to decide the general loads of standards as indicated by client inclinations and applications, while the GRA is embraced to rank the choices in heterogeneous climate.

Qingyang Song et. al, [148] presented a novel vertical handoff choice plan to offer clients with improved Qos and augment the administrator's income. This technique offers co-usable handover choice among client and organization by characterizing

merit work and a client administrator exchange model. Semi-Markov choice interaction strategy is utilized to boost the organization income without bargaining Qos necessities.

A cross-network cross-layer based joint asset the executives system is proposed in [149] to streamline MT traffic conveyance among heterogeneous organizations to use the variety and administration task of various organizations. This structure comprises of two parts: traffic confirmation control and RAT-level radio asset the board to give traffic conveyance among RATs as per load and the traffic prerequisites of client. It amplifies the throughput of flexible traffic while keep up the Qos imperatives of inelastic applications.

A traffic-mindful Online Network Selection calculation [150] is introduced to coordinate with the Qos necessities of traffic with particular ideal organizations. The relationship among numerous traffic network choices is utilized to augment the client's QoE. The powerful online organization determination is joined with decoupled and virtual multiplexing based online organization choice calculations to improve the assembly speed of Online Network Selection calculation.

Abhijit Sarma et. al, [151] planned the Qos mindful handover strategy to carry out handover component in a Wi-Fi and WiMAX coordinated climate, which offers data transfer capacity booking for various traffic to offer support situated handover to the client. It permits the clients to play out a handover utilizing load-adjusting component to disseminate traffic load consistently across coordinated organizations while accomplishing the Qos for the end clients with low handover cost.

It is proposed in reference no. [152] that an intelligent handoff optimization algorithm for network selection in heterogeneous networks. In this research work, number of handoffs and throughput has been worked out but it doesn't tell about delay and handover failure probability.

It is proposed in reference no. [153] ES-DQN based strategy for vertical handoff. In this paper delay and throughput has been worked out but it doesn't tells anything about number of handovers and handover failure probability.

The authors have proposed in reference no. [154] presented MDP-based vertical handoff. This paper takes care of throughput and handover failure probability but doesn't give any idea about delay and number of handovers.

The authors have presented in [155] a QoS aware handoff based on service history information. In this research work delay and throughput has been worked out but doesn't give any information about number of handovers and handover failure probability.

The authors have presented in reference no. [156] a QoS-aware intelligent vertical handoff scheme. This paper takes care of delay and throughput but doesn't tell anything about number of handovers and handover failure probability.

2.3 Examination Issues for the Proposed Solution

Among the various methodologies tending to the multi-standards dynamic issue gave in the writing, a half and half based methodology is considered since it decides the capacity of the organization to fulfill the QoS prerequisites of a specific assistance. Utility capacity can be communicated numerically as a component of organization, client and administration setting. The disadvantages of the current total utility models are examined, and afterward another cross breed weighted utility capacity is proposed to give advancement between QoS, energy utilization and cost. Despite the fact that the current arrangements in the writing gives versatility in the heterogeneous organizations, there are number of issues to be tended to during network determination choice particularly when there is an enormous number of covering organizations. It is tracked down that the connected works in the writing gauge the hybrid time between the passage and leave point of MT at the limit of the organization, and perform handovers just if the assessed hybrid time is more noteworthy than the steady edge esteem. At the point when the MT is moving with high speed, it is important to discover how long the MT will remain in the objective organization. In the event that the assessed hybrid time is not exactly the edge esteem, handover to such an organization isn't valuable, as it requires more number of handovers for the fulfillment of administration. The likelihood of handover disappointments and superfluous handovers increments as the multi interface MT travels through the reconciliation of various access organizations. Hence, MT area data like speed and course is obligatory for high speed clients while defining network

choice calculation to stay away from superfluous handovers. From the writing, it is additionally discovered that MIH based methodologies select the objective organization just dependent on interface layer knowledge.

2.4 Outline

This part has assessed related writing in the field of portability the board and access network choice in heterogeneous remote organizations. Various strategies for network determination for VHD are introduced and ordered. It likewise features the significant difficulties to be tended to in the development of HWN. The difficulties gave by NGWN unmistakably underline the shortage of conventional organization driven arrangements in supporting client versatility and unavoidable applications. The audit additionally finishes up with an outline of the new examination chips away at the utility hypothesis, portability attributes and MADM based organization determination choice to offer client driven assistance arranged organization choice for versatile clients. In the accompanying section, sigmoid-based utility structure is proposed to characterize the versatility of uses. This strategy additionally adjusts the weight esteems dependent on the client's convenient inclination as for the Qos boundaries.

2.5 Summary

In the extensive literature survey it has been found that to the best of our knowledge no work has been done which clearly indicates that four parameters delay, throughput, no. of handovers and handover failure probability has been controlled simultaneously and this clearly indicates the novelty in research work.

CHAPTER 3

PORTABILITY-BASED NETWORK SELECTION

3.1 Overview

Giving worldwide availability fast and ensured quality at any spot and any time is presently turning into a reality because of the incorporation and co-appointment of various RATS like WiMAX, UMTS, WLAN, and LTE [157]. Because of the assorted qualities of heterogeneous organizations like data transmission, idleness, cost, and inclusion, a few difficulties must be tended to as far as Qos, portability the board, and client inclinations. At present, no single remote innovation professes to offer practical types of assistance, which offer high transfer speeds and low latencies to all versatile clients in a huge inclusion territory. This is the place where the requirement for an efficient VHD calculation for heterogeneous remote innovations becomes obvious [158].

After a broad writing audit, it is tracked down that the utility hypothesis-based numerical model can be utilized to measure the nature of the organization to fulfill the prerequisites of both the client and administration. In this methodology, sigmoid-based utility capacity is utilized to assess the applicant organizations [159]. A utility-based methodology is joined with client versatility (speed and bearing) in this proposed work to offer the best objective organization for high-speed clients with negligible handover rates. The current works don't think about two issues: i) interdependency among the rules during network assessment and ii) reconciliation of organization assessment utilizing sigmoid-based utility capacity for the necessary Qos with portability qualities. If the organization assessment measure isn't associated with the versatility attributes of MT, it brings about an expanded likelihood of handovers, handover disappointments, and pointless handovers, particularly for high-speed clients. In this manner, utility-based organization assessment is incorporated with client portability to improve the client level Qos [160].

To address these issues, a suitable coordinated Multi-standards network determination calculation dependent on Cuckoo search and Genetic calculation is proposed to keep the versatile clients in every case best associated anyplace and whenever in a heterogeneous climate. On the off chance that the MT speed and moving example are

sporadic, more superfluous handoff can happen. To perform effective vertical handovers in HWN, superfluous vertical handovers, and handover disappointments should be killed. It brings about an expanded flagging overhead and postponements, which thusly causes power utilization at the MT [161].

At the point when the MT is moving at high speed, it is important to discover how long the MT will remain in the objective organization. If the assessed algorithm is not exactly the versatile edge, handoff to such an organization isn't valuable, as it requires more handoff to finish the progressing administration. In this work, these variables are considered significant boundaries to choosing the objective organization in HWN. Starting here in view, this work is more imaginative in limiting the number of handover disappointments and the number of superfluous handovers [162].

In this section, the disadvantages of the current RSS-based calculation models are examined, and afterward, an adjusted crossover model is proposed to think about interdependency among the standards during network assessment. The proposed plot is executed when a client is preceding onward a bicycle or a vehicle; network choice is performed just dependent on crossover model capacity thinking about Qos (delay and information rate), energy utilization, and cost. Likewise, the MT inside the organization is assessed and versatile edge esteems are determined as an element of speed and handover inertness to keep the likelihood of handovers, handover disappointments, and pointless handovers inside the cutoff points [163].

Reproductions are led to get the exact and settled exhibition measurements to feature the viability of the proposed coordinated plan. Reproduction results show that the proposed plot outflanks against two different strategies: i) proposed conspire with fixed limit technique and ii) Handover Necessity Estimation (HNE) based strategy [164].

3.2Role of utility hypothesis in-network choice

Among the various methodologies tending to the multi-model choice issue given in the writing, the utility hypothesis-based methodology is thought of. Utility capacity decides the capacity of the organization to fulfill the Qos prerequisites of specific help. The kind of choice measurements (static or dynamic) and the number of choice measurements considered for network assessment may likewise influence the

consistency level of organization choice. If the solitary characteristic is utilized for network choice, the chosen organization may not fulfill the information rate and defer prerequisites of specific help. This causes the assistance debasement of portable clients[165].

Subsequently, there is a need to consider the different qualities of the organization to figure out the utility worth in the organization choice component. Any utility capacity can be communicated numerically as an element of properties and client inclinations. Client inclination mirrors the significance of every measurement in the choice cycle as indicated by the prerequisites of running applications (e.g., Voice over IP, Video Streaming applications) and the sort of client (cost delicate or Qos touchy client). Client inclinations are predefined weight esteems that can be put away in the client profile. It very well may be considered in the organization determination measure by including the weight esteems or by choosing a fitting utility capacity to catch client inclinations [166].

In this exploration work, a help versatile crossover model of Cuckoo search and Genetic calculation is proposed which gives improvement between Qos, energy utilization, and cost. The level of client affectability to Qos boundaries for a specific help ought to be considered in the investigation of the utility model for network determination instruments. Accordingly, it is important to consider the client's opportune inclination concerning the Qos boundaries notwithstanding the application requests to demonstrate the utility capacity adaptively. Thusly, it is utilized in the proposed work to check whether the organization fulfills the prerequisites of clients and applications [167]. The primary commitment of this work is to dispose of the invalid utility impact during the accumulation of rudimentary utility capacities and to augment the client fulfillment degree by choosing the best reasonable organization [168].

3.3 Portability-based scenario

Cutting-edge remote organizations will be consistently coordinated with different sorts of innovations and different sorts of administrations, to guarantee that clients are in every case all around associated. In this way, handoff turns into an open test for these heterogeneous organizations. As a rule, the handoff of the board is acted in three stages: Handoff commencement, target network determination, and handoff signal

handling. In the proposed position-based vertical handoff choice calculation, the initial two stages are centered around. Handoff commencement chooses when a handoff ought to be started. The objective of handoff inception is exactness in planning. To accomplish accuracy in a handoff choice, numerous handoff calculations are proposed in writing. The proposed calculation can be separated into two sorts: Position-based handoff and RSS-based handoff [169].

Speed data and the situation of the MS can be gotten from different sources, like assessment from RSS, utilization of worldwide situating framework (GPS) or helped GPS (AGPS), and so on the speed data of the MS can likewise be acquired from different techniques, like assessment, use of GPS or AGPS, gas pedal installed in the MS, etc.[170]. In addition, it is seen that different strategies are utilized to diminish the ping-pong handoff, which pointlessly happens between various administrations with a fast to-and-fro recurrence. Ping-pong handoffs are famous for expanding the flagging burden, thus different methodologies are proposed to stay away from these handoffs. A portion of the fruitful methodologies incorporate the dwelling clock technique, hysteresis edge strategy, strategies applying the normal rectangular window on RSS esteems, and utilization of the most un-square line (LSL) on RSS esteem[171].

Because of this data, a position-based vertical handoff calculation is proposed in this work. To expand the end-clients fulfillment levels, network choice, viz, the choice to choose the best organization among the accessible competitors likewise assumes a significant part [172]. Handoff choice boundaries are the characteristics that are utilized to figure out which access organization ought to be picked. We can pull together the various boundaries as follows:

Organization-related: inclusion, transfer speed, inertness, connect quality or RSS, Carrier-to-Interferences Ratio (CIR), SIR, BER, financial expense, security level, and so forth Terminal-related: speed, battery power, area data, and so on Client related: client profile and inclinations. Administration related: administration capacities, Qos, and so forth [173].

These boundaries can be ordered into static and dynamic, contingent upon the recurrence and reasons for changes. The proposed position-based calculation known as Hybrid Vertical Handoff Decision calculation (HVHD) is a consolidated calculation that joins the static boundaries of the organization like expense, accessible data transmission, and force utilization, and dynamic boundaries like RSS, speed, and position of the portable station. The expense of utilizing an organization for the client is a significant issue. The organization suppliers may well give an assortment of charging plans and alternatives that will most likely impact the client's decision of the organization, and subsequently the handoff choice. A basic yet productive reenactment is furnished to contrast the proposed calculation and different strategies [174].

3.4 Overview of Handoff Algorithms

As per the paper discussed in Handoff Mohanty and Achilles (2006), in this paper, the MS distance from the cell boundary where the handoff is to be established is determined by the condition that the objective probability of handoff depression is 0.02, and this distance is then used for multifaceted edge identification for handoff selection. Although this is an excellent technique, it is not valid when the administrative area of one help center is completely covered by another help center.

Yan et al (2008) proposed a strategy to limit wasteful handoff in different remote companies. In this technology, the travel distance of the MS is estimated by progressive RSS estimates, and the travel speed is estimated by an accelerometer installed in the MS. This distance is then manipulated and the distance is limited to limit handoff frustrations and wasted handoffs. Although this technology limits unnecessary hands-off, estimating the MS distance from the path with RSS is not exceptionally accurate and assumes that the speed of the MS is constant, which is not very practical.

Lee et al (2007) introduced a development of mindful vertical handoff calculation among WLAN and Mobile WiMAX. In this calculation, the normal speed size and heading are utilized in the handoff dynamic. The normal size of speed is utilized to ascertain the home season of the MS. It is then used to ascertain how long the MS will remain in the help space of a base station, and this home season of the MS is

contrasted with a limit time with choose whether a handoff to the objective BS is gainful or not. They arrived at the midpoint of the heading of speed utilized to decide if there is a high likelihood of ping-pong development. At that point, because of this condition (likelihood of ping-pong development), the home time is adaptively appointed to the refreshing clock. In this calculation, the solitary speed data is utilized in deciding if an objective BS is worth handoff, and in refreshing the versatile dwelling clock.

For every one of the expressed strategies, the accompanying measurements are recorded as results from the recreation.

1. Handover latency

Handover delay is the term between the commencement and finishing of the handover interaction and is identified with the intricacy of the VHD cycle. A decrease in the handover delay is particularly significant for postponing delicate voice or mixed media applications.

2..Number of handoffs

The number of handoffs done by the MS during a characterized period. Superfluous handoffs ought to be limited as they squander network assets and increment preparing overheads.

3. Handoff disappointment rate

In this reproduction, the situation of the MS is checked after every handoff. The position ought to be inside the help scope of both the old and new base stations. If this condition isn't met, that specific handoff is viewed as a handoff disappointment.

4. Throughput

The throughput alludes to the information rate conveyed to the portable terminals in the organization. Handover to an organization up-and-comer with higher throughput is generally attractive.

3.4.1 RSS-based Algorithm

In remote organizations, the capacity to adequately deal with clients' versatility and fulfill the wanted nature of administration (QoS) has been raising a lot of interest

among analysts for over 10 years now. The accessibility of fluctuating remote innovations makes heterogeneity and gives an assortment of new applications (like mixed media) that straightforwardly smooth progress across different remote organization interfaces. Group of people yet to come correspondence frameworks need to give answers for the difficulties of heterogeneous remote organizations (HWNs) by fulfilling portable clients Qos necessities. The 4G frameworks have components for giving high information move rates, viable client control, and consistent portability [161].

Several components have been proposed for Internet working, for example, strongly coupled and almost coupled models engaged in various remote innovations (Budhikot et al., 2003; Salkintzis, 2004; 3GPP, 2006; Verma et al., 2009). However, there are many difficult tasks in different organizations, including issues such as handoff, asset status, and versatility in identifying field authorities, security, and assessments. One of the versatility of working components is the hand-off advancement, which dictates how the portable terminal (MT) changes the connection point during dynamic correspondence (Achilles et al., 2004). Developmental algorithms (EAs) are broad and complex organizational progress and a good methodology for adequately treating multi-factor planning problems with different goals. In remote companies, EAs have a wide range of applications in base station settings, channel allocation, and portability of officers [162].

RSS-based algorithms provide the necessary solutions to network technologies. Let us assume in a scenario that demands good signal coverage, optimum data rate, low service cost, and high network reliability a handoff is required. To achieve these objectives, sometimes it creates handoff too early which leads to wastage of network resources and sometimes it creates handoff too late which leads to excessive power consumption and call dropping. To handle these abnormalities, RSS-based algorithms are very boon to network technologies. They overcome these abnormalities and give good results as compared to the conventional ones and achieve the desired objectives.

The handoff is suggested as a way to change the correspondence divert used in the current association while the call is in progress. This conversation takes into account the phone engineering used to expand range usage in HWN. However, it faces several issues related to the position of versatility, the limitations of choice, the selection

system, and the methodology. The handoff position can be the same or vertical (Eleantila et al., 2001; Zhu & McNair, 2004; Akhila et al., 2012). The previous refers to the development of MTs from one cell site to the next homogeneous access organization. The latter alternative (asymmetric) approach, however, depicts the comparative development of the organization. In HWN, vertical handoff may be enabled for availability or accommodation, but such selection may be subject to network-related, terminal-related, subscriber-related, and administration-related restrictions [177].

Company-related limitations are mainly related to transfer speed, idleness, received signal strength (RSS), signal-to-reduction and noise ratio (SINR), cost, and security and transmission channel. Terminal-related limits are speed, battery power, area data, etc. Client-related restrictions govern client profiles and trends, while administration-related restrictions govern administrative restrictions and quotas.

Above are some limitations for use in the handoff selection calculation. These have a signal strength that can be strongly correlated with the quality of the administration (Chen et al. 2009), and the network association time, which indicates the extent to which the subscriber is associated with the current position of the association. Connected, accessible transfer speed, which estimates existing data correspondence assets communicated every second (Inayat et al., 2005; Al Qaeda et al., 2009), power consumption becomes a primary issue. MTs battery (Syhuda and Mahmoud, 2008; Chandralekha and Behera, 2011), monetary costs, as each company has its pricing policy must be considered in addressing handover options (Chen and Hasut, 2006; Saeed, 2011), The customer's inclination towards the customer's personal preference leads to determining the type of organization that can be done on different companies (Lee et al., 2007; Tomar, 2009).

RSS-based computations are a major measure of signal strength. Vertical hand-off selection opposes the existing association's RSS to compromise on handover options (Al Qaeda et al., 2009). The main advantage of this technique is that it limits handover frustrations, wasted handovers, and association breakdowns as well as delays in handover. The data transmission-based vertical handoff takes into account additional transfer speeds, client administration requirements, and the location of MTs that can be deleted from one access network to the next (Lee et al., 2009). In case MT

Express is idle, the priority access network is assigned. It gives very good output and achieves low handover inactivity for late brittle applications. However, the ping-pong effect can be provided by these calculations.

The cost function-based vertical handoff option selects a mix of different factors such as RSS, accessible transmission capacity, administrative cost, a network coverage area, security, and battery capacity to assess the performance of the organization and target organizations. Appropriately, then the handoff will be selected. Each predictable goal in this technology is determined by the pricing requirement of the company. This technique is useful for using the cost function. This reduces the chances of interruptions to handovers and increases the level of customer satisfaction requests. The cost function-based handover option provides calculation authentication and load circulation techniques and the company that carries the most important weight work is selected as the handover target. It has the advantage of high output and low handover interruption rate (Lee et al., 2007).

In addition, half-and-half calculations use different limits or multiple rules in handover selection, depending on the computational knowledge. This method can be applied vertically by applying any computational knowledge process such as blurred logic (FL), blurred multiple attribute decision making (FMADM), artificial neural networks (ANN), simulating annealing (SA), or genetic algorithm (GA). Bin and Jiafeng (2012) proposed a fast multifaceted strategy based on the Type-2 blur logic to find and select the best hand-off-and-commerce network with the most extreme output for a different organization of vehicles. The selection reinforces the calculation. In Chandralekha and Behera (2010), client orientation with ANNs was used to execute hand-offs for the best-provided administration in a variety of accessible organizations. Broadly speaking, computational insight-based hand-off selection calculations have a high-performance complexity.

In any case, they improve customer satisfaction while roaming and have a high impact. Finally, the careful setting methodology uses the information to establish contact with the identifying data with MT and the organization. This methodology takes into account client data, organization, and gadgets, to ensure the best possible level of administration and to provide clients with an unquestionable level of availability.

3.4.2 Limitations of RSS-based Algorithms

The current techniques have a few disadvantages in that some of them have not thought about Qos prerequisites, network boundaries, and the closest base station blockage while the call is being moved. The Qos may dip under managed edge worth and associations are frequently dropped if handoff demands are not allowed at the perfect time. Likewise, they don't consider clients' inclinations and the different connection choices for versatile clients. They accomplish low throughput and are confronted with uncertain handoff choices, and expanded intricacy, now and again causing pointless handoffs and ping pong impacts which are superfluous in handoff measure. So there is a need to foster another advanced handover method for improved assistance conveyance in cell organizations. The traditional techniques for handoff advancement are not solid and financially savvy. They present trouble in execution and are reasonable for static circumstances, as it were. In this exploration work, the mixture of Genetic Algorithm (GA) and Cuckoo search is applied for streamlining delicate handoff choices in remote organizations. The utilization of GA change, hybrid, choice, and recombination methods can enormously improve the presentation of the framework. The equal and quick union nature of GA and CS makes it reasonable and versatile for tackling streamlining issues in a wide scope of utilizations including remote organizations.

In remote correspondence firms, basic handoff calculations use traditional handoff selection schemes, where the target is the opposite network and the current firm relies on Signal Strength Indication (RSSI) [178]. The hurdle in choosing RSSI is that when the MTs reach the phone limit of two BSs they get the signal characteristics from both BSs which are very close. In addition, the strength of the signal further damages the shadowing effect, which is set to make frequent and continuous nonsensical handoffs between the two BSs. This problem is called the ping-pong effect [179].

The choice is made dependent on the RSSI at the edge of the two organizations' inclusion territory utilizing the ideal inclusion idea or versatile handoff choice technique. The thought is to assess the up-and-comer networks utilizing utility capacity, utility record, and utility proportion. The utility capacity offers a benefit demonstrating Qos of the remote organizations. The utility capacity of organization j

from the perspective of a versatile client is made out of a few standardized elements, that are increased with their loads of significance $f_{i,j}$ as given in condition (3.1).

$$Utility_j = \sum_i w_i \times f_{i,j} \quad (3.1)$$

Where w_i is the weight of factor i and $f_{i,j}$ is a factor i of network j .

An MT may handoff straightaway if the utility proportion increments and may not have any desire to handoff if the utility proportion diminishes. In this model, an assessment of the framework shows that they are touchier than static choice calculations in any event when the underlying utility proportion is high. Handoff choice in remote organizations is a difficult errand and custom handoff plans are not adequate to manage consistent versatility interest within the sight of setting mindful administrations. They increment intricacy and uncertainty in handoff choice as the client's speed builds prompting increment call drop rate. Henceforth, the requirement for streamlining approaches.

3.5 Summary

In this chapter RSS based algorithms are discussed. From the discussion, it is revealed that RSS-based algorithms provide very promising solutions to the problems faced by heterogeneous wireless networks. They improve the quality of service to a great extent. But in modern technology, they lack dynamic situations and are valid only for static situations. But in the rapidly changing environment, they pose a failure to the demands of the users. So we have to refine these conventional RSS-based algorithms and we have to generate such RSS-based algorithms which are adaptive in nature. It means that they can adjust to situations as per the requirements of the user and give satisfactory solutions to the dynamically changing environment. So the proposed hybrid algorithm of cuckoo search and genetic algorithms takes care of such demands of the user and provides the best solutions. It is very beneficial to the user.

CHAPTER4

CUCKOO SEARCH AND GENETIC ALGORITHM

4.1 Introduction

Present-day remote organization configuration is trying because of the unique climate under which clients' administrations are given along these lines making boundary improvement an unpredictable assignment. This dynamic, and frequently obscure, working conditions build remote systems administration principles dependent on AI and man-made brainpower calculations (Mehboob et al., 2014). Cuckoo Search (CS) and Genetic calculations (GAs) give a grounded structure to executing computerized reasoning undertakings like characterization, learning, and improvement. Their adaptability makes them amazingly valuable in a wide scope of use spaces including remote organizations. As a meta-heuristic computational technique (Hillier and Lieberman, 2001), CS and GA have been effectively applied in the airplane and media transmission industry, chip plan, PC activity, programming creation, and monetary business sectors (Mitchell, 1998).

As per Ridley (2004), these calculations are propelled by natural advancement by mimicking and adjusting strong methods utilized by different organic entities. At the beginning of transformative figuring, improvements occurred rather autonomously from one another (Fogel, 1998), and this prompted the development of various subareas like transformative programming, advancement procedures, cuckoo search calculations, hereditary calculations, and hereditary programming (Eiben and Smith, 2003). The basic hidden thought, behind every one of these strategies, is the very to such extent that with a given populace of people, characteristic determination (natural selection) is summoned by ecological strain to develop the wellness of the populace. This is an unmistakable streamlining measure.

Streamlining assumes a significant part in taking care of various designing issues. The objective of improvement measures is to decide either the most extreme or a base worth of the issue being tackled, by and large, known as the target work [180]. These issues incorporate yet are not restricted to frameworks plan, power network activity, power age, remote correspondence steering, and minimization of energy misfortunes

during power transmission. Legitimate approvals of streamlining calculations require an appraisal of computational time and assembly rate notwithstanding the exactness to decide the base or greatest qualities [181-187]. A few scientists have developed advancement calculations dependent on nature perceptions, these calculations are known as nature-enlivened calculations.

In [188] a bat-roused calculation was created dependent on echolocation to detect the distance between a bat and its environmental factors. Molecule swarm advancement (PSO) was improved in the wake of noticing the conduct of fish and bird tutoring [189]. Differential advancement (DE) calculation was made by Storm and Prince [190] in light of populace development utilizing change, hybrid, and determination activities. Insect and honey bee calculations were created dependent on the rummaging conduct of insects and honey bees that utilize pheromone as a synthetic courier and the centralization of pheromone is viewed as a sign of value answers for the issue being tackled[191]. Recreated tempering (SA) depends on the qualities of the metal toughening measure[192].

4.2 Cuckoo Search Method

Cuckoo search (CS) calculation is likewise a nature-enlivened calculation, in light of the brood regenerative procedure of cuckoo birds to build their populace [193]. Be that as it may, CS is more viable than other nature-roused calculations. Truth be told, DE, SA, and PSO are uncommon instances of CS calculation, thus it is not astonishing why CS calculation outflanks them [194]. In [195] CS calculation beat DE calculation as far as assembly speed to arrive at an ideal arrangement. Also, CS calculation was accounted for as being more computationally proficient than the PSO [196]. Baskan [197] utilized CS calculation to limit gridlock by improving the exhibition of transportation street organizations. The target work was characterized as a sum of movement time and contributed to the cost of 16 connection limit developments. The cuckoo search delivered the best outcomes when contrasted with different strategies found in the writing. In [198] CS calculation was utilized to keep up the issue level and the voltage vacillations inside a satisfactory level, accordingly limiting genuine force misfortunes in a brilliant framework. The point of this work is to create and evaluate the exhibition of Cuckoo search calculations with expanding exchanging boundaries among nearby and worldwide irregular strolls as the number

of emphasis increments. The principal CS calculation has a straightly expanding exchanging boundary. The second CS calculation executes a dramatically expanding exchanging boundary, and the third CS calculation utilizes expanding power exchanging boundary[199].

4.2.1 Cuckoo Search

Cuckoo is a gathering of wellsprings with a momentous idea technique that differentiations strongly from other winged creature species. Some padded types of the cuckoo, for example, Ani and Guira lay eggs in shared houses. Regardless, they can purge the eggs of others to grow the further chance of their eggs. Various species utilize a methodology of brood parasitism to lay their eggs in various winged living beings or host pioneer homes. Parasitic cuckoo marking is extraordinary in homes where eggs have as of late been laid and their arrangement to lay eggs is exceptionally precise. They lay an egg in the host house which will ordinarily get quicker than the different eggs. At the point when this occurs, the external cuckoo brings out eggs that are not emerging from the house. This lead is additionally intended to diminish the chance of legitimate eggs. Likewise, cuckoo chickens outside may get more sustenance by following the call of host chickens. There are times when the host cuckoo tracks down that one of the eggs is out. In light of everything, the cuckoo either discards eggs or gives up totally the house and continues to fabricate different houses[200].

4.2.2 Levy Flights

Duty flights are unpredictable walks whose direction is subjective and their step length is gotten from demand scattering. These duty flights are performed by animals and frightening little creatures and are depicted by unexpected straight flights organized by 90-degree bends. In contrast to normal unpredictable courses, demand flights are progressively effective in inspecting enormous scope search regions. This is mostly because of vacillations in demand flights which are a lot quicker than commonplace inconsistent running. Cost flights can diminish the measure of rectification tally cycles with explicit self-assertive running by around 4 solicitations [201].

4.2.3. Cuckoo Search Algorithm

The cuckoo search estimation is a nature-enlivened computation that depends on the age of cuckoo-winged animals. When working with C.S. computations, it is required to consolidate potential plans with cuckoo eggs. Cuckoos generally lay their pre-arranged eggs in other cuckoo homes with a longing to raise them as a substitute additive for their off-springs. Ordinarily, when the cuckoo discovers that they don't have eggs in their homes, in those cases the distant eggs are either tossed out of the houses or deserted to the whole house. The C.S. progression computation is set up in three ways:

- Each cuckoo picks a home subjectively and lays one egg in it.
- The best homes with a great of eggs will be preceded by individuals to come.
- For a fixed number of homes, a host cuckoo can track down a far-off egg with a probability of $\epsilon \in [0, 1]$. For the present circumstance, the host cuckoo can either dispose of the egg or give up the home and develop another somewhere else.

The last guideline can be forced by squeezing the negligible portions of a piece of n that has new houses (with new unpredictable plans). The quality or prosperity of the appropriate response may compare to a gauge of the objective capacity. From the execution perspective, what is portrayed is that each egg in the house represents one answer, and each cuckoo can lay only one egg (so represents a course of action). We can't securely have any regard between an egg, a house, or a cuckoo. The fact of the matter is that to smother a horrendous framework in the house, another and better arrangement of origination (cuckoo egg) is utilized [202].

The above definitive guidance on having a new Settlers home (with new scatter action). The quality or goodness of the answer is comparable to the evaluation of objective work. From a usage point of view, the requested illustration is that each egg in the house represents an answer and each cuckoo can only lay one egg (thus representing an action). We cannot safely produce any products between eggs, house, or cuckoo. The fact is that the use of new and potentially improved game plans (cuckoo eggs) to displace the terrible action at home. Cuckoo gaze assessment is very effective for all progress issues because it harmonizes between scattered walks in the

neighborhood and unpredictable walks [203].

Cuckoo's examination calculation is particularly amazing for issues of headway worldwide as it keeps up concordance between sporadic strolls of neighborhoods and self-assertive strolls throughout the planet. The rationality between discretionary strolls around and throughout the planet is compelled by a standard boundary in the reach $[0, 1]$. The attribute of subjective strolls around there and throughout the planet is portrayed in Eqs. (4.1) and (4.2), separately. Their boundaries have appeared in Table 4.1.

Table 4.1: local and global random walk characteristic elements

Characteristic Element	Discourse
W_i^t and w^{et}	Current positions are chosen by arbitrary stage
ϕ	Positive advanced size scaling factor
W_i^{t+1}	Immediately adjacent place
s	Ladder position height
π	Section astute result of two vectors
T	Heavy-side operator
c_a	Used to switch among nearby and worldwide arbitrary strolls
λ	An arbitrary number from the uniform dissemination
$Z(d, \beta)$	Toll appropriation, used to characterize the progression size of irregular walk

The essential strides of the Cuckoo search calculation dependent on three standards can be summed up as the pseudo-code displayed in Calculation. 1.

$$W_i^{t+1} = W_i^t + \phi d \theta T (c_a - \lambda) \pi (w_j^t - w_k^t) \quad (4.1)$$

$$W_i^{t+1} = W_i^t + \phi Z(d, \beta) \quad (4.2)$$

Calculation 1: Cuckoo search pseudo code

Objective function $f(x)$, $x = (x_1, x_2, \dots, x_d)^T$
Create an initial population of n containing houses ($x_i = 1, 2 \dots n$)
However ($t < \text{maximum output}$) or (stop standard)
Receive cuckoo (I mean) randomly by levy circulation;
Assess it is quality/welfare F_i ;
Arbitrarily select the house between n (such as j);
Assess it is quality/welfare F_j ;
If ($f_i > f_j$)
a new solution to replace j ;
The end
Some of the more terrible houses (p_a) are desert
New works will be carried out in new areas by levy aircraft;
Have the best systems (or homes with quality systems);
Rank arrangements and track current best;
At the end
After refining

4.3 The Genetic Algorithm Scheme

Hereditary calculations are viewed as a feature of improvement procedures that impersonates the cycle of character development. The technique addresses both compelled and unconstrained improvement issues dependent on the guideline of normal choice by more than once changing a populace of individual arrangements with the end goal that at each progression, it chooses people aimlessly from the current populace to be guardians and utilizations them to create the kids for the future. This is done in a circle towards an ideal arrangement. It tends to be said anyway that most techniques for hereditary calculation share these components practically speaking (Weise, 2009): populaces of chromosomes; choice as indicated by wellness; hybrid to create new posterity; and arbitrary change of new posterity. The chromosomes of hereditary calculation generally appear as touch strings. The pseudo-

code of a basic hereditary calculation is introduced with choice, hybrid, and transformation administrators.

Pseudo-code for Genetic method

```
Operator SGA ()
{
    introduce populace;
    ascertain wellness work;
    while End Criteria Not Satisfied
    {
        select guardians for multiplication;
        perform recombination and change;
        assess populace;
    }
}
```

In this exploration work, a hereditary calculation (GA)- based methodology is utilized to assess the exhibition of Heterogeneous remote organizations to expand limit and organization execution. The conventional handoff plans are inclined to ping pong and corner impacts and fostering an enhanced handoff conspire for consistent, quicker, and less force-burning-through handoff choice testing. The GA plan can viably enhance delicate handoff choice by choosing the best-fit organization for the versatile terminal (MT) thinking about the nature of administration (QoS) prerequisites, network boundaries, and client's inclination as far as the cost of various connection focuses for the MT. The power and capacity to decide worldwide optima for any capacity utilizing hybrid and change activities makes GA a promising arrangement.

Given a target capacity to be amplified, one can haphazardly make a bunch of applicant arrangements and apply for the target work as a theoretical wellness measure - the bigger the better. In light of this wellness, a portion of the better competitors is picked to seed the cutting edge by applying recombination and

transformation to them. Recombination is a parallel administrator applied to two chosen up-and-comers (the alleged guardians) and results from a couple of new competitors (the youngsters). Transformation is an unwary administrator, applied to one competitor and results in one new applicant. Executing recombination and change prompts a bunch of new applicants (the posterity) that contend – in light of their wellness – with the old ones for a spot in the future. This interaction can be iterated until an answer is found or a formerly drawn computational line is reached. In this interaction, there are two significant powers driving advancement; 1) choice that goes about as a power-pushing quality, and 2) variety administrators (recombination and change) that make the fundamental variety, accordingly pushing curiosity.

Their consolidated application prompts improving wellness esteems in back-to-back populaces showing that advancement is streamlining. A huge number of developmental interactions are stochastic. Variety administrators are typically stochastic, since the decision on what snippets of data will be traded during recombination, just as the progressions in an applicant arrangement during transformation, are irregular. Determination administrators can be either deterministic or stochastic. In the last case, fitter people have a higher opportunity to be chosen than less fit ones, however commonly even the most vulnerable people get an opportunity to turn into a parent or to endure. The overall plan of a developmental calculation can be given as follows:

INTRODUCE populace with arbitrary people (competitor arrangements)

ASSESS (register wellness), everyone's identity,

WHILE not TERMINATION CONDITION DO

CHOOSE guardians

RECOMBINE set of chosen guardians

MUTATE *Transform the subsequent posterity*

EVALUATE *Assess the posterity*

CHOOSE *new populace from the last populace and posterity*

Introduce populace with arbitrary people (applicant arrangements)

Assess (process wellness, all things considered,

WHILE not TERMINATION CONDITION DO

CHOOSE guardians

RECOMBINE sets of chosen guardians

Transform the subsequent posterity

Assess the posterity

CHOOSE new populace from the last populace and posterity

Along these lines, this examination work considers the utilization of GA to enhance delicate handoff choices in remote organizations with dynamic channel setups. Customarily, GAs stay away from nearby optima with a high likelihood of utilizing the transformation and hybrid administrators, accordingly giving good execution in changing organization conditions[204].

The determination interaction decides the arrangements that ought to be protected for propagation while permitting others to cease to exist. In this manner, the determination administrator essentially chooses the best arrangement and disposes of the rest while keeping the populace size steady. The hybrid administrator arbitrarily picks a locus between two chromosomes to make two posterity, subsequently imitating natural recombination between two single-chromosome (haploid) creatures [205]. The transformation administrator haphazardly flips a portion of the pieces in a chromosome. A wellness work is utilized for recognizable proof of good arrangement where the wellness esteem measures the optimality of an answer. Accordingly, the worth appointed to every arrangement relies upon how close the arrangement is to the ideal arrangement of the issue. Regularly utilized strategies to execute choice are the roulette wheel choice strategy, straight positioning technique, and competition determination strategy. The hypothesis of roulette wheel determination created [206] accepting that the chromosomes are chosen dependent on their probabilities that are corresponding to their wellness esteem.

In competition determination, people are picked indiscriminately from the populace where a few competitions are played among a couple of them and the champ at every competition level is chosen for the future [205]. The exhibition of the calculation is improved by discovering a chromosome that stores explicit data about the issue just as a potential answer for the issue set. The goal of assessment work is the thing that

gives the component to assess the situation with every chromosome by making a connection between the hereditary calculation and the framework. It takes a chromosome (likely arrangement) as information and produces a number (target esteem) which is a proportion of the chromosome's presentation showing how well that chromosome takes care of the issue [207]. To look after consistency, wellness work is utilized to plan the target worth to wellness esteem relative to the utility of the person which that chromosome addresses. Even though there are various procedures utilized for this planning the two most usually utilized are windowing and direct standardization. During the regenerative stage, people are chosen from the current populace and recombined to create posterity that will establish the future[208].

Calculation 2: Genetic Algorithm

Let $t = 0$ be the age counter;

Make and instate an n -dimensional populace: $P(0)$;

rehash

Figure the target work esteem $f(x_i)$ of every x_i in the populace $P(t)$;

Decide the wellness esteems by utilizing the target work esteems $f(x_i)$;

Select guardians in $P(t)$ because of their wellness;

Perform hybrid to deliver posterity;

Perform transformation on posterity;

Supplant the current populace with posterity to shape the new age $P(t + 1)$;

Advance to the new age, i.e., $t = t + 1$;

until a halting condition is valid;

In the proposed plot, we are consolidating the cuckoo search calculation with the Genetic calculation in this manner we are refining the calculation. This is the curiosity in our exploration paper and the outcomes show that with the utilization of the proposed conspire we are getting improved and more great qualities for example data transmission, delay, throughput, and handover disappointment likelihood. The proposed objective is to improve the viability of fundamental dynamics. There is a need to pick an ideal objective framework using a successful decision calculation and play out the fundamental handovers in vertical correspondence. To the extent of

execution, it is critical to restrict power use by keeping the upward handover decision clear and the Bandwidth overhead should restrict the proportion of extra sorts out traffic used to execute handovers by achieving an ideal organize. The GA scheme can effectively optimize soft handoff decision by selecting the best fit network for the mobile terminal considering quality of service requirements, network parameters and users' preference in terms of cost of different attachment points for the MT. The robustness and ability to determine global optima for any function using crossover and mutation operations makes GA a promising solution. Each application requires assorted Qos, so the organized decision may contrast in a like way. The proposed mixture employments of GA-based design and cuckoo search tends to various remote frameworks including WIMAX, WLAN, 3G UMTS, and 4G LTE. The essential place is on progressing fragile handoff so the M.T. can channel, likewise, finds the best open access arrangements in a promising manner. To achieve this goal and to pick the best mastermind a flexible terminal when changing beginning with one framework and then onto the following requires an incredible decision calculation that chooses the best sort out for an unequivocal application that the customer relies upon the Qos boundary required. Numerically, the exhibition boundaries are addressed as follows:

- $\text{Throughput} = \frac{\text{Totalbytessent} \times 8}{\text{Totallostpacketsent} - \text{Timethefirstpacketsent}} \text{ (bits/sec)} \quad (4.5)$

- $\text{Bandwidth} = \frac{\sum_{i=0}^N \text{send}_N - \text{RetranSmitByte}_{N-x}}{\sum \text{Totalbytessent}} \quad (4.6)$

$X \leftarrow \text{Drop Packets}$

- $\text{Timedelay} = \frac{\sum_{i=0}^N \text{Timeoflastpacket} - \text{Timeofforstpacket}}{\sum_{i=0}^N \text{TotalDropPackets}} \quad (4.7)$

- $\text{Handoverfailureprobability} = \frac{\sum_{i=0}^N \text{TotalDropPackets}_i}{\sum_{j=0}^K \text{TotalDroppackets}} \quad (4.8)$

The bio-inspired algorithms (cuckoo search and genetic algorithms) are effective for those applications wherein the optimized solution is sought by considering various fitness factors. These factors are optimized by using various bio-inspired algorithms; it is done so because one particular pattern is mapped with the process of real-time application to receive the best possible outcomes of the system. Along with the vertical handoffs, the horizontal handoff can be optimized. Further, the power

adjustments of the user equipment can be subjected to the optimized conditions. Further, the next optimization can be applied in the context of the duty cycle of the user- equipment. As the user's equipment can be kept active until he is using the service of communication, however, when it is in sleep mode, the power usage and handoff can be controlled for the user equipment. The bio-inspired algorithms (CS and GA) scheme can effectively optimize soft handoff decisions by selecting the best-fit network for the mobile terminal (MT) considering quality of service (QoS) requirements, network parameters, and user's preference in terms of cost of different attachment points for the MT. The robustness and ability to determine global optima for any function using crossover, mutation, and cuckoo search operations make this proposed hybrid model a promising solution.

4.4 Summary

In randomly changing environmental fluctuations and traffic diversities the use of Genetic Algorithm and Cuckoo Search Algorithm is very much fruitful to both network operators and users. Both these algorithms can be adapted to any other network technologies after obtaining the desired simulation parameters. The use of these bio-inspired algorithms makes the system simple, robust, and generic and very much suitable for making vertical handoff decisions.

CHAPTER 5

DESIGN OF THE VERTICAL HANDOFF USING HYBRIDISATION OF CUCKOO SEARCH AND GENETIC ALGORITHM

5.1 Overview

Vertical handover frameworks have encountered various upgrades and various new advances have been introduced over the several years. There are as yet a couple of openings requiring further examination. This section gathers the traps that need further thought. There are as yet a couple of openings needing next further examination. This segment traces the openings that require next further thought.

(I) When vertical handover occurs, giving the necessary Qos over the assorted far-off frameworks is a huge issue, and raised degrees of adaptability have further troubles. To guarantee the Qos, VHO techniques ought to carefully consider customer versatility and framework conditions to pick the best candidate to arrange and play out a fast handover.

(ii) Ensuring the Qos isn't adequate to invigorate the best help of customers of Experience (CoE) is a thought that is getting importance. It is related to customer satisfaction. Given incredible frameworks organization execution need not for the most part give total satisfaction to the end customers. Therefore, there is a need to mull over customer tendencies and adaptable stuff additionally while arranging VHO methods and systems.

(iii) In heterogeneous conditions, get-to frameworks ought to be related in an ideal manner with the ultimate objective that the customers are for each situation best related. In any case, issues related to the cover frameworks organization including charging and assessing for the use of the frameworks, the leading body of other such issues between directors should be in general urge the VHO and to guarantee CoE similarly as Strength of Service (SoS). The between frameworks organization of these divergent distant frameworks has transformed into a troublesome and critical domain of exploration. Various access frameworks including 3GPP (e.g., EDGE, HSPA, UMTS, LTE) and non-3GPP (e.g., WiMAX, Wi-Fi) measures ought to be buried related in an ideal manner to give customers a fair Qos.

(iv) A homogeneous VHO evaluation approach is missing. Thusly, a commonplace methodology is needed with the objective that the examiners, fashioners, and customers viably can take a gander at and evaluate the different VHO strategies found in the composition. Hereafter, there is a need to release norms or rules on incredible practices for VHO evaluation.

5.2 Approach

The significant parts of the system involve the Hybrid GA-CS-based analyzer, Database Server, Mobile Terminal, and Wireless Access Networks. The proposed Hybrid - based system thinks about a few remote organizations like WiMAX, WLAN, 3G-UMTS, and 4G-LTE. The significant spotlight is on the advancement of delicate handoff to such an extent that the MT will sweep and track down the best accessible access networks on schedule. In enhancing handoff choice to choose the best accessible organization, the hybrid GA-CS procedure makes these three significant strides

Step 1: For example, consider versatile hubs that can move consistently in a space covered by the gathering of organizations overseen by almost six individual specialist co-ops where recreation rules comprise access organizations like GSM, CDMA, WLAN, and WIFI.

Step 2: Number of Cuckoo Birds: This boundary chooses the number of Cuckoo birds being introduced in the field space. Step Size: in the event of CSA (Cuckoo Search Algorithm), step size alludes to the distance covered by a cuckoo bird for a fixed number of emphases. It is liked to have a moderate advance size to get a successful arrangement. On the off chance that the progression size is excessively huge or excessively little,

Step 3: it prompts hereditary calculation or call hereditary calculation and discovers the populace which relies upon that organization that comes from cuckoo search and discover ideal arrangements. At the point when the versatile hub is occupied with some other work.

Step 4: Then the main enhancement plan will choose a gathering of the proper organization from the accessible organizations by thinking about non-streamlined

boundaries upsides of the multitude of organizations in heterogeneous organization climate and ship off hereditary calculations which enhance over the advanced gathering of organizations.

The hereditary calculation works in an accompanying manner:-

- The calculation makes an irregular beginning populace of remote versatile hubs.
- A succession of the new populace of portable hubs is made from people in the current age by iteratively playing out the accompanying tasks:
- Evaluating the wellness worth of competitor arrangements in the current populace.
- Selecting better arrangements called guardians dependent on their wellness.
- Choosing a few people with lower wellness esteems in the current populace as first-class people and passing them to the following populace as kids.
- Performing hybrid by joining the vector passages of two guardians to shape possibly better arrangements (posterity) for the future.
- Applying irregular changes to at least one vector section of an individual parent (transformation) to frame kids. Transformation, which adds to the variety of a populace, is regularly performed with a low likelihood, pm in the reach 0.01–0.2.
- Replacing the current populace with the youngsters made by determination, hybrid, and transformation to frame the future.

The calculation stops once a halting basis is set up, at that point the three periods of handoff (network disclosure, handoff choice, and handoff execution) become introduced. Something else, wellness esteem assessment of competitor arrangements is returned to.

Step 5: Similarly, on the off chance that we reproduce the same situation with advanced boundaries with quick cuckoo search calculation the client can discover the best gathering network in sensible time and the best organization come after hereditary calculation so by this

Step 6: we decrease the season of finding upgrade network in reason capable utilizing cross breed approach of cuckoo-search with the hereditary algorithm. so improve inactivity, data transmission, PDR and throughput, and handover disappointment likelihood.

5.3 Flowchart of the proposed model




Fig 5.1: Flowchart of the proposed model




Fig 5.2 Flowchart of the proposed model

5.4 Proposed Hybrid Algorithm 3

Input: Network Initialization

1:ProcedureNext_one (location, destination)

2:Check velocity and position for MN (Mobile Nodes)

3: $a \leftarrow \text{false}$

4:Query_MIIS_dBC (location, destination, MIIS_Pkt)

5:ifmin_cover_time (loc, DIS, MIIS.Pkt)>0 then

6:ifDiS_ReC_Probability (loc, DIS, MIIS.Pkt)>0)

7:then $a \leftarrow \text{true}$

8: Initialize the population of the host nest Return (a) While iteration<Max_netwiteration<Max_network do

9: fori=1.....N do

10:for (updating fitness functionality by Levy flight)

11:update velocity and position for Mobile node

```

12:updateNext_one (loc, dest)
13:Evaluate Threshold (TH)
14:           Update the fitness function
15:Step 2: Apply Geneticfitness function
16:           Procedure Next_one(time, Prediction window, sense prediction)
17:           Evaluate TH
18:           Filter network by Genetic Fitness value
19:           Update velocity and position of Mobile Node
20:           Step 3: The hybrid Cuckoo Search-Genetic Algorithm phase:
21:           Procedure check_next (time, Prediction window, sense prediction)
22:           for i=1.....N do
23:               Calculate the probability of crossover and
24:               Evaluate TH
25:               if converge then go to step 4
26:               else change the next position and apply step 2 till converge
27:           After convergence find
28:               Step 4:TH value Cuckoo_search_GA
29:               Evaluate parameters
30:               Calculate Cost_function (TH value)
31:               Procedure Cost Function
32:               repeat
33:               update application request list (MIIS_weights)
34:               update list of Network Preference
35:               update QOS, QOS_req(MIIS_weights)
36:               TH TH (app_req, user, Qos)
37:               Return
38:           end for
39:       end for
40:   end if
41   end if

```

In our proposed work, we have opted for hybrid optimization for optimal performance to tackle the challenges imposed by the speed of the portable hub (mobile node). For different values of velocities of the portable hub, the objective parameters (packet drop) are reduced and hence, throughput is degraded.

Furthermore, the use of hybrid optimization helps in improving the static base algorithm such as RSS. The use of RSS helps in the selection of a static threshold and this static threshold gets optimized via an optimization algorithm which is our proposed algorithm.

5.5 Reenactment Results

The created enhancement structure was reproduced in Matrix Laboratory (MATLAB) programming utilizing MATLAB's optima device and results show that an ideal MT connection point is the one with the most noteworthy handoff achievement likelihood esteem which decides the heading for effective handoff in HWN climate.

In light of the above investigation, a straightforward reproduction model is built and carried out utilizing Matlab, as talked about beneath. To approve the effectiveness of the Hybrid model-based versatile limit plot regarding client portability, outside remote climate is considered in the proposed methodology. Two-beam ground spread model is utilized to recreate the outside heterogeneous remote climate. This model gives more exact expectations at a significant distance from the transmitter than the free space model since it considers both direct (view) and ground reflection ways among CN and MT. It addresses the correspondence range as a circle around the transmitter.

Consequently, the parcel conveyance proportion is high in the two-beam ground model contrasted with other blurring models. During the reenactment, MT speed is changed from 10 km/hr to 40 km/hr to gauge the presentation measurements, for example, the number of handoffs, handover disappointment likelihood, throughput, and handover idleness. To dissect the effect of client portability on the client level Qos, for example, parcel misfortune rate and throughput, the transmission among CN and MT is broken down into the accompanying segments.

5.5.1 Reenactment Model

To assess and dissect the proposed work, a heterogeneous organization framework that is made out of two cell frameworks, for example, a Global framework for Mobile Communication , and Wireless Fidelity and Long Term Evolution structure an overlay structure, is thought of, as demonstrated in Figure 5.3.




Fig 5.3 System Model

Utilizing this model every MS moves along a straight line from some beginning stage to some end point. CBR traffic is reproduced with a bundle size of 512 bytes at the application layer and between appearance parcel seasons of 20ms. The complete reenactment time is 199 seconds. The recreation boundary esteems are given in Table 5.1.

Table 5.1 Simulation parameters

Name of the Characteristic Element	Value of the Characteristic Element
Simulation range	1999 * 1999
Simulation duration	199 seconds
Transmission radius of LTE	100 meters
Transmission radius of GSM	500 meters
Transmission radius of WIFI	500 meters
LTE transmission power	0.0134W
GSM transmission power	0.5W
WIFI transmission power	0.5W
Packet size	512 bytes
Inter-arrival packet time	20ms
Mobility model	Random direction model

Situation 1: For the Vertical handoff commencement plot, it is accepted that the MS is in LTE. Various boundaries for this situation have appeared in Table 5.2.

Table 5.2 Various boundaries for current PoA

CharacteristicElement	Values
Current PoA	LTE
Traffic	CBR
Weight Scheme	Hybrid Model of Cuckoo and Genetic
MS-Velocity (km/hr)	10
MS-PoA Distance (m)	70
RSS of MS (dbm)	-55.8

In light of the boundary esteems, the RSS of the MS is more noteworthy than the edge of the current organization, LTE and the situation of the MS is lower than the position edge. The MS won't play out the handoff and stay associated with its present PoA.

Situation 2: Assuming the MS moves away with a speed of 10m/s from its present PoA, the distance between the LTE-AP and the MS increments, and the RSS gets more fragile. The new boundary set is introduced in Table 5.3.

Table 5.3 Characteristic Elementesteems when MS moves from the current PoA

Characteristic Element	Values
Current PoA	LTE
Traffic	CBR
Weight Scheme	Hybrid Model of Cuckoo and Genetic
MS-Velocity (km/hr)	10
MS-PoA Distance (m)	90
RSS of MS (dbm)	-60 (undetectable)

As the MS is moving, the upward handoff network determination plot detects the accessibility of three distinct organizations. The boundary esteems for these three organizations are introduced in Table 5.4.

Table 5.4 Network Characteristic Element Values

Characteristic Element	LTE	GSM	WIFI
Offered bandwidth	3mbps	385kbps	451kbps
Power consumption	4 hours	3.5 hours	3 hours
Cost	11 Rs/min	6Rs/min	3Rs/min
RSS threshold	-61dBm	-90dBm	-91dBm

The organization choice calculation discovers the best accessible organization that can uphold the coherence and nature of the current assistance as far as progressively changing the organizational climate. It is seen that, in light of the organizational boundaries and their related climate, the versatile station favors the GSM organization.

The level of organization association is a metric that is utilized to assess the presentation of the plan. This measurement shows the level of organizations' associations that the proposed conspire likes foramina MS moving with a speed of 0-10 m/s. This rate is determined after the framework finishes the whole reproduction. The Hybrid model calculation favors WIFI roughly 100% of the time for the more slow-moving versatile station. At medium speed, the MS is associated with WIFI around 47% of the time and GSM roughly 52% of the time for the whole recreation time frame. At fast, GSM is favored roughly 72% of the time.

Five methods are compared with each other in this simulation model, which is (1) the Random or Static parameters based algorithm (2) the RSS-based algorithm and the (3) Cuckoo Search Algorithm (4) the Genetic Algorithm (5) the Proposed Hybrid algorithm, which is named as Hybrid Vertical Handoff Decision algorithm (HVHD). In method 1, the static parameters of the network alone are considered for the handoff process, and hence, results in a lot of false handoffs. In method 2, the RSS of the MS relating to its administration BS is contrasted and the sign strength limit of BS. If it is lesser than the threshold, a handoff is performed. Velocity information is not considered for handoff initiation. In the HVHD algorithm, method 5, a handoff is performed when the RSS of the MS is lower than the threshold of the respective service BS and the distance of the MS from the BS is greater than the threshold distance $a v$. In addition to the RSS of the MS, this calculation uses the position and

speed data of the MS and the dynamic parameters of the network to make a handoff decision.

5.5.2 Realization and Representation of Objectives

For every one of the expressed strategies, the accompanying measurements are recorded as results from the reproduction.

1. Handover Delay

Handover inertness or delay is the defer experienced when the MT is detached from the previous base station until it gets the primary parcel from the next base station. Its variety of different handovers during recreation has appeared in Figure 5.4. It brings about because of deferrals brought about by handover setting off, development discovery, address designation, and meeting reconfiguration. There is no impact of speed on handover idleness. HVHD influences the handover idleness during the redirection of the traffic stream to the new base station. It is derived that the time needed for building up the association with UMTS is higher than the deferral related to UMTS to WLAN handover. This is because of deferrals experienced from the interaction, for example, the conveyor and the passage arrangement for the UMTS organization. It is found in [76] that the lone setting mindful technique without MIHF has a dormancy of 140-160 milliseconds for WLAN to UMTS handover. Since the proposed EMIH helps the HDM by gathering the data and setting off the handover inception at the right time, handover inertness is diminished to 21-23 milliseconds i.e., by 85% when it is contrasted with just setting mindful VHD conspire [76]. To feature the productivity of the proposed plot, a handover defer examination is performed between network choice utilizing the MIH approach and setting mindful organization choice without utilizing MIH conspire.




Fig 5.4: Comparison of Delay

The analysis of the graph shown in Figure 5.4 indicates a delay under different velocities of the mobile node. This analysis uses four kinds of wireless channels with different groups of nodes. The speed of the portable hub (mobile node) increases the effects on the performance of the node and the network-based scenario. In the case of different velocities, the condition of handoff variants although it is extremely hard to decide what sort of sensor group handovers the delay to mobile. This decision results in the use of static, dynamic, and optimizes base algorithms. It further consists of improving the bandwidth using selecting an effective sensor channel or vertical Handover's selecting an effective bandwidth employing hybrid and single optimization approaches. In the proposed approach, the use of hybrid optimization helps in improving the static base algorithm such as RSS. The use of RSS helps in the selection of a static threshold and this static threshold gets optimized via an optimization algorithm. In most cases, the optimization approach does not converge and provides a random answer which further reduces the performance of delay. In the proposed approach, the cuckoo search and genetic algorithm are also used. This methodology iteratively improves the performance of the cuckoo search. The graph indicates a significant improvement in delay using the proposed hybrid approach as compared to the existing approach and other single optimization methodologies.

2. Number of handoffs

The number of handoffs completed by the MS during a characterized period. Pointless handoffs ought to be limited as they squander network assets and increment handling overheads. In Figure 5.5, the absolute number of handoffs that happened in the recreation for every technique is portrayed against different speeds. From Figure 5.5, it is seen that without position data of the MS, for example, the static boundary-based and RSS-based techniques have a more noteworthy number of handoffs than HVHD calculation. The colossal decrease in the number of handoffs is one of the significant accomplishments of the calculation. The quantity of handoffs experienced by the HVHD calculation is multiple times and multiple times lesser than that of the static and RSS-based calculations individually.




Fig. 5.5 Comparison of Number of Handoffs

The analysis of the graph shown in Figure 5.5 indicates the number of handovers under different velocities of the mobile node. Increasing the Handover increases the overhead and its effects on delay and on the other hand, it increases the drop rate, reduces the throughput but increases the delay of the system. This analysis uses four kinds of wireless channels with different groups of nodes. The speed of the portable hub (mobile node) increases the effect on the performance of the node and the network-based scenario. In the case of different velocities, the condition of handoff variants though it was extremely hard to make the decision that what sort of sensor group handovers effectively which further reduces the delay and it reduces its effect

on the number of handover failures. This decision results in the use of static, dynamic, and optimizes base algorithms. It further consists of improving the bandwidth employing selecting an effective sensor channel or vertical Handover's selecting an effective bandwidth employing hybrid and single optimization approaches. In the proposed approach, the use of hybrid optimization helps in improving the static base algorithm such as RSS. The use of RSS helps in the selection of a static threshold and this static threshold gets optimized via an optimization algorithm. In most cases, the optimization approach does not converge and provides a random answer which further reduces the performance of time delay. In the proposed approach, the cuckoo search and genetic algorithm are also used. This methodology iteratively improves the performance of a cuckoo search. The graph indicates a significant improvement in Handover using the proposed hybrid approach as compared to the existing approach and other single optimization methodologies.

3. Throughput

Throughput alludes to the information that is sent by the MS during a characterized period. It mirrors the vigor of the choice plan. The recreations are performed for static boundary-based, RSS-based, and HVHD calculations.

The outcomes for the throughput are given in Figure 5.6 when the versatile client is moving in the WLAN inclusion from GSM. It has unmistakably appeared in the chart that without the calculation when the portable station is utilizing WLAN organization, the throughput corrupts when the speed increments. It is because the WLAN innovation is delicate when the clients move with higher velocities. After applying the HVHD calculation, the outcomes are improved for the throughput when the versatile station is joined to the GSM network during the time it is crossing the WLAN cell. Results are improved because the upward handoff measure is kept away from albeit the MS is situated in the WLAN inclusion. They can in any case utilize the GSM, so there is no compelling reason to perform handoff to the WLAN passageway. These realities and the improved outcomes for the throughput legitimize the advantage of the HVHD calculation. The accomplished throughput of the EVHD calculation is 35.4% and 26.4% more than that of the static and RSS-based calculations individually.

Considering the communicated diagrams, the HVHD estimation performs better similar to the number of handoffs, handoff frustration rate, and throughput appearing

differently concerning the static limit-based, and RSS-based computations. The show assessment of the HVHD with other handoff estimations is given in Table 5.4.




Fig. 5.6 Comparison of throughput

The analysis of the graph shown in Figure 8 indicates throughput under different velocities of the mobile node. This analysis uses four kinds of wireless channels with different groups of nodes. The speed of the portable hub (mobile node) increases the effects on the performance of the node and the network-based scenario. In the case of different velocities, the condition of handoff variants reduces the packet drop and delay effect on the parameter of the throughput. However, it is extremely hard to decide what sort of sensor group handovers effectively. This decision results in the use of static, dynamic, and optimizes base algorithms. It further consists of improving the bandwidth utilizing selecting an effective sensor channel or vertical Handover's selecting an effective bandwidth employing hybrid and single optimization approaches. In the proposed approach, the use of hybrid optimization helps in improving the static base algorithm such as RSS. The use of RSS helps in the selection of a static threshold and this static threshold gets optimized via an optimization algorithm. In most cases, the optimization approach does not converge and provides a random answer which further reduces the performance of time and the rate of packet drop. In the proposed approach, the cuckoo search and genetic algorithm are also used. This methodology iteratively improves the performance of the cuckoo search. The graph indicates a significant improvement in throughput using

the proposed hybrid approach as compared to the existing approach and other single optimization methodologies.

4. Handoff failure rate

In this recreation, the situation of the MS is checked after every handoff. The position ought to be inside the assistance scope of both the old and new base stations. If this condition isn't met, that specific handoff is viewed as a handoff disappointment.

From Figure 5.7, it is seen that static boundary-based, and RSS based, have more handoff disappointment rates than the EVHD calculation. The MS with higher speed will cross the limit of the current BS prior when contrasted with sluggish MS and in this way, a handoff is needed to be started before finishing the handoff system on schedule. In the EVHD calculation, the handoff commencement trigger is produced before for high speeds of the MS which thus lessens the handoff disappointment rate. The handoff disappointment rate in the EVHD calculation is multiple times and 1.6 occasions lesser than that of the static and RSS-based calculations individually, at 5m/s speed.




Fig 5.7 Comparison of handoff failure probability

The analysis of the graph shown in Figure 5.7 indicates handover failure probability under different velocities of the mobile node. Handover failure probability increases the drop rate and affects delay and on the other hand, it reduces the throughput of the system. This analysis uses four kinds of wireless channels with different groups of

nodes. The speed of the portable hub (mobile node) increases the effect on the performance of the node and the network-based scenario. In the case of different velocities, the condition of handoff variants though is extremely hard to decide what sort of sensor group handovers effectively which further reduces the delay and also reduces its effect on the parameter of handover failure. This decision results in the use of static, dynamic, and optimizes base algorithms. It further consists of improving the bandwidth utilizing selecting an effective sensor channel or vertical Handover's selecting an effective bandwidth employing hybrid and single optimization approaches. In the proposed approach, the use of hybrid optimization helps in improving the static base algorithm such as RSS. The use of RSS helps in the selection of a static threshold and this static threshold gets optimized via an optimization algorithm. In most cases, the optimization approach does not converge and provides a random answer which further reduces the performance of time delay. In the proposed approach, the cuckoo search and genetic algorithm are also used. This methodology iteratively improves the performance of a cuckoo search. The graph indicates a significant improvement in handover failure using the proposed hybrid approach as compared to the existing approach and other single optimization methodologies.

Table 5.5 Comparison of the handoff decision methods

Algorithm	Handover Delay(ms)			No. of handoffs			Throughput (Packets/Ms)			Handoff Failure Probability		
	10	20	30	10	20	30	10	20	30	10	20	30
Velocity(km/hr)												
Random	1.45	1.40	1.35	3	6	6.6	10.1	11	11.5	0.145	0.130	0.125
RSS	1.30	1.35	1.25	2	3.2	4	10.2	11	10.5	0.132	0.110	0.115
CSA	1.20	1.20	1.15	0	0	1	10.5	12	11.5	0.125	0.110	0.105
GA	1.25	1.20	1.15	1	2	2.4	11.1	13.1	13.5	0.115	0.100	0.095
HVHD	0.85	.80	0.75	0	0	1	12.5	13	13.5	0.090	0.080	0.075

The exhibition examination uncovers that the HVHD calculation outflanks the current calculations in accomplishing a lesser number of handoffs and handoff failure rate and thereby higher throughput. The work suggests that the HVHD algorithm is efficient in making the handoff decision. This unit presents the results of the proposed model. The methodology of research proposed in this thesis is analyzed against four methods which are explained above The random method, RSS method, Cuckoo method, and

Genetic method. The results demonstrate that the novel proposed technique has the best advantage. Thus, it helps to achieve the objectives of the research study.

5.6 Summary

In this work, a position-based vertical handoff choice calculation is proposed. This calculation joins the static boundaries of the organization, for example, cost, accessible data transfer capacity, and force utilization, and dynamic boundaries like RSS, speed, and position of the portable station for handoff inception and organization determination plans. It is tracked down that the speed and position of the MS have a gigantic impact on the handoff dynamic. As per the recreation results and Table 5.4, it is reasoned that the proposed calculation outflanks different strategies, by offering consistent support with low handoff disappointments and high throughput.

The proposed incorporated plan diminishes the pointless handovers and administration disturbance time by setting off the handover cycle precisely utilizing both connection layer and application layer data. Ongoing reenactment results approve the effectiveness of the proposed approach as far as improving the normal throughput by 14% and 39%, diminishing the parcel misfortune rate by 16% and 36% contrasted with the steady edge and MIH with PRMC-based organization determination plans. It additionally diminishes the handover delay by 85% contrasted with the lone setting mindful organization choice plan.

CHAPTER 6

CONCLUSION AND FUTURE WORK

This section presents the end drawn from the examination and recommends a few headings for the extent of future exploration work.

6.1 Overview

Always developing broadcast communications industry and web advancements drive the advancement towards furnishing clients with pervasive help access and consistent availability in a multi-administrator and multi-client climate. Subsequently, the clients can interface with the web from any place whenever, particularly, when the client is moving. To provide food for the exceptional development in the field of portable internet providers, network administrators have begun to convey the intermingling of various, covering radio access advancements. The principle challenge in a particularly heterogeneous remote climate is to empower the joining of Qos and portability support in network choice instruments to keep the versatile clients in every case best associated with the organization while limiting the VHO rate and augmenting the end client fulfillment.

6.2 Examination Contributions

This research work presents the user-centric, service-oriented, mobility-based network selection strategy for heterogeneous wireless networks by proposing four major solutions as listed below:

Multiplicative weighted utility capacity – guarantees the ensured Qos for mixed media benefits by assessing the organizations utilizing first degree of measures, for example, sigmoidal-based utility estimation. The information rate and defer prerequisites of administration are utilized to measure the quality upheld by a specific access organization. The energy utilization metric (J/Kbps) is determined for various classes of administration as indicated by the information rate necessities. The rudimentary utilities of Qos, cost, and energy utilization are determined utilizing sigmoidal capacity thinking about the base and greatest necessities for every measure. Association between the rules is considered during network assessment to wipe out the invalid utility impact while totaling the rudimentary utilities. The general utility

capacity is determined for each organization by accumulating the rudimentary utilities of choice measurements utilizing multiplicative weighted utility capacity. After the assessment of organizations, the accessible organizations are positioned in slipping requests dependent on the worth of worldwide utility capacity. The organization with the most extreme utility capacity is chosen as the objective organization.

A combination of utility capacity with the Hybridization of Cuckoo Search and Genetic Algorithm based organization determination is discussed to limit the likelihood of handovers, superfluous handovers, and handover disappointments. The utility-based organization choice is incorporated with client versatility to give client-driven, administration-situated portability-based organization choice to accomplish organization, client, and administration intermingling. In this work, hybridization is determined for the high-speed client moving along a straight-line direction especially in a covering area of accessible organizations to diminish the number of handovers.

The proposed plot is carried out with two standards (the person-on-foot clients and high-speed clients). For the person-on-foot clients, network determination is performed just dependent on multiplicative utility capacity though for high-speed clients, Adaptive Hybridization is determined to keep the likelihood of handover disappointments and superfluous handovers inside the cutoff points. Through the proposed model, it is demonstrated that the proposed versatile limit conspire outflanks against consistent edge plot by decreasing the likelihood of handovers, handover disappointments, and superfluous handovers by 25%, 16%, and 8% separately for the speed of 40 m/s.

Consequently, steady edge esteem can't be utilized as a choice measurement to perform handover for high-speed clients. It is additionally contrasted and the presentation of the HNE technique to show that the proposed network determination dependent on multiplicative utility capacity and hybridization lessens the likelihood of handovers by 40% and keeps the likelihood of handover disappointments and pointless handovers to the planned worth of $P_f = P_u = 0.02$. Consequently, the proposed versatile edge plot keeps the likelihood of handovers, handover disappointments, and superfluous handovers inside as far as possible.

Hybridization of Cuckoo Search and Genetic Algorithm incorporates the Cuckoo Search and Genetic Algorithm administrations with portability,

administration, client, and organization setting to improve the effectiveness of the HVHD-based organization choice system. Moreover, another degree of handover capacity like the Media Independent Handover Function (MIHF) is introduced to convey ideal handover for high-speed clients. HVHD structure upholds the organization revelation interaction and handover setting off occasions dependent on the connection layer knowledge. HVHD system gives total data about the connection layer and application layer to Handover Decision Module to give the best organization to complete the handover effectively. Ongoing recreation results approve the effectiveness of the proposed approach as far as improving the normal throughput by 14% and 39%, diminishing the parcel misfortune rate by 16% and 36% contrasted with the Cuckoo search and Genetic Algorithm based organization choice plans. It likewise decreases the handover delay by 85% contrasted with the solitary RSS-based strategies.

6.3 Extension for Future Work

The fundamental focal point of the work introduced in this proposition is to propose a logical answer for access choice of high-speed clients in HWN. Although numerous arrangements are accessible in the writing for network determination, there are still some open issues that require further examination.

The valuing models utilized by various organization administrators ought to be researched during network determination measures because of the conjunction of numerous specialist co-ops and RAT. In this theory, just innovation-based evaluation is considered to improve the examination of organization choice.

- More often than not, portable clients might be associated with the omnipresent UMTS organization. Hence, different organizations like WiMAX and WLAN would be under-used, subsequently making an uneven burden across various co-found organizations. The uneven burden in covering inclusion territory may prompt high call hindering and dropping probabilities. It requires further examination to concentrate on network level Qos, for example, new call obstructing and handoff dropping probabilities concerning load adjusting and dynamicity of organization determination because of elements of client requests and remote climate.

- The HVHD-based organization determination plan might be carried out in various versatility situations and the impact of MT speed on connect going down edge esteem i.e., interface quality can be examined to keep away from too soon or past the point of no return commencement of handover.
- The effect of channel corruption on the client level Qos might be dissected by considering blurring models like shadowing and multi-beam models and expanding the number of clients in the HVHD-based organization determination plot. Giving energy-proficient arrangements by breaking down the effect of portability and handover conventions regarding load adjusting among the joining of various organizations might be a significant future investigation towards energy preservation of versatile terminals.
- Organization determination for undeniable level interactive media applications like HDTV, and full movement video can be accomplished by coordinating LTE/LTE-Advanced organizations with non-3GPP advances.

The Quality of administration (Qos) ought to improve. Supporting sight and sound applications with various Qos prerequisites within the sight of expanded remote access advancements is another difficult issue for 4G remote organizations. In such networks, depending on the data transfer capacity, versatility, and application necessities, clients will want to switch among the diverse access innovations consistently. Efficient radio assets the executives and call confirmation control techniques will be key parts in such heterogeneous remote frameworks supporting different kinds of uses with various Qos prerequisites.

The call drop likelihood of the versatile client diminishes. To offer remote types of assistance whenever and anyplace, consistent terminal versatility should be upheld in 4G organizations. Portable clients will want to meander across the geographic limits of remote organizations through versatility on the board. In this way, the call drop likelihood will diminish.

The quantity of portable client's increments. At the point when 4G administrations are dispatched, clients will be normal from generally various areas, occupations, and financial classes. To oblige the requests of these different clients, specialist co-ops

should configuration customize a lot of benefits. Along these lines, the number of versatile clients will naturally increment.

- As of now proposed VHD calculations either come up short on a far-reaching thought of different network boundaries or the examinations announcing these calculations need sufficient detail for execution lamentably. The examination of vertical handover choice calculations in heterogeneous networks is as yet a difficult region. The fundamental trouble is conceiving a calculation that is genuinely valuable in wide-going conditions and client inclinations. One potential arrangement would be, given that the computational force of handsets improves exceptionally consistently, to carry out a few VHD calculations in a handset and receive versatile strategies that pick a calculation astutely dependent on conditions and client inclinations.

6.4 Summary

So a mobility prediction based model is discussed that takes care of every possible situations and satisfy the user requirements . In future it can be used in the variation in the number of customers and variation in the number of technologies. Also it can be tested for lesser power consumption. These opportunities will make this hybrid model of cuckoo search and genetic algorithm more successful.

RUNDOWN OF PUBLICATIONS

During the time of program, a few examination papers were distributed for distribution in peer investigated worldwide diaries and meeting procedures. The natty gritty arrangements of these papers applicable to the current PhD program are attached underneath:

PUBLICATIONS

SCI INDEXED JOURNAL (SUSTAINABILITY)

1.KeshavJha, Akhil Gupta et al. , “CSVAG: Optimizing Vertical Handoff using Hybrid Cuckoo Search and Genetic Algorithm-based Approaches”, Sustainability, MDPI, Vol. 14,8547,2022.

UGC APPROVED JOURNAL (GRADIVA REVIEW JOURNAL)

2.Keshav Jha, Akhil Gupta et al, “Future 5G Networks enabling smooth and secure vertical Handovers”

PAPERS IN NATIONAL/INTERNATIONAL CONFERENCE PROCEEDINGS

3.Jha, Keshav, and Akhil Gupta. "20 A critical survey on vertical handoff algorithms." *Intelligent Circuits and Systems* (2021): 113.

4.Jha, Keshav, and Akhil Gupta. "22 A comprehensive anatomy for handover probability in heterogeneous wireless networks." *Intelligent Circuits and Systems* (2021): 129.

5.Jha,Keshav and Sajjan Singh.” A Review on Vertical Handover Decision Based Strategies in Heterogeneous Wireless Overlay Networks.” *International Journal of Control Theory and Applications*(2017).

BIBLIOGRAPHY

- [1] Trestian, Ramona, Olga Ormond, and Gabriel-MiroMuntean. "Energy–quality–cost tradeoff in a multimedia-based heterogeneous wireless network environment." *IEEE Transactions on Broadcasting* 59.2 (2013): 340-357.
- [2] Sauter, Martin. *Beyond 3G: Bringing Networks, Terminals, and the Web Together*. John Wiley & Sons, 2009.
- [3] Gustafsson, Eva, and Annika Jonsson. "Always best connected." *IEEE Wireless communications* 10.1 (2003): 49-55.
- [4] Lampropoulos, George, Apostolis K. Salkintzis, and Nikos Passas. "Media-independent handover for seamless service provision in heterogeneous networks." *IEEE Communications Magazine* 46.1 (2008): 64-71.
- [5] Khattab, Omar, and Omar Alani. "Survey on media independent handover (MIH) approaches in heterogeneous wireless networks." *European Wireless 2013; 19th European Wireless Conference*.VDE, 2013.
- [6] Ezzouhairi, A., A. Quintero, and S. Pierre. "A fuzzy decision making strategy for vertical handoffs." *2008 Canadian Conference on Electrical and Computer Engineering*.IEEE, 2008.
- [7] He, Qing. "A fuzzy logic based vertical handoff decision algorithm between WWAN and WLAN." *2010 International Conference on Networking and Digital Society*.Vol.2.IEEE, 2010.
- [8] Nguyen-Vuong, Quoc-Thinh, NazimAgoulmine, and YacineGhamri-Doudane. "Terminal-controlled mobility management in heterogeneous wireless networks." *IEEE Communications Magazine* 45.4 (2007): 122-129.
- [9] Xie, Guannan, et al. "A user-preference-aware terminal-controlled access network selection scheme in heterogeneous wireless networks." *2013 IEEE 78th Vehicular Technology Conference (VTC Fall)*.IEEE, 2013.
- [10] Lee, SuKyoung, et al. "Vertical handoff decision algorithms for providing optimized performance in heterogeneous wireless networks." *IEEE transactions on vehicular technology* 58.2 (2008): 865-881.
- [11] Kassar, Meriem, Brigitte Kervella, and Guy Pujolle. "An overview of vertical handover decision strategies in heterogeneous wireless networks." *Computer communications* 31.10 (2008): 2607-2620.

- [12] Ahmed, Atiq, Leila MerghemBoulahia, and Dominique Gaiti. "Enabling vertical handover decisions in heterogeneous wireless networks: A state-of-the-art and a classification." *IEEE Communications Surveys & Tutorials* 16.2 (2013): 776-811.
- [13] Ernst, Jason B., Stefan C. Kremer, and Joel JPC Rodrigues. "A survey of QoS/QoE mechanisms in heterogeneous wireless networks." *Physical Communication* 13 (2014): 61-72.
- [14] Nguyen-Vuong, Quoc-Thinh, NazimAgoulmine, and YacineGhamri-Doudane. "A user-centric and context-aware solution to interface management and access network selection in heterogeneous wireless environments." *Computer Networks* 52.18 (2008): 3358-3372.
- [15] Niyato, Dusit, and EkramHossain. "Dynamics of network selection in heterogeneous wireless networks: An evolutionary game approach." *IEEE transactions on vehicular technology* 58.4 (2008).
- [16] Miyim, A. M., Mahamod Ismail, and RosdiadeeNordin. "Vertical handover solutions over LTE-advanced wireless networks: An overview." *Wireless personal communications* 77.4 (2014): 3051-3079.
- [17] Zahran, Ahmed H., Ben Liang, and Aladdin Saleh. "Signal threshold adaptation for vertical handoff in heterogeneous wireless networks." *mobile Networks and Applications* 11.4 (2006): 625-640.
- [18] Mohanty, Shantidev, and Ian F. Akyildiz. "A cross-layer (layer 2+ 3) handoff management protocol for next-generation wireless systems." *IEEE transactions on mobile computing* 5.10 (2006): 1347-1360.
- [19] Yan, Xiaohuan, Y. AhmetŞekercioğlu, and Sathya Narayanan. "A survey of vertical handover decision algorithms in Fourth Generation heterogeneous wireless networks." *Computer networks* 54.11 (2010): 1848-1863.
- [20] Lee, SuKyoung , et al. "Vertical handoff decision algorithms for providing optimized performance in heterogeneous wireless networks." *IEEE transactions on vehicular technology* 58.2 (2008): 865-881.
- [21] Yang, Kemeng, IqbalGondal, and Bin Qiu. "Context aware vertical soft handoff algorithm for heterogeneous wireless networks." *2008 IEEE 68th Vehicular Technology Conference*.IEEE, 2008.
- [22] Chen, Ling-Jyh, et al. "Enhancing QoS support for vertical handoffs using implicit/explicit handoff notifications." *Second International Conference on*

Quality of Service in Heterogeneous Wired/Wireless Networks (QSHINE'05).
IEEE, 2005.

- [23] Zhu, Fang, and Janise McNair. "Optimizations for vertical handoff decision algorithms." *2004 IEEE Wireless Communications and Networking Conference (IEEE Cat.No. 04TH8733)*. Vol. 2. IEEE, 2004.
- [24] Hasswa, Ahmed, Nidal Nasser, and HossamHassanein. "A seamless context-aware architecture for fourth generation wireless networks." *Wireless Personal Communications* 43.3 (2007): 1035-1049.
- [25] Tawil, Rami, Guy Pujolle, and Oscar Salazar. "A vertical handoff decision scheme in heterogeneous wireless systems." *VTG Spring 2008-IEEE Vehicular Technology Conference*. IEEE, 2008.
- [26] Nasser, Nidal, Ahmed Hasswa, and HossamHassanein. "Handoffs in fourth generation heterogeneous networks." *IEEE Communications Magazine* 44.10 (2006): 96-103.
- [27] Pahlavan, Kaveh, et al. "Handoff in hybrid mobile data networks." *IEEE Personal Communications* 7.2 (2000): 34-47.
- [28] Xia, Liu, L-G. Jiang, and Chen He. "A novel fuzzy logic vertical handoff algorithm with aid of differential prediction and pre-decision method." *2007 IEEE international conference on communications*. IEEE, 2007.
- [29] Bhute, Harsha A., P. P. Karde, and V. M. Thakare. "Vertical handover decision strategies in heterogeneous wireless networks." *International Conference on Recent Trends in Information, Telecommunication and Computing, ITC. Citeseer*. 2014.
- [30] Hua, Li, MdHumayunKabir, and Takuro Sato. "Velocity adaptive vertical handoff on multi-frequency system." *2009 IEEE 20th International Symposium on Personal, Indoor and Mobile Radio Communications*. IEEE, 2009.
- [31] Yan, Xiaohuan, Nallasamy Mani, and Y. AhmetSekercioglu. "A traveling distance prediction based method to minimize unnecessary handovers from cellular networks to WLANs." *IEEE communications letters* 12.1 (2008): 14-16.
- [32] McNair, Janise, and Fang Zhu. "Vertical handoffs in fourth-generation multinet network environments." *IEEE Wireless communications* 11.3 (2004): 8-15.

- [33] Austin, Mark D., and Gordon L. Stuber. "Velocity adaptive handoff algorithms for microcellular systems." *IEEE Transactions on Vehicular Technology* 43.3 (1994): 549-561.
- [34] Austin, Mark D., and Gordon L. Stüber. "Direction biased handoff algorithms for urban microcells." *Wireless Personal Communications* 3.3 (1996): 287-298.
- [35] Zheng, Li, Wang Yu, and Wu Weiling. "Position location and direction assisted handoff algorithm in DWCS." *2004 IEEE 15th International Symposium on Personal, Indoor and Mobile Radio Communications (IEEE Cat.No. 04TH8754)*. Vol. 1. IEEE, 2004.
- [36] Tripathi, Nisliith D., Jeffrey H. Reed, and Hugh F. VanLandingham. "An adaptive direction biased fuzzy handoff algorithm with unified handoff candidate selection criterion." *VTC'98.48th IEEE Vehicular Technology Conference. Pathway to Global Wireless Revolution (Cat.No. 98CH36151)*. Vol. 1. IEEE, 1998.
- [37] Chuah, Chen-Nee, and Roy D. Yates. "Evaluation of a minimum power handoff algorithm." *Proceedings of 6th International Symposium on Personal, Indoor and Mobile Radio Communications*. Vol. 2. IEEE, 1995.
- [38] Calvagna, Andrea, and Giuseppe Di Modica. "A user-centric analysis of vertical handovers." *Proceedings of the 2nd ACM international workshop on Wireless mobile applications and services on WLAN hotspots*. 2004.
- [39] Hasswa, Ahmed, Nidal Nasser, and Hossam Hassanein. "Generic vertical handoff decision function for heterogeneous wireless." *Second IFIP International Conference on Wireless and Optical Communications Networks, 2005. WOCN 2005*. IEEE, 2005.
- [40] Nguyen-Vuong, Quoc-Thinh, Nazim Agoulmine, and Yacine Ghamri-Doudane. "A user-centric and context-aware solution to interface management and access network selection in heterogeneous wireless environments." *Computer Networks* 52.18 (2008): 3358-3372.
- [41] Wei, Qing, et al. "Context-aware handover using active network technology." *Computer Networks* 50.15 (2006): 2855-2872.
- [42] Ahmed, Tansir, Kyandoghere Kyamakya, and Markus Ludwig. "Design and implementation of a context-aware decision algorithm for heterogeneous networks." *Proceedings of the 2006 ACM symposium on applied computing*. 2006.

- [43] TalebiFard, Peyman, and Victor CM Leung. "A dynamic context-aware access network selection for handover in heterogeneous network environments." *2011 IEEE conference on computer communications workshops (INFOCOM WKSHPS)*.IEEE, 2011.
- [44] Zekri, Mariem, BadiiJouaber, and DjamalZeghlache. "Context aware vertical handover decision making in heterogeneous wireless networks." *IEEE Local Computer Network Conference*.IEEE, 2010.
- [45] Ahmed, Tansir, KyandoghereKyamakya, and Markus Ludwig. "Architecture of a context-aware vertical handover decision model and its performance analysis for GPRS-WiFi handover." *11th IEEE Symposium on Computers and Communications (ISCC'06)*. IEEE, 2006.
- [46] Stevens-Navarro, Enrique, Yuxia Lin, and Vincent WS Wong. "An MDP-based vertical handoff decision algorithm for heterogeneous wireless networks." *IEEE Transactions on Vehicular Technology* 57.2 (2008): 1243-1254.
- [47] Su Kyoung Lee, K. Sriram, Kyungsoo Kim, Jong Hyup Lee, Yoon Hyuk Kim and N. Golmie, "Vertical handoff decision algorithm providing optimized performance in heterogeneous wireless networks," in *Global Telecommunications Conference, 2007.GLOBECOM '07. IEEE*, 2007, pp. 5164-5169.
- [48] Stevens-Navarro, Enrique, and Vincent WS Wong. "Comparison between vertical handoff decision algorithms for heterogeneous wireless networks." *2006 IEEE 63rd vehicular technology conference*.Vol.2.IEEE, 2006.
- [49] Sgora, Aggeliki, Dimitrios D. Vergados, and PeriklisChatzimisios. "An access network selection algorithm for heterogeneous wireless environments." *The IEEE symposium on Computers and Communications*.IEEE, 2010.
- [50] Tran, Phuoc Nguyen, and Nadia Boukhatem. "Comparison of MADM decision algorithms for interface selection in heterogeneous wireless networks." *2008 16th international conference on software, telecommunications and computer networks*.IEEE, 2008.
- [51] Taniuchi, Kenichi, et al. "IEEE 802.21: Media independent handover: Features, applicability, and realization." *IEEE Communications Magazine* 47.1 (2009): 112-120.

- [52] Bari, Farooq, and Victor Leung. "Multi-attribute network selection by iterative TOPSIS for heterogeneous wireless access." *2007 4th IEEE consumer communications and networking conference*.IEEE, 2007.
- [53] Bari, Farooq, and Victor Leung. "Application of ELECTRE to network selection in a heterogeneous wireless network environment." *2007 IEEE Wireless Communications and Networking Conference*.IEEE, 2007.
- [54] Mohamed, Lahby, CharkaouiLeghris, and AdibAbdellah. "A hybrid approach for network selection in heterogeneous multi-access environments." *2011 4th IFIP International Conference on New Technologies, Mobility and Security*.IEEE, 2011.
- [55] Kosmides, Pavlos, AngelosRouskas, and Miltiades Anagnostou. "Network selection in heterogeneous wireless environments." *2011 18th International Conference on Telecommunications*.IEEE, 2011.
- [56] Song, Qingyang, and Abbas Jamalipour. "Network selection in an integrated wireless LAN and UMTS environment using mathematical modeling and computing techniques." *IEEE wireless communications* 12.3 (2005): 42-48.
- [57] Hsu, Chih-Cheng, et al. "ANSWER: Adaptive network selection in WLAN/UMTS environment." *International Conference on Embedded and Ubiquitous Computing*.Springer, Berlin, Heidelberg, 2007.
- [58] Opricovic, Serafim, and Gwo-HshiungTzeng. "Compromise solution by MCDM methods: A comparative analysis of VIKOR and TOPSIS." *European journal of operational research* 156.2 (2004): 445-455.
- [59] Wang, Tien-Chin, Jia-Ling Liang, and Chun-Yen Ho. "Multi-criteria decision analysis by using fuzzy VIKOR." *2006 International conference on service systems and service management*.Vol.2.IEEE, 2006.
- [60] Gallardo-Medina, Jesus Ruben, Ulises Pineda-Rico, and Enrique Stevens-Navarro. "VIKOR method for vertical handoff decision in beyond 3G wireless networks." *2009 6th International Conference on Electrical Engineering, Computing Science and Automatic Control (CCE)*.IEEE, 2009.
- [61] Martinez-Morales, Jose D., Ulises Pineda-Rico, and Enrique Stevens-Navarro. "Performance comparison between MADM algorithms for vertical handoff in 4G networks." *2010 7th International Conference on Electrical Engineering Computing Science and Automatic Control*.IEEE, 2010.

- [62] Lahby, Mohamed, LeghrisCherkaoui, and AbdellahAdib. "Network selection decision based on handover history in heterogeneous wireless networks." *arXiv preprint arXiv:1206.1587* (2012).
- [63] Lahby, Mohamed, LeghrisCherkaoui, and AbdellahAdib. "New multi access selection method based on mahalanobis distance." *Applied Mathematical Sciences* 6.53-56 (2012): 2745-2760.
- [64] Lahby, Mohamed, LeghrisCherkaoui, and AbdellahAdib. "New optimized network selection decision in heterogeneous wireless networks." *International Journal of Computer Applications* 54.16 (2012).
- [65] Lahby, Mohamed, AbdelbakiAttoui, and AbderrahimSekkaki. "An optimized vertical handover approach based on M-ANP and TOPSIS in heterogeneous wireless networks." *International Symposium on Ubiquitous Networking*. Springer, Singapore, 2016.
- [66] Kunarak, Sunisa, and RaungrongSuleesathira. "Predictive RSS with fuzzy logic based vertical handoff algorithm in heterogeneous wireless networks." *The 2010 International Conference on Advanced Technologies for Communications*. IEEE, 2010.
- [67] Yiping, Chen, and Yang Yuhang. "A new 4G architecture providing multimode terminals always best connected services." *IEEE Wireless Communications* 14.2 (2007): 36-41.
- [68] Taaghoul, Pouya, Apostolis K. Salkintzis, and Jay Iyer. "Seamless integration of mobile WiMAX in 3GPP networks." *IEEE Communications Magazine* 46.10 (2008): 74-85.
- [69] Lampropoulos, George, Apostolis K. Salkintzis, and Nikos Passas. "Media-independent handover for seamless service provision in heterogeneous networks." *IEEE Communications Magazine* 46.1 (2008): 64-71.
- [70] Golmie, Nada. "Seamless mobility: are we there yet?." *IEEE Wireless Communications* 16.4 (2009): 12-13.
- [71] Falowo, Olabisi E., and H. Anthony Chan. "RAT selection for multiple calls in heterogeneous wireless networks using modified topsis group decision making technique." *2011 IEEE 22nd International Symposium on Personal, Indoor and Mobile Radio Communications*. IEEE, 2011.
- [72] Martinez-Morales, Jose D., Ulises Pineda-Rico, and Enrique Stevens-Navarro. "Performance comparison between MADM algorithms for vertical handoff in

- 4G networks." *2010 7th International Conference on Electrical Engineering Computing Science and Automatic Control*.IEEE, 2010.
- [73]Zhu, Fang, and Janise McNair. "Optimizations for vertical handoff decision algorithms." *2004 IEEE Wireless Communications and Networking Conference (IEEE Cat.No. 04TH8733)*.Vol. 2.IEEE, 2004.
- [74] Kassar, Meriem, Brigitte Kervella, and Guy Pujolle. "An overview of vertical handover decision strategies in heterogeneous wireless networks." *Computer communications* 31.10 (2008): 2607-2620.
- [75] Akyildiz, Ian F., et al. "Mobility management in next-generation wireless systems." *Proceedings of the IEEE* 87.8 (1999): 1347-1384.
- [76]Akyildiz, Ian F., Jiang Xie, and ShantidevMohanty."A survey of mobility management in next-generation all-IP-based wireless systems." *IEEE Wireless communications* 11.4 (2004): 16-28.
- [77]Sun, Junzhao, Douglas P. Howie, and Jaakko J. Sauvola. "Mobility management techniques for the next-generation wireless networks." *Wireless and Mobile Communications*.Vol. 4586.International Society for Optics and Photonics, 2001.
- [78] Swami, ErSunita, and ErSonikaSoni. "Vertical handover decision approaches in heterogeneous wireless networks using fuzzy logic system: a survey." *International Journal of Engineering Research and General Science* 3.3 (2015): 912-916.
- [79] Koundourakis, George, Dimitrios I. Axiotis, and Michael Theologou. "Network-based access selection in composite radio environments." *2007 IEEE Wireless Communications and Networking Conference*.IEEE, 2007.
- [80] Ormond, Olga, Philip Perry, and John Murphy. "Network selection decision in wireless heterogeneous networks." *2005 IEEE 16th International Symposium on Personal, Indoor and Mobile Radio Communications*.Vol.4.IEEE, 2005.
- [81] Song, Qingyang, and Abbas Jamalipour. "A network selection mechanism for next generation networks." *IEEE International Conference on Communications, 2005.ICC 2005*. 2005. Vol. 2. IEEE, 2005.
- [82] Stevens-Navarro, Enrique, Vincent WS Wong, and Yuxia Lin. "A vertical handoff decision algorithm for heterogeneous wireless networks." *2007 IEEE wireless communications and networking conference*.IEEE, 2007.

- [83] Wang, Ying, et al. "Vertical handover decision in an enhanced media independent handover framework." *2008 IEEE wireless communications and networking conference*.IEEE, 2008.
- [84] Horrich, Sana, Sana Ben Jamaa, and Philippe Godlewski. "Adaptive vertical mobility decision in heterogeneous networks." *2007 Third International Conference on Wireless and Mobile Communications (ICWMC'07)*. IEEE, 2007.
- [85] Niyato, Dusit, and EkramHossain. "A cooperative game framework for bandwidth allocation in 4G heterogeneous wireless networks." *2006 IEEE international conference on communications*.Vol.9.IEEE, 2006.
- [86] Haddad, Majed, et al. "A nash-stackelberg fuzzy q-learning decision approach in heterogeneous cognitive networks." *2010 IEEE Global Telecommunications Conference GLOBECOM 2010*.IEEE, 2010.
- [87] Zekri, Mariem, BadiJouaber, and DjamalZeghlache. "On the use of network QoS reputation for vertical handover decision making." *2010 IEEE GlobecomWorkshops*.IEEE, 2010.
- [88] Calvagna, Andrea, and Giuseppe Di Modica. "A user-centric analysis of vertical handovers." *Proceedings of the 2nd ACM international workshop on Wireless mobile applications and services on WLAN hotspots*. 2004.
- [89]Koundourakis, G.; Axiotis, D.I.; Theologou, M. Network-based access selection in composite radio environments. In *Proceedings of the 2007 IEEE Wireless Communications and Networking Conference, Hong Kong, China, 11–15 March 2007*; pp. 3877–3883.
- [90]Ormond, O.; Perry, P.; Murphy, J. Network selection decision in wireless heterogeneous networks. In *Proceedings of the 2005 IEEE 16th International Symposium on Personal, Indoor and Mobile Radio Communications, Berlin, Germany, 11–14 September 2005*; Volume 4, pp. 2680–2684.
- [91]Song, Q.; Jamalipour, A.A network selection mechanism for next generation networks. In *Proceedings of the IEEE International Conference on Communications, ICC 2005, Seoul, Korea, 16–20 May 2005*; Volume 2, pp. 1418–1422.
- [92]Stevens-Navarro, E.; Wong, V.W.; Lin, Y.A vertical handoff decision algorithm for heterogeneous wireless networks. In *Proceedings of the 2007 IEEE*

- Wireless Communications and Networking Conference, Hong Kong, China, 11–15 March 2007; pp. 3199–3204.
- [93]Wang, Y.; Yuan, J.; Zhou, Y.; Li, G.; Zhang, P. Vertical handover decision in an enhanced media independent handover framework.In Proceedings of the 2008 IEEE Wireless Communications and Networking Conference, Las Vegas, NV, USA, 31 March–3 April 2008; pp. 2693–2698.
- [94]Horrich, S.; Jamaa, S.B.; Godlewski, P. Adaptive vertical mobility decision in heterogeneous networks. In Proceedings of the 2007 Third International Conference on Wireless and Mobile Communications (ICWMC'07), Guadeloupe, French Caribbean, 4–9 March 2007; pp.1–6.
- [95]Niyato, D.; Hossain, E.A cooperative game framework for bandwidth allocation in 4G heterogeneous wireless networks. In Proceedings of the 2006 IEEE International Conference on Communication, Istanbul, Turkey, 11–15 June 2006; Volume 9, pp. 4357–4362.
- [96]Haddad, M.; Altman, Z.; Elayoubi, S.E.; Altman, E.A nash-stackelberg fuzzy q-learning decision approach in heterogeneous cognitive networks. In Proceedings of the 2010 IEEE Global Telecommunications Conference GLOBECOM 2010, Miami, FL, USA, 6–10 December 2010; pp. 1–6.
- [97]Zekri, M.; Jouaber, B.; Zeghlache, D.On the use of network QoS reputation for vertical handover decision making. In Proceedings of the 2010 IEEE Globecom Workshops, Miami, FL, USA, 6–10 December2010; pp. 2006–2011.
- [98] El-Sayed, Hesham, et al. "Quality of service models for heterogeneous networks: overview and challenges." *annals of telecommunications-Annales des télécommunications* 63.11 (2008): 639-668.
- [99] Liu, Sheng-mei, et al. "A simple additive weighting vertical handoff algorithm based on SINR and AHP for heterogeneous wireless networks." *2010 International Conference on Intelligent Computation Technology and Automation*.Vol.1.IEEE, 2010.
- [100] Chamodrakas, Ioannis, and DrakoulisMartakos."A utility-based fuzzy TOPSIS method for energy efficient network selection in heterogeneous wireless networks." *Applied Soft Computing* 11.4 (2011): 3734-3743.
- [101]Nguyen-Vuong, Quoc-Thinh, YacineGhamri-Doudane, and NazimAgoulmine."On utility models for access network selection in wireless

- heterogeneous networks." *NOMS 2008-2008 IEEE Network Operations and Management Symposium*. IEEE, 2008.
- [102] Quoc-Thinh Nguyen-Vuong, Nazim Agoulmine, El Hadi Cherkaoui, and Laura Toni (2013), —Multi-criteria Optimization of Access Selection to improve the Quality of Experience in Heterogeneous Wireless Access networks, *IEEE Transactions on Vehicular Technology*, 62(4), pp. 1785-1800.
- [103] Wang, Lusheng, and Geng-Sheng Kuo. "Mathematical modeling for network selection in heterogeneous wireless networks—A tutorial." *IEEE Communications Surveys & Tutorials* 15.1 (2012): 271-292.
- [104] Kosmides, Pavlos, Angelos Rouskas, and Miltiades Anagnostou. "Utility-based RAT selection optimization in heterogeneous wireless networks." *Pervasive and Mobile Computing* 12 (2014): 92-111.
- [105] Sun, Lei, Jianquan Wang, and Zhaobiao Lv. "An adaptive network selection scheme in 4g composite radio environments." *2012 8th International Conference on Wireless Communications, Networking and Mobile Computing*. IEEE, 2012.
- [106] Trestian, Ramona, Olga Ormond, and Gabriel-Miro Muntean. "Enhanced power-friendly access network selection strategy for multimedia delivery over heterogeneous wireless networks." *IEEE Transactions on Broadcasting* 60.1 (2014): 85-101.
- [107] Fang, Yuguang. "Movement-based mobility management and trade off analysis for wireless mobile networks." *IEEE Transactions on Computers* 52.6 (2003): 791-803.
- [108] Zhu, Yanmin, Lei Ni, and Bo Li. "Exploiting mobility patterns for inter-technology handover in mobile environments." *Computer communications* 36.2 (2013): 203-210.
- [109] Nguyen-Vuong, Quoc-Thinh, Nazim Agoulmine, and Yacine Ghamri-Doudane. "Terminal-controlled mobility management in heterogeneous wireless networks." *IEEE Communications Magazine* 45.4 (2007): 122-129.
- [110] Hasib, Abdul, and Abraham O. Fapojuwo. "Analysis of common radio resource management scheme for end-to-end QoS support in multiservice heterogeneous wireless networks." *IEEE Transactions on Vehicular Technology* 57.4 (2008): 2426-2439.

- [111] Lee, Wonjun, et al. "Movement-aware vertical handoff of WLAN and mobile WiMAX for seamless ubiquitous access." *IEEE Transactions on Consumer Electronics* 53.4 (2007): 1268-1275.
- [112] Meng, Yun, et al. "An adaptive network selection scheme based on the combination of user mobility and traffic load." *2012 IEEE 23rd International Symposium on Personal, Indoor and Mobile Radio Communications-(PIMRC)*.IEEE, 2012.
- [113] Ali, Tariq, and Mohammad Saquib."Performance evaluation of WLAN/cellular media access for mobile voice users under random mobility models." *IEEE transactions on wireless communications* 10.10 (2011): 3241-3255.
- [114] Kumar, Abhinav, Ranjan K. Mallik, and Robert Schober."A probabilistic approach to modeling users' network selection in the presence of heterogeneous wireless networks." *IEEE Transactions on Vehicular Technology* 63.7 (2014): 3331-3341.
- [115] Mu, Dawei, XianleiGe, and Rong Chai."Vertical handoff modeling and simulation in VANET scenarios." *2013 International Conference on Wireless Communications and Signal Processing*.IEEE, 2013.
- [116] Wang, Hao, David I. Laurenson, and Jane Hillston."A general performance evaluation framework for network selection strategies in 3G-WLAN interworking networks." *IEEE Transactions on Mobile Computing* 12.5 (2012): 868-884.
- [117] Hassane, Abdoul Aziz Issaka, Li Renfa, and ZengFanzi. "Handover necessity estimation for 4G heterogeneous networks." *arXiv preprint arXiv:1202.1733* (2012).
- [118] Hussain, Riaz, et al. "Vertical handover necessity estimation based on a new dwell time prediction model for minimizing unnecessary handovers to a WLAN cell." *Wireless personal communications* 71.2 (2013): 1217-1230.
- [119] Marques, Hugo, et al. "Simulation of 802.21 handovers using ns-2." *Journal of Computer Systems, Networks, and Communications* 2010 (2010).
- [120] Yoo, Sang-Jo, David Cypher, and Nada Golmie."Timely effective handover mechanism in heterogeneous wireless networks." *Wireless Personal Communications* 52.3 (2010): 449-475.

- [121] Khattab, Omar, and Omar Alani. "Survey on media independent handover (MIH) approaches in heterogeneous wireless networks." *European Wireless 2013; 19th European Wireless Conference*. VDE, 2013.
- [122] Ghahfarokhi, Behrouz Shahgholi, and Naser Movahhedinia. "A survey on applications of IEEE 802.21 Media Independent Handover framework in next generation wireless networks." *Computer Communications* 36.10-11 (2013): 1101-1119.
- [123] Marquez-Barja, Johann, et al. "Evaluation of a technology-aware vertical handover algorithm based on the IEEE 802.21 standard." *2011 IEEE Wireless Communications and Networking Conference*. IEEE, 2011.
- [124] Song, Heecheol, et al. "Analysis of vertical handover latency for IEEE 802.21-enabled Proxy Mobile IPv6." *13th International Conference on Advanced Communication Technology (ICACT2011)*. IEEE, 2011.
- [125] Ahuja, Kiran, Brahmjit Singh, and Rajesh Khanna. "Network selection algorithm based on link quality parameters for heterogeneous wireless networks." *Optik* 125.14 (2014): 3657-3662.
- [126] Khalil, Abdelaziz, et al. "Tradeoff analysis for vertical handover between UMTS-WiFi enhanced by IEEE802. 21." *2013 IEEE International RF and Microwave Conference (RFM)*. IEEE, 2013.
- [127] Omheni, Nouri, et al. "A MIH-based approach for best network selection in heterogeneous wireless networks." *Journal of Systems and Software* 92 (2014): 143-156.
- [128] Abdullah, Radhwan M., et al. "A network selection algorithm based on enhanced access router discovery in heterogeneous wireless networks." *Wireless personal communications* 77.3 (2014): 1733-1750.
- [129] Singhrova, Anita, and Nupur Prakash. "Vertical handoff decision algorithm for improved quality of service in heterogeneous wireless networks." *IET communications* 6.2 (2012): 211-223.
- [130] Charilas, Dimitris E., Athanasios D. Panagopoulos, and Ourania I. Markaki. "A unified network selection framework using principal component analysis and multi attribute decision making." *Wireless personal communications* 74.1 (2014): 147-165.

- [131] Kaleem, Faisal, et al. "A fuzzy preprocessing module for optimizing the access network selection in wireless networks." *Advances in Fuzzy Systems* 2013 (2013).
- [132] Muñoz, P., Raquel Barco, and Isabel de la Bandera. "Optimization of load balancing using fuzzy Q-learning for next generation wireless networks." *Expert systems with applications* 40.4 (2013): 984-994.
- [133] Salih, Yass K., et al. "A proactive fuzzy-guided link labeling algorithm based on MIH framework in heterogeneous wireless networks." *Wireless personal communications* 75.4 (2014): 2495-2511.
- [134] Kantubukta, Vasu, et al. "Energy and quality of service aware FUZZY-technique for order preference by similarity to ideal solution based vertical handover decision algorithm for heterogeneous wireless networks." *IET networks* 2.3 (2013): 103-114.
- [135] Shen, Yulong, et al. "The QoS-Ensured Vertical Handoff Decision in Heterogeneous Wireless Networks." *J. Inf. Sci. Eng.* 30.3 (2014): 875-893.
- [136] Wang, Chien-Hua, Sheng-Hsing Liu, and Chin-Tzong Pang. "Using genetic algorithm improve the consistency of fuzzy analytic hierarchy process." *The 6th International Conference on Soft Computing and Intelligent Systems, and The 13th International Symposium on Advanced Intelligence Systems*. IEEE, 2012.
- [137] Zhang, Ding, et al. "An access selection algorithm based on GRA integrated with FAHP and entropy weight in hybrid wireless environment." *2013 7th International conference on application of information and communication technologies*. IEEE, 2013.
- [138] Lahby, Mohamed, LeghrisCherkaoui, and AbdellahAdib. "Network selection algorithm based on diff-ahp and topsis in heterogeneous wireless networks." *2012 International Conference on Multimedia Computing and Systems*. IEEE, 2012.
- [139] Liu, Bin, et al. "AHP and game theory based approach for network selection in heterogeneous wireless networks." *2014 IEEE 11th Consumer Communications and Networking Conference (CCNC)*. IEEE, 2014.
- [140] Verma, Rajiv, and NirajPratap Singh. "GRA based network selection in heterogeneous wireless networks." *Wireless personal communications* 72.2 (2013): 1437-1452.

- [141] Mehbodniya, Abolfazl, et al. "Wireless network access selection scheme for heterogeneous multimedia traffic." *IET networks* 2.4 (2013): 214-223.
- [142] Jos'e D. Mart'inez-Morales, Ulises Pineda-Rico, and Enrique Stevens-Navarro (2010), Performance Comparison between MADM Algorithms for Vertical Handoff in 4G networks, Proc. of 7th International Conference on Electrical Engineering, Computing Science and Automatic Control, Tuxtla Gutiérrez, Chiapas, México, pp.309-314.
- [143] Lahby, Mohamed, LeghrisCherkaoui, and AbdellahAdib."New multi access selection method using differentiated weight of access interface." *2012 International Conference on Communications and Information Technology (ICCIT)*.IEEE, 2012.
- [144] Mehbodniya, Abolfazl, et al. "A fuzzy MADM ranking approach for vertical mobility in next generation hybrid networks." *2012 IV International Congress on Ultra Modern Telecommunications and Control Systems*.IEEE, 2012.
- [145] Zhang, Lina, and Qi Zhu. "Multiple attribute network selection algorithm based on AHP and synergetic theory for heterogeneous wireless networks." *Journal of Electronics (China)* 31.1 (2014): 29-40.
- [146] De Miranda Rios, Vin'cius, Claudio de Castro Monteiro, and VaniceCanutoCunha."Alternatives to network selection in heterogeneous wireless environments." *16th International Conference on Advanced Communication Technology*.IEEE, 2014.
- [147] Song, Qingyang, and Abbas Jamalipour."Network selection in an integrated wireless LAN and UMTS environment using mathematical modeling and computing techniques." *IEEE wireless communications* 12.3 (2005): 42-48.
- [148] Song, Qingyang, and Abbas Jamalipour."A quality of service negotiation-based vertical handoff decision scheme in heterogeneous wireless systems." *European Journal of Operational Research* 191.3 (2008): 1059-1074.
- [149] Ju, Honghao, et al. "Adaptive cross-network cross-layer design in heterogeneous wireless networks." *IEEE Transactions on Wireless Communications* 14.2 (2014): 655-669.
- [150] Wu, Qihui, et al. "Traffic-aware online network selection in heterogeneous wireless networks." *IEEE Transactions on Vehicular Technology* 65.1 (2015): 381-397.

- [151] Sarma, Abhijit, SandipChakraborty, and Sukumar Nandi. "Deciding handover points based on context-aware load balancing in a WiFi-WiMAX heterogeneous network environment." *IEEE Transactions on Vehicular Technology* 65.1 (2015): 348-357.
- [152] PoojaDhand, Sumit Mittal, and GeetaSharma. An intelligent hando_ optimization algorithm for network selection in heterogeneous networks. *International Journal of Information Technology*, pages 1-12, 2021.
- [153]. Jiani Sun, ZhihongQian, Xin Wang, and XueWang. Es-dqn-based vertical hando_ algorithm for heterogeneous wireless networks. *IEEE Wireless Communications Letters*, 9(8):1327-1330, 2020.
- [154]. Enrique Stevens-Navarro, Yuxia Lin, and Vincent W. S. Wong. Anmdp-based vertical handoff decision algorithm for heterogeneous wireless networks. *IEEE Transactions on Vehicular Technology*, 57(2):1243-1254, 2008.
- [155]. Taehoon Kim, Sang-wook Han, and Youngnam Han. A qos-aware vertical handoff algorithm based on service history information. *IEEE Communications Letters*, 14(6):527-529, 2010.
- [156]. Bingtao Yang, Xue Wang, and ZhihongQian. A multi-armed bandit model-based vertical handoff algorithm for heterogeneous wireless networks. *IEEE Communications Letters*, 22(10):2116-2119, 2018.
- [157]. Zhang, Jinzhong, et al. "A Novel Enhanced Arithmetic Optimization Algorithm for Global Optimization." *IEEE Access* 10 (2022): 75040-75062.
- [158] .Zhu, Anqi, et al. "Adaptive Access Selection Algorithm for Multi-Service in 5G Heterogeneous Internet of Things." *IEEE Transactions on Network Science and Engineering* 9.3 (2022): 1630-1644.
- [159].Zhu, Anqi, et al. "Adaptive multi-access algorithm for multi-service edge users in 5G ultra-dense heterogeneous networks." *IEEE Transactions on Vehicular Technology* 70.3 (2021): 2807-2821.
- [160] .Khan, BenishSharfeen, et al. "Artificial Neural Network-Based Joint Mobile Relay Selection and Resource Allocation for Cooperative Communication in Heterogeneous Network." *IEEE Systems Journal* 16.4 (2022): 5809-5820.
- [161] PoojaDhand, Sumit Mittal, and GeetaSharma. An intelligent hando_ optimization algorithm for network selection in heterogeneous networks. *International Journal of Information Technology*, pages 1-12, 2021.

- [162]. Jiani Sun, ZhihongQian, Xin Wang, and XueWang. Es-dqn-based vertical handoff algorithm for heterogeneous wireless networks. *IEEE Wireless Communications Letters*, 9(8):1327-1330, 2020.
- [163]. Chkirbene, Zina, et al. "Deep reinforcement learning for network selection over heterogeneous health systems." *IEEE Transactions on Network Science and Engineering* 9.1 (2021): 258-270.
- [164] Hussain, Riaz, et al. "Vertical handover necessity estimation based on a new dwell time prediction model for minimizing unnecessary handovers to a WLAN cell." *Wireless personal communications* 71.2 (2013): 1217-1230.
- [165]. Zheng, Jinkai, et al. "Digital Twin Empowered Heterogeneous Network Selection in Vehicular Networks With Knowledge Transfer." *IEEE Transactions on Vehicular Technology* 71.11 (2022): 12154-12168.
- [166]. Tubishat, Mohammad, et al. "Dynamic butterfly optimization algorithm for feature selection." *IEEE Access* 8 (2020): 194303-194314.
- [167]. Feng, Shaohan, et al. "Dynamic model for network selection in next generation HetNets with memory-affecting rational users." *IEEE Transactions on Mobile Computing* 20.4 (2020): 1365-1379.
- [168]. Wang, Feng, and Vincent KN Lau. "Dynamic RAT Selection and Transceiver Optimization for Mobile-Edge Computing Over Multi-RAT Heterogeneous Networks." *IEEE Internet of Things Journal* 9.20 (2022): 20532-20546.
- [169]. Moons, Bart, et al. "Efficient vertical handover in heterogeneous low-power wide-area networks." *IEEE Internet of Things Journal* 7.3 (2019): 1960-1973.
- [170]. Narmanlioglu, Omer, and Murat Uysal. "Event-triggered adaptive handover for centralized hybrid VLC/MMW networks." *IEEE Transactions on Communications* 70.1 (2021): 455-468.
- [171]. Taehoon Kim, Sang-wook Han, and Youngnam Han. A qos-aware vertical handoff algorithm based on service history information. *IEEE Communications Letters*, 14(6):527-529, 2010.
- [172]. Xie, Jianli, Wenjuan Gao, and Cuiran Li. "Heterogeneous network selection optimization algorithm based on a Markov decision model." *China Communications* 17.2 (2020): 40-53.
- [173]. Ma, Mingfang, et al. "Intelligent network selection algorithm for multiservice users in 5G heterogeneous network system: Nash Q-learning method." *IEEE Internet of Things Journal* 8.15 (2021): 11877-11890.

- [174].Zeshan, Arooba, and TuncerBaykas."Location aware vertical handover in a VLC/WLAN hybrid network." *IEEE Access* 9 (2021): 129810-129819.
- [175].Allahham, MhdSaria, et al. "Multi-agent reinforcement learning for network selection and resource allocation in heterogeneous multi-RAT networks." *IEEE Transactions on Cognitive Communications and Networking* 8.2 (2022): 1287-1300.
- [176].Guo, Xiaoxue, et al. "Multiattribute Access Selection Algorithm for Heterogeneous Wireless Networks Based on Fuzzy Network Attribute Values." *IEEE Access* 10 (2022): 74071-74081.
- [177].Fan, Kexin, et al. "Network Selection Based on Evolutionary Game and Deep Reinforcement Learning in Space-Air-Ground Integrated Network." *IEEE Transactions on Network Science and Engineering* 9.3 (2022): 1802-1812.
- [178] Kaur, R., &Sood, R, Comprehensive study of Handoff Strategy: A Survey. *International Journal of Engineering and Computer Science*, 2(12), 3576-3579.
- [179]. Bingtao Yang, Xue Wang, and ZhihongQian.A multi-armed bandit model-based vertical handoff algorithm for heterogeneous wireless networks. *IEEE Communications Letters*, 22(10):2116-2119, 2018.
- [180] Noureddine, S. "An optimization approach for the satisfiability problem." *Applied Computing and Informatics* 11.1 (2015): 47-59.
- [181] Belić, Ernest, et al. "GPU-based online optimization of low voltage distribution network operation." *IEEE Transactions on Smart Grid* 8.3 (2017): 1460-1468.
- [182] Koppel, Alec, Brian M. Sadler, and Alejandro Ribeiro."Proximity without consensus in online multiagent optimization." *IEEE Transactions on Signal Processing* 65.12 (2017): 3062-3077.
- [183] Platonov, Anatoliy."Information theory and optimization of analog feedback communication systems." *2016 IEEE International Black Sea Conference on Communications and Networking (BlackSeaCom)*.IEEE, 2016.
- [184] Tang, Ming, et al. "Optimizations and economics of crowdsourced mobile streaming." *IEEE Communications Magazine* 55.4 (2017): 21-27.
- [185] Das, Sourav, et al. "Design-space exploration and optimization of an energy-efficient and reliable 3-D small-world network-on-chip." *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 36.5 (2016): 719-732.

- [186] Yan, Zheng, Jianchao Fan, and Jun Wang. "A collective neurodynamic approach to constrained global optimization." *IEEE transactions on neural networks and learning systems* 28.5 (2016): 1206-1215.
- [187] A.R. Parkinson, R.J. Balling, J.D. Hedengren, Optimization Methods for Engineering Design: Applications and Theory, fifth ed., Brigham Young University, 2013.
- [188] Yang, Xin-She. "A new metaheuristic bat-inspired algorithm." *Nature inspired cooperative strategies for optimization (NICSO 2010)*. Springer, Berlin, Heidelberg, 2010.65-74.
- [189] Rini, Dian Palupi, SitiMariyamShamsuddin, and SitiSophiyatiYuhaniz. "Particle swarm optimization: technique, system and challenges." *International journal of computer applications* 14.1 (2011): 19-26.
- [190] Storn, Rainer, and Kenneth Price. "Differential evolution—a simple and efficient heuristic for global optimization over continuous spaces." *Journal of global optimization* 11.4 (1997): 341-359.
- [191] Storn, Rainer, and Kenneth Price. "Differential evolution—a simple and efficient heuristic for global optimization over continuous spaces." *Journal of global optimization* 11.4 (1997): 341-359.
- [192] Kefayat, M., A. LashkarAra, and SA NabaviNiaki. "A hybrid of ant colony optimization and artificial bee colony algorithm for probabilistic optimal placement and sizing of distributed energy resources." *Energy Conversion and Management* 92 (2015): 149-161.
- [193] Kirkpatrick, Scott, C. Daniel Gelatt, and Mario P. Vecchi. "Optimization by simulated annealing." *science* 220.4598 (1983): 671-680.
- [194] Yang, Xin-She. *Nature-inspired optimization algorithms*. Academic Press, 2020.
- [195] Solihin, Mahmud Iwan, and MohdFauziZanil. "Performance comparison of Cuckoo search and differential evolution algorithm for constrained optimization." *IOP conference series: materials science and engineering*. Vol. 160.No. 1.IOP Publishing, 2016.
- [196] Adnan, MdAkhtaruzzaman, and M. A. Razzaque. "A comparative study of particle swarm optimization and Cuckoo search techniques through problem-specific distance function." *2013 international conference of information and communication technology (ICoICT)*.IEEE, 2013.

- [197] Baskan, Ozgur. "Determining optimal link capacity expansions in road networks using cuckoo search algorithm with lévy flights." *Journal of Applied Mathematics* 2013 (2013).
- [198] Buaklee, Wirote, and KomsanHongesombut. "Optimal DG allocation in a smart distribution grid using cuckoo search algorithm." *2013 10th International Conference on Electrical Engineering/Electronics, Computer, Telecommunications and Information Technology*. IEEE, 2013.
- [199].Zhang, Cheng-Xu, et al. "An improved cuckoo search algorithm utilizing nonlinear inertia weight and differential evolution for function optimization problem." *IEEE Access* 9 (2021): 161352-161373.
- [200].Wang, Likun, et al. "Cuckoo search algorithm for multi-objective optimization of transient starting characteristics of a self-starting HVPMSM." *IEEE Transactions on Energy Conversion* 36.3 (2020): 1861-1872.
- [201]. Gao, Shuzhi, et al. "Multi-strategy adaptive cuckoo search algorithm." *IEEE Access* 7 (2019): 137642-137655.
- [202].Bello-Salau, Habeeb, et al. "New discrete cuckoo search optimization algorithms for effective route discovery in IoT-based vehicular ad-hoc networks." *IEEE Access* 8 (2020): 145469-145488.
- [203]. Jiamei Chen, Yao Wang, Yufeng Li, and ErshenWang. Qoe-aware intelligent vertical handoff scheme over heterogeneous wireless access networks. *IEEE Access*, 6:38285-38293, 2018.
- [204].Xie, Jianli, WenjuanGao, and Cuiran Li. "Heterogeneous network selection optimization algorithm based on a Markov decision model." *China Communications* 17.2 (2020): 40-53.
- [205] John, H. (1992). *Adaptation in natural and artificial systems*. USA: MITCognet.
- [206]. Vijayanand, R., and D. Devaraj. "A novel feature selection method using whale optimization algorithm and genetic operators for intrusion detection system in wireless mesh network." *IEEE Access* 8 (2020): 56847-56854.
- [207].Cui, Xuerong, et al. "Improved genetic algorithm to optimize the Wi-Fi indoor positioning based on artificial neural network." *IEEE Access* 8 (2020): 74914-74921.
- [208]. SandeepVerma, NeetuSood, and Ajay Kumar Sharma. Genetic algorithm-based optimized cluster head selection for single and multiple data sinks in heterogeneous wireless sensor network. *Applied Soft Computing*, 85:105788, 2019.